# SAFETY DATA SHEET

novatio

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

# SAFETY CLEAN GEL

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

: SAFETY CLEAN GEL Product name **Registration number REACH** Product type REACH

: Not applicable (mixture)

#### : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

#### 1.2.2 Uses advised against

No uses advised against known

### 1.3. Details of the supplier of the safety data sheet

### Supplier of the safety data sheet

Novatio\* Industrielaan 5B B-2250 Olen +32 14 25 76 40 **▲** +32 14 22 02 66 info@novatio.be \*NOVATIO is a registered trademark of Novatech International N.V.

#### Manufacturer of the product

Novatech International N.V. Industrielaan 5B B-2250 Olen +32 14 85 97 37 ₲ +32 14 85 97 38 info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) : +32 14 58 45 45 (BIG)

# SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008					
	Class	Category	Hazard statements		
	Aerosol	category 1	H222: Extremely flammable aerosol.		
	Aerosol	category 1	H229: Pressurised container: May burst if heated.		
	STOT SE	category 3	H336: May cause drowsiness or dizziness.		

H412: Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Revision number: 0100

Aquatic Chronic



category 3

Signal word H-statements	Danger		
H222 H229	Extremely flammable aerosol. Pressurised container: May burst if heated.		
H336 H412	May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects		
P-statements P210 P211 P251 P261		en flames and other ignition sources. No smoking.	
by: Brandweerinformal che Schoolstraat 43 A, B ww.big.be zw for revision: 3.2, 9, 12	tiecentrum voor gevaarlijke stoffen vzw (BIG) -2440 Geel	Publication date: 2020-07-24 Date of revision: 2022-04-20	878-16239-033-en

Created by iijke sto Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be © BIG vzw Reason for revision: 3.2, 9, 12

BIG number: 66150

P304 + P340 P410 + P412

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

Supplemental information FUH066

Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119471843-32	927-241-2	C≤70%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412 EUH066	(1)(10)	UVCB	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
butane 01-2119474691-32	106-97-8 203-448-7	C≤30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(21) 1,3-butadiene < 0.1%

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

# SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eve contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

#### 4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms After inhalation: Dizziness. Drowsiness. After skin contact: ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin. After eve contact: No effects known. After ingestion: No effects known. 4.2.2 Delayed symptoms No effects known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 3.2, 9, 12

# SECTION 5: Firefighting measures

## 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher. Major fire: Quantities of water.

#### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

#### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

# SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

#### See section 8.2

6.1.2 Protective equipment for emergency responders Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

# See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

#### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Avoid prolonged and repeated contact with skin. Remove contaminated clothing immediately.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Keep out of direct sunlight. Keep container in a well-ventilated place. Fireproof storeroom. Meet the legal requirements.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

### 7.2.3 Suitable packaging material:

Aerosol

7.2.4 Non suitable packaging material: No data available

# 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1 Occupational exposure

### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

## Belgium

Reason for revision: 3.2, 9, 12

Publication date: 2020-07-24 Date of revision: 2022-04-20

Revision number: 0100

BIG number: 66150

	outane	Short time value			980 ppm
		Short time value			2370 mg/n
Hydrocarbures aliphatiques (Alcanes C1-C3)	s sous forme gazeuse:	Time-weighted average	e exposure limit 8 h		1000 ppm
France					
n-Butane		Time-weighted average réglementaire indicativ	e exposure limit 8 h (VL: Valeur no ⁄e)	n	800 ppm
		Time-weighted average réglementaire indicativ	e exposure limit 8 h (VL: Valeur no re)	n	1900 mg/n
Germany			-,		-
Butan		Time-weighted average	e exposure limit 8 h (TRGS 900)		1000 ppm
			e exposure limit 8 h (TRGS 900)		2400 mg/r
Propan		Time-weighted average	e exposure limit 8 h (TRGS 900)		1000 ppm
			e exposure limit 8 h (TRGS 900)		1800 mg/r
Austria					
Butan (beide Isomeren): n-E 600a)	Butan (R 600) Isobutan (R	Tagesmittelwert (MAK)	)		800 ppm
		Tagesmittelwert (MAK)	)		1900 mg/n
		Kurzzeitwert 60(Mow)	3x (MAK)		1600 ppm
		Kurzzeitwert 60(Mow)	Зх (МАК)		3800 mg/n
					4000
Propan (R 290)		Tagesmittelwert (MAK)			1000 ppm
		Tagesmittelwert (MAK)			1800 mg/r
		Kurzzeitwert 60(Mow)			2000 ppm
		Kurzzeitwert 60(Mow)	3x (MAK)		3600 mg/r
UK		i			
Butane		Time-weighted average (EH40/2005))	e exposure limit 8 h (Workplace ex	posure limit	600 ppm
		Time-weighted average (EH40/2005))	e exposure limit 8 h (Workplace ex	posure limit	1450 mg/r
		Short time value (Work	place exposure limit (EH40/2005)	)	750 ppm
		Short time value (Work	place exposure limit (EH40/2005)	)	1810 mg/r
USA (TLV-ACGIH)					
Butane, isomers b) National biological limit va If limit values are applicable ar	ilues nd available these will be listed	Short time value (TLV -	Adopted Value)		1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable an 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane	nd available these will be listed vill be listed below. In using the substance or mixto le and available these will b es, isoalkanes, cyclics, < 2% aro	d below. <b>ure as intended</b> be listed below.		Domonia	1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable an 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL)	nd available these will be listed vill be listed below. en using the substance or mixto le and available these will b es, isoalkanes, cyclics, < 2% aro Type	d below. ure as intended be listed below. omatics	Value	Remark	1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable at 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane	nd available these will be listed vill be listed below. en using the substance or mixto le and available these will b es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef	d below. <b>ure as intended</b> be listed below. <u>omatics</u> ffects inhalation	Value 871 mg/m³	Remark	1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable ar 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL	nd available these will be listed vill be listed below. en using the substance or mixtu le and available these will b es, isoalkanes, cyclics, < 2% aro <u>Type</u> Long-term systemic ef ation	d below. <b>ure as intended</b> be listed below. <u>omatics</u> ffects inhalation ffects dermal	Value	Remark	1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable and 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General popula hydrocarbons, C9-10, n-alkane	nd available these will be listed vill be listed below. en using the substance or mixtu- le and available these will b es, isoalkanes, cyclics, < 2% aro Long-term systemic ef Long-term systemic ef ation es, isoalkanes, cyclics, < 2% aro	d below. <b>ure as intended</b> be listed below. <u>omatics</u> ffects inhalation ffects dermal	Value 871 mg/m³ 77 mg/kg bw/day		1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable and 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General popula hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL)	nd available these will be listed vill be listed below. en using the substance or mixtu- le and available these will be es, isoalkanes, cyclics, < 2% aro Type Long-term systemic eff Long-term systemic eff tion es, isoalkanes, cyclics, < 2% aro Type	d below. ure as intended be listed below. <u>omatics</u> ffects inhalation ffects dermal <u>omatics</u>	Value 871 mg/m <sup>3</sup> 77 mg/kg bw/day Value	Remark	1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable and 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General popula hydrocarbons, C9-10, n-alkane	nd available these will be listed vill be listed below. en using the substance or mixtr le and available these will b es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef estion es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef Long-term systemic ef	d below. ure as intended be listed below. <u>omatics</u> ffects inhalation ffects dermal <u>omatics</u> ffects inhalation	Value         871 mg/m³         77 mg/kg bw/day         Value         185 mg/m³		1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable and 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General popula hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL)	nd available these will be listed vill be listed below. en using the substance or mixtu le and available these will b es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef tion es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef Long-term systemic ef Long-term systemic ef	d below. ure as intended be listed below. <u>omatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects inhalation</u> <u>ffects dermal</u>	Value         871 mg/m³         77 mg/kg bw/day         Value         185 mg/m³         46 mg/kg bw/day		1000 ppm
Butane, isomers b) National biological limit va If limit values are applicable and 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General popula hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL)	nd available these will be listed vill be listed below. en using the substance or mixtr le and available these will b es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef estion es, isoalkanes, cyclics, < 2% aro Type Long-term systemic ef Long-term systemic ef	d below. ure as intended be listed below. <u>omatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects inhalation</u> <u>ffects inhalation</u> <u>ffects dermal</u>	Value         871 mg/m³         77 mg/kg bw/day         Value         185 mg/m³		1000 pp
Butane, isomers b) National biological limit va lf limit values are applicable an 2 Sampling methods If applicable and available it w 3 Applicable limit values whe lf limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL S Control banding If applicable and available xposure controls information in this section want exposure scenarios th 1 Appropriate engineering co Use spark-/explosionproof Keep away from ignition so 2 Individual protection measu	nd available these will be listed vill be listed below. en using the substance or mixtu- le and available these will be es, isoalkanes, cyclics, < 2% aroon Type Long-term systemic eff Long-term systemic eff Long-te	d below. ure as intended be listed below. <u>omatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects oral</u> applicable and available itified use. tem. Take precautions ag concentration in the air <b>ive equipment</b>	Value         871 mg/m³         77 mg/kg bw/day         Value         185 mg/m³         46 mg/kg bw/day         46 mg/kg bw/day         46 mg/kg bw/day         e, exposure scenarios are attac         gainst electrostatic charges. Ke         regularly.	Remark	c. Always us
Butane, isomers b) National biological limit va lf limit values are applicable an 2 Sampling methods If applicable and available it w 3 Applicable limit values whe If limit values are applicabl 4 Threshold values DNEL/DMEL - Workers hydrocarbons, C9-10, n-alkane Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL S Control banding If applicable and available xposure controls information in this section evant exposure scenarios th 1 Appropriate engineering co Use spark-/explosionproof Keep away from ignition so 2 Individual protection measu Avoid prolonged and repea	nd available these will be listed vill be listed below. en using the substance or mixtu le and available these will be es, isoalkanes, cyclics, < 2% aro Type Long-term systemic eff Long-term	d below. ure as intended be listed below. <u>omatics</u> <u>ffects inhalation</u> <u>ffects dermal</u> <u>ffects oral</u> applicable and available itified use. tem. Take precautions ag concentration in the air <b>ive equipment</b>	Value         871 mg/m³         77 mg/kg bw/day         Value         185 mg/m³         46 mg/kg bw/day         46 mg/kg bw/day         46 mg/kg bw/day         e, exposure scenarios are attac         gainst electrostatic charges. Ke         regularly.	Remark	c. Always us

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Head/neck protection. Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (aerosol)
Explosion limits	0.6 - 9.5 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	700 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	921 mm²/s ; 40 °C ; Liquid
Melting point	No data available in the literature
Boiling point	-45 °C - 166 °C ; Liquid
Relative vapour density	No data available in the literature
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.76 ; 20 °C ; Liquid
Absolute density	760 kg/m³ ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
рН	Not applicable (aerosol)

### 9.2. Other information

Evaporation rate

0.35 ; Butyl acetate ; Liquid

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

#### **Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

# 10.5. Incompatible materials

No data available.

#### 10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

# SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

#### Acute toxicity

SAFETY CLEAN GEL

No (test)data on the mixture available

Reason for revision: 3.2, 9, 12

Judgement is based on the relevant ingredients hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 15000 mg/kg bw			Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw		Rabbit (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 6.1 mg/l air	4 h	Rat (male / female)	Experimental value	

#### **Conclusion**

Not classified for acute toxicity

#### Corrosion/irritation

#### SAFETY CLEAN GEL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	0	Equivalent to OECD 405		24; 48; 72 hours	Rabbit		Single treatment without rinsing
Skin	0	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

#### **Conclusion**

Not classified as irritating to the respiratory system Not classified as irritating to the skin

Not classified as irritating to the eyes

#### Respiratory or skin sensitisation

#### SAFETY CLEAN GEL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	••••••	Observation time point	Species	Value determination	Remark
Skin	0	Equivalent to OECD 406			Guinea pig (female)	Read-across	

**Conclusion** 

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

#### Specific target organ toxicity

#### SAFETY CLEAN GEL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	· · · · · ·	Value determination
Oral (stomach tube)	NOAEL	EPA OPP 82-1	≥ 500 mg/kg bw/day		No adverse systemic effects	13 weeks (7 days / week)	Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 6000 mg/m³ air		No adverse systemic effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation			STOT SE cat.3		Drowsiness, dizziness			Literature study

#### Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

### Mutagenicity (in vitro)

### SAFETY CLEAN GEL

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: 3.2, 9, 12

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)		Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Read-across	

#### Mutagenicity (in vivo)

#### SAFETY CLEAN GEL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	Equivalent to OECD		Mouse (male / female)		Read-across
	474				

#### **Conclusion**

Not classified for mutagenic or genotoxic toxicity

#### Carcinogenicity

# SAFETY CLEAN GEL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

1	Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
e	exposure								
	Dermal	NOAEL	Carcinogenic	50 %	52 week(s)		No carcinogenic		Experimental value
L			toxicity study				effect		

#### **Conclusion**

Not classified for carcinogenicity

#### Reproductive toxicity

## SAFETY CLEAN GEL

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	- 0.	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEL		≥ 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEL		≥ 5220 mg/m³ air	10 days (6h / day)	Rat	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

#### **Toxicity other effects**

#### SAFETY CLEAN GEL

Classification is based on the relevant ingredients hydrocarbons. C9-10, n-alkanes, isoalkanes, cyclics. < 2% aromatics

			i	i de la companya de la	i i			
Route of	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
exposure								determination
					Skin dryness or			Literature study
					cracking			

#### **Conclusion**

Repeated exposure may cause skin dryness or cracking.

#### Chronic effects from short and long-term exposure

#### SAFETY CLEAN GEL

No effects known.

#### **11.2.** Information on other hazards

No evidence of endocrine disrupting properties

Reason for revision: 3.2, 9, 12

# SECTION 12: Ecological information

# 12.1. Toxicity

#### SAFETY CLEAN GEL

No (test)data on the mixture available

Classification is based on the relevant ingredients

#### hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	10 mg/l - 30 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	22 mg/l - 46 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOELR	OECD 201	< 1 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR		0.182 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		0.317 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Reproduction

#### **Conclusion**

Harmful to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

[	Method	Value	Duration	Value determination
[	OECD 301F		28 day(s)	Experimental value

### **Conclusion**

Water

Log Kow

Does not contain any not readily biodegradable component(s)

#### 12.3. Bioaccumulative potential

**Biodegradation water** 

#### SAFETY CLEAN GEL

0				
Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### BCF fishes

Parameter	Method		Value	Duration	Species		Value determination	
BCF BCFBAF v3.0		.00	6.91 l/kg - 1582.4		Pisces		QSAR	
			l/kg					
og Kow	g Kow							
Method R		Remark		Value		Temperature	Value determination	
				1.99 - 5.25			QSAR	

#### **Conclusion**

No straightforward conclusion can be drawn based upon the available numerical values

#### 12.4. Mobility in soil

hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Value determination
log Koc		4.16 - 5.88	QSAR

#### **Conclusion**

Contains component(s) that adsorb(s) into the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

#### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

#### 12.7. Other adverse effects

SAFETY CLEAN GEL

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Reason for revision: 3.2, 9, 12

#### **Ozone-depleting potential (ODP)**

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

#### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29\* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

#### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

# SECTION 14: Transport information

## Road (ADR)

14. <u>1. UN number</u>	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

#### Rail (RID)

14. <u>1</u> . UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)

#### Inland waterways (ADN)

Reason for revision: 3.2, 9, 12

Publication date: 2020-07-24 Date of revision: 2022-04-20

Revision number: 0100

14. <u>1</u> . UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)

# Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14. <u>4. Packing group</u>	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

# Air (ICAO-TI/IATA-DGR)

14. <u>1. UN number</u>			
UN number	1950		
14.2. UN proper shipping name			
Proper shipping name	aerosols, flammable		
14.3. Transport hazard class(es)			
Class	2.1		
14.4. Packing group			
Packing group			
Labels	2.1		
14.5. Environmental hazards			
Environmentally hazardous substance mark	no		
14.6. Special precautions for user			
Special provisions	A145		
Special provisions	A167		
Special provisions	A802		
Passenger and cargo transport			
Limited quantities: maximum net quantity per packaging	30 kg G		

Reason for revision: 3.2, 9, 12

	ety, health and enviror an legislation:	nmental regulations/legislation sp	ecific for the	e substance o	r mixture	
	content Directive 2010/75/E	11				
_	DC content		Remark			
	0.67 %		Keinark			
	80.128 g/l					
Direct	ive 2012/18/EU (Seveso III)		•			
	reshold values under norm	al circumstances				
Su	bstance or category		Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixtue the summation rule has to be applied for:
P3	b FLAMMABLE AEROSOLS		5000 (net)	50000 (net)	None	Flammability
				1		
≥3 REACI Co	0% aliphatic hydrocarbons H Annex XVII - Restriction ontains component(s) subject	on (EC) No 648/2004 and amendments of to restrictions of Annex XVII of Regulatio	n (EC) No 1907	/2006: restriction	ns on the man	ufacture, placing on the market
di	iu use of certain dangerous	substances, mixtures and articles. Designation of the substance, of the group of substances or of the mixture	Conditions of re	striction		
isoalkanes, cy	ns, C9-10, n-alkanes, yclics, < 2% aromatics	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 5.1. (d) hazard class 5.1.	<ol> <li>Shall not be used in:         <ul> <li>ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,</li> <li>tricks and jokes,</li> <li>games for one or more participants, or any article intended to be used as such, even v ornamental aspects,</li> <li>Articles not complying with paragraph 1 shall not be placed on the market.</li> <li>Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:                 <ul></ul></li></ul></li></ol>			
isoalkanes, cy <u>Nationa</u>	yclics, < 2% aromatics	category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	dispensers are intended for supply to the general public for entertainment and decorati purposes such as the following: — metallic glitter intended mainly for decoration,			
<u>SAFE</u> No	<u>TY CLEAN GEL</u> o data available					
	I legislation The Netherland	de la companya de la				

SAFETY CLEAN GEL

Waterbezwaarlijkheid

Z (2); Algemene Beoordelingsmethodiek (ABM)

#### **National legislation France**

SAFETY CLEAN GEL

# No data available

## National legislation Germany

51					
	agerklasse (TRGS510) 2B: Aerosolpackungen und Feuerzeuge				
	WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017			
hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	TA-Luft	5.2.5/I			

#### National legislation Austria

SAFETY CLEAN GEL

No data available

#### National legislation United Kingdom

SAFETY CLEAN GEL

No data available

# Other relevant data

No data available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2, 9, 12