



# Maintenance Spray

## H1

CLEANING, LUBRICATING AND PROTECTING

- ✓ For fine precision lubrication.
- ✓ Rust remover and protector for bolts and nuts.
- ✓ Repels water and moisture through rapid and high penetration capacity.



### Technical Info

- NSF registration number: Category H1. Compliant with: FDA, Titel 21, Sektion 178.3570.
- Free of: lead, animal fat and synthetic oils.
- Odour: typical.
- Operating temperature: -15°C to +110°C.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

### Packing

Maintenance Spray H1 - aerosol 400ml

232501000

### Product [MS1]

#### Characteristics

Maintenance Spray H1 combines high penetration capacity with rapid moisture displacement for use in all food processing companies. Maintenance Spray H1 loosens clamped screws, bolts, nuts, pipe fittings and connections and leaves a protective film that prevents rust and oxidation.

#### Applications

Suitable for all food processing companies.

- Stopping and preventing short circuits.
- Loosening rusted nuts, bolts, screws, valves, valves, ...
- Expelling moisture from control cabinets and electronic measuring equipment.
- Protecting against moisture from printed circuit boards, electrical contacts, sensors, switches, ...
- Re-shining stainless steel and chrome parts, protect tools and machines.
- Removing oil and tar stains, soak tar and old fats.
- Keeping operating levers, guides and rods of machines ready for operation.

### Use

- Shake before use.
- Spray application.
- Use the straw for less accessible places.



Lubricants