

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

NOVAFILL FLEX 2 ZWART

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : NOVAFILL FLEX 2 ZWART
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Primer

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements



Contains: butanone; acetone.

Signal word Danger

H-statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 2; 3; 8; 15

Revision number: 0700

Publication date: 2006-02-27

Date of revision: 2024-11-27

BIG number: 43175

1 / 25

NOVAFILL FLEX 2 ZWART

P251	Do not pierce or burn, even after use.
P280	Wear eye protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
Supplemental information	
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard
Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	25% ≤C<50%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
butanone 01-2119457290-43	78-93-3 201-159-0	10% ≤C<25%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
acetone 01-2119471330-49	67-64-1 200-662-2	10% ≤C<25%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
trizinc bis(orthophosphate) 01-2119485044-40	7779-90-0 231-944-3	2.5% ≤C<10%	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)	Constituent	M: 10 (Acute, ECHA (registration dossier)) M: 1 (Chronic, BIG)
n-butyl acetate 01-2119485493-29	123-86-4 204-658-1	2.5% ≤C<10%	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
2-methoxy-1-methylethyl acetate 01-2119475791-29	108-65-6 203-603-9	2.5% ≤C<10%	Flam. Liq. 3; H226 STOT SE 3; H336	(1)(2)(6)(10)	Constituent	

- (1) For H- and EUH-statements in full: see section 16
(2) Substance with a Community workplace exposure limit
(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dizziness. Drowsiness.

After skin contact:

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

2 / 25

NOVAFILL FLEX 2 ZWART

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

Gas/vapour heavier than air at 20°C. Avoid prolonged and repeated contact with skin.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Store in a cool area. Keep container in a well-ventilated place. Keep out of direct sunlight. Fireproof storeroom. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

NOVAFILL FLEX 2 ZWART

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	275 mg/m ³
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	550 mg/m ³
Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m ³
Butanone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	600 mg/m ³
	Short time value (Indicative occupational exposure limit value)	300 ppm
	Short time value (Indicative occupational exposure limit value)	900 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m ³
n-Butyl acetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	241 mg/m ³
	Short time value (Indicative occupational exposure limit value)	150 ppm
	Short time value (Indicative occupational exposure limit value)	723 mg/m ³

Belgium

2-Butanone	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	600 mg/m ³
	Short time value	300 ppm
	Short time value	900 mg/m ³
Acétate de 2-(1-méthoxy)propyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	275 mg/m ³
	Short time value	100 ppm
	Short time value	550 mg/m ³
Acétate de butyle, tous isomères: n-, iso, sec, tert	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	238 mg/m ³
	Short time value	150 ppm
	Short time value	712 mg/m ³
Acétone	Time-weighted average exposure limit 8 h	246 ppm
	Time-weighted average exposure limit 8 h	594 mg/m ³
	Short time value	492 ppm
	Short time value	1187 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m ³

NOVAFILL FLEX 2 ZWART

The Netherlands

1-Methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	550 mg/m ³
2-Butanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	197 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	590 mg/m ³
	Short time value (Public occupational exposure limit value)	300 ppm
	Short time value (Public occupational exposure limit value)	900 mg/m ³
Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m ³
	Short time value (Public occupational exposure limit value)	1000 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	495 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m ³
	Short time value (Public occupational exposure limit value)	781 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m ³
n-Butylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	241 mg/m ³
	Short time value (Public occupational exposure limit value)	150 ppm
	Short time value (Public occupational exposure limit value)	723 mg/m ³

France

Acétate de 2-méthoxy-1-méthyléthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	275 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	550 mg/m ³
Acétate de n-butyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	241 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	150 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	723 mg/m ³
Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m ³
Méthyléthylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	600 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	300 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	900 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m ³

NOVAFILL FLEX 2 ZWART

Germany

2-Methoxy-1-methylethylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	270 mg/m ³ (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm (1)
Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m ³ (2)
	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm (2)
Butanon	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	600 mg/m ³ (1)
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm (3)
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³ (3)
n-Butylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	300 mg/m ³ (4)
	Time-weighted average exposure limit 8 h (TRGS 900)	62 ppm (4)
Zink und seine anorganischen Verbindungen	Time-weighted average exposure limit 8 h (MAK)	0.1 mg/m ³ (5)
	Time-weighted average exposure limit 8 h (MAK)	2 mg/m ³ (6)

(1) UF: 1 (I)

(2) UF: 2 (I)

(3) UF: 8 (II)

(4) UF: 2 (I)

(5) Alveolengängige Fraktion; UF: I(4)

(6) Einatembare Fraktion; UF: I(2); Zinkchlorid: Kurzzeitkategorie I(1)

Austria

1-Methoxypropylacetat-2	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	275 mg/m ³
	Kurzzeitwert 5(Mow) 8x (MAK)	100 ppm
	Kurzzeitwert 5(Mow) 8x (MAK)	550 mg/m ³
Aceton	Tagesmittelwert (MAK)	500 ppm
	Tagesmittelwert (MAK)	1200 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	4800 mg/m ³
Butanon	Tagesmittelwert (MAK)	100 ppm
	Tagesmittelwert (MAK)	295 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	200 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	590 mg/m ³
Butylacetat alle Isomere (außer tert-Butylacetat): Isobutylacetat n-Butylacetat sec-Butylacetat	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	241 mg/m ³
	Kurzzeitwert Mow (MAK)	100 ppm
	Kurzzeitwert Mow (MAK)	480 mg/m ³
Dimethylether	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1910 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3820 mg/m ³

NOVAFILL FLEX 2 ZWART

UK

1-Methoxypropyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	274 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	548 mg/m ³
Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m ³
Butan-2-one (methyl ethyl ketone)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	899 mg/m ³
Butyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	150 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	724 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	966 mg/m ³
Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m ³

Ireland

2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	50 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	275 mg/m ³
	Short time value (Binding occupational exposure limit values)	100 ppm
	Short time value (Binding occupational exposure limit values)	550 mg/m ³
Acetone	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	500 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	1210 mg/m ³
Dimethyl ether	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	1000 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	1920 mg/m ³
Methyl ethyl ketone	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	200 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	600 mg/m ³
	Short time value (Binding occupational exposure limit values)	300 ppm
	Short time value (Binding occupational exposure limit values)	900 mg/m ³
n-Butyl acetate	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	50 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	241 mg/m ³
	Short time value (Binding occupational exposure limit values)	150 ppm
	Short time value (Binding occupational exposure limit values)	723 mg/m ³

USA (TLV-ACGIH)

Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Butyl acetates, all isomers	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
	Short time value (TLV - Adopted Value)	150 ppm
Dimethyl Ether	Time-weighted average exposure limit 8 h (WEEL)	1000 ppm
Methyl ethyl ketone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	75 ppm
	Short time value (TLV - Adopted Value)	150 ppm
Propylene Glycol Monomethyl Ether Acetate	Time-weighted average exposure limit 8 h (WEEL)	50 ppm

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

7 / 25

NOVAFILL FLEX 2 ZWART

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

2-Butanon (Methylethylketon) (2-Butanon)	Urin: expositionsende, bzw. schichtende	2 mg/l	
Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	

UK

Butan-2-one (butan-2-one)	Urine: post shift	70 µmol/L	
---------------------------	-------------------	-----------	--

USA (BEI-ACGIH)

Acetone (Acetone)	Urine: end of shift	25 mg/L	Nonspecific
Methyl ethyl ketone (Methyl ethyl ketone)	Urine: end of shift	2 mg/L	Nonspecific

8.1.2 Sampling methods

Product name	Test	Number
1-Methoxy-2-Propyl Acetate	OSHA	99
2-Butanone (MEK) (Methyl ethyl ketone)	NIOSH	2500
2-Butanone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
2-Butanone (Volatile Organic compounds)	NIOSH	2549
2-Butanone	NIOSH	2027
2-Butanone	OSHA	1004
Acetone (ketones I)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
Acetone	NIOSH	2027
Acetone	NIOSH	3900
Acetone	NIOSH	8319
Acetone	OSHA	69
Butyl acetate (Volatile Organic compounds)	NIOSH	2549
MEK	NIOSH	8002
Methyl Ethyl Ketone (ketones I)	NIOSH	2555
Methyl Ethyl Ketone	NIOSH	8319
n-Butyl Acetate (Esters I)	NIOSH	1450
n-Butyl Acetate	OSHA	1009
n-Butyl Acetate	OSHA	5000
Propylene glycol monomethyl ether acetate (glycol ethers)	NIOSH	2554
Zinc & Cpds (as Zn)	NIOSH	7030

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	600 mg/m ³	
	Acute systemic effects inhalation	900 mg/m ³	
	Long-term systemic effects dermal	1161 mg/kg bw/day	

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1210 mg/m ³	
	Acute local effects inhalation	2420 mg/m ³	
	Long-term systemic effects dermal	186 mg/kg bw/day	

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	300 mg/m ³	
	Acute systemic effects inhalation	600 mg/m ³	
	Long-term local effects inhalation	300 mg/m ³	
	Acute local effects inhalation	600 mg/m ³	
	Long-term systemic effects dermal	11 mg/kg bw/day	
	Acute systemic effects dermal	11 mg/kg bw/day	

2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	275 mg/m ³	
	Acute local effects inhalation	550 mg/m ³	
	Long-term systemic effects dermal	796 mg/kg bw	

DNEL/DMEL - General population

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

8 / 25

NOVAFILL FLEX 2 ZWART

butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	106 mg/m ³	
	Acute systemic effects inhalation	450 mg/m ³	
	Long-term systemic effects dermal	412 mg/kg bw/day	
	Long-term systemic effects oral	31 mg/kg bw/day	

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	200 mg/m ³	
	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects oral	62 mg/kg bw/day	

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	35.7 mg/m ³	
	Acute systemic effects inhalation	300 mg/m ³	
	Long-term local effects inhalation	35.7 mg/m ³	
	Acute local effects inhalation	300 mg/m ³	
	Long-term systemic effects dermal	6 mg/kg bw/day	
	Acute systemic effects dermal	6 mg/kg bw/day	
	Long-term systemic effects oral	2 mg/kg bw/day	
	Acute systemic effects oral	2 mg/kg bw/day	

2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	33 mg/m ³	
	Long-term local effects inhalation	33 mg/m ³	
	Long-term systemic effects dermal	320 mg/kg bw	
	Long-term systemic effects oral	36 mg/kg bw	
	Acute systemic effects oral	500 mg/kg bw/day	

PNEC

acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Fresh water (intermittent releases)	21 mg/l	
STP	100 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	

trizinc bis(orthophosphate)

Compartments	Value	Remark
Fresh water	19.7 µg/l	
Marine water	7.7 µg/l	
STP	100 µg/l	
Fresh water sediment	146.9 mg/kg sediment dw	
Marine water sediment	162.2 mg/kg sediment dw	
Soil	83.1 mg/kg soil dw	

n-butyl acetate

Compartments	Value	Remark
Fresh water	0.18 mg/l	
Marine water	0.018 mg/l	
Fresh water (intermittent releases)	0.36 mg/l	
STP	35.6 mg/l	
Fresh water sediment	0.981 mg/kg sediment dw	
Marine water sediment	0.098 mg/kg sediment dw	
Soil	0.09 mg/kg soil dw	

2-methoxy-1-methylethyl acetate

Compartments	Value	Remark
Fresh water	0.635 mg/l	
Marine water	0.064 mg/l	
Fresh water (intermittent releases)	6.35 mg/l	
STP	100 mg/l	
Fresh water sediment	3.29 mg/kg sediment dw	
Marine water sediment	0.329 mg/kg sediment dw	
Soil	0.29 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

9 / 25

NOVAFILL FLEX 2 ZWART

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Avoid prolonged and repeated contact with skin. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.5 mm	Class 6	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Colour	Black
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	Not applicable (aerosol)
Boiling point	No data available in the literature
Flammability	Extremely flammable aerosol.
Explosion limits	1.5 - 18.6 vol % ; Liquid
Flash point	Not applicable (aerosol)
Auto-ignition temperature	Not applicable (aerosol)
Decomposition temperature	No data available in the literature
pH	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Dynamic viscosity	Not applicable (aerosol)
Solubility	No data available in the literature
Log Kow	Not applicable (mixture)
Vapour pressure	5200 hPa ; 20 °C ; Liquid
Absolute density	870 kg/m ³ ; 20 °C ; Liquid
Relative density	0.87 ; 20 °C ; Liquid
Relative vapour density	No data available in the literature
Particle size	Not applicable (aerosol)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

NOVAFILL FLEX 2 ZWART

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available

Judgement is based on the relevant ingredients

butanone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	2193 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 8050 ml/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation						Data waiving	

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50		> 15800 mg/kg bw	24 h	Rabbit (male)	Experimental value	

trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC50	Equivalent to OECD 403	> 5.70 mg/l air	4 h	Rat (male / female)	Experimental value	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	10760 mg/kg bw - 12789 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 14112 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	OECD 403	> 21 mg/l	4 h	Rat (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	6190 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC0	Equivalent to OECD 403	> 1728 ppm	4 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available

Classification is based on the relevant ingredients

butanone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

NOVAFILL FLEX 2 ZWART

acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Not irritating		3 day(s)	24; 48; 72 hrs; 4 days	Guinea pig	Experimental value	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature study	

trizinc bis(orthophosphate)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Not applicable (in vitro test)	Not irritating	OECD 439	42 h		Reconstructed human epidermis	Experimental value	

n-butyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

Conclusion

Causes serious eye irritation.
Not classified as irritating to the skin
Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available
Judgement is based on the relevant ingredients
butanone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	

acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Experimental value	

trizinc bis(orthophosphate)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for skin
Not classified as sensitizing for inhalation

Specific target organ toxicity

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available
Classification is based on the relevant ingredients

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

12 / 25

NOVAFILL FLEX 2 ZWART

butanone

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral							Data waiving	
Dermal							Data waiving	
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	5041 ppm	No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (vapours)			STOT SE cat.3	Central nervous system (drowsiness, dizziness)			Annex VI	

acetone

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (drinking water)	NOAEL	Equivalent to OECD 408	4.86 mg/kg bw/day - 5.95 mg/kg bw/day	No effect	13 week(s)	Mouse (male / female)	Experimental value	
Oral (drinking water)	LOAEL	Equivalent to OECD 408	11.3 mg/kg bw/day	Liver (histopathology)		Mouse (female)	Experimental value	
Dermal							Data waiving	
Inhalation (vapours)	NOAEC	Subchronic toxicity test	19000 ppm	No effect	8 weeks (5 days / week)	Rat (male)	Experimental value	
Inhalation (vapours)	Dose level	Human observation study	361 ppm	Central nervous system (neurotoxic effects)	2 day(s)	Human	Epidemiological study	

trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 408	31.25 mg/kg bw/day	No effect	13 weeks (daily)	Rat (male / female)	Experimental value	
Dermal		OECD 411			13 weeks (daily)	Rat (male / female)	Experimental value	Not quantifiable
Inhalation (aerosol)	NOAEC systemic effects	OECD 413	9.97 mg/m ³ air	No adverse systemic effects	90 day(s)	Rat (male / female)	Experimental value	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	EPA OTS 798.2650	125 mg/kg bw/day	No effect	13 weeks (daily)	Rat (male / female)	Read-across	
Oral (stomach tube)	LOAEL	EPA OTS 798.2650	500 mg/kg bw/day	Central nervous system (central nervous system depression)	13 weeks (daily)	Rat (male / female)	Read-across	
Inhalation (vapours)	NOAEC	EPA OTS 798.2450	500 ppm	No adverse systemic effects	13 weeks (daily, 5 days / week)	Rat (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 422	≥ 1000 mg/kg	No effect	41 day(s) - 45 day (s)	Rat (male / female)	Experimental value	
Oral (stomach tube)	Dose level	US EPA	500 mg/kg bw/day	Drowsiness, dizziness		Rat (male / female)	Experimental value	
Dermal	NOAEL	Equivalent to OECD 411	1838 mg/kg bw/day	No effect	13 weeks (5 days / week)	Rabbit (male)	Read-across	
Dermal	LOAEL	Equivalent to OECD 411	3676 mg/kg bw/day	Overall effects	13 weeks (6h / day, 5 days / week)	Rabbit (male)	Read-across	
Inhalation (vapours)	NOEL	OECD 453	300 ppm	No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

Conclusion

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

13 / 25

NOVAFILL FLEX 2 ZWART

May cause drowsiness or dizziness.
Not classified for subchronic toxicity

Mutagenicity (in vitro)

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available
Judgement is based on the relevant ingredients
butanone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Rat liver cells	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

acetone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	

trizinc bis(orthophosphate)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster lung fibroblasts (V79)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	EU Method B.13/14	Bacteria (S.typhimurium)		Experimental value	

n-butyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	

2-methoxy-1-methylethyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative without metabolic activation	Equivalent to OECD 482	Rat liver cells	No effect	Experimental value	

Mutagenicity (in vivo)

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available
Judgement is based on the relevant ingredients
butanone

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)	No effect	Experimental value	Single intraperitoneal injection

acetone

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (drinking water))	Micronucleus test	13 week(s)	Mouse (male / female)	No effect	Literature study	

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

14 / 25

NOVAFILL FLEX 2 ZWART

trizinc bis(orthophosphate)

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Inhalation (aerosol))	OECD 489		Rat (male)	No effect	Experimental value	

n-butyl acetate

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)	No effect	Read-across	Single treatment

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available

Judgement is based on the relevant ingredients

acetone

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal	NOEL	Carcinogenic toxicity study	79 mg	No carcinogenic effect		Mouse (female)	Literature study	

trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	> 22000 mg/l	No carcinogenic effect	52 week(s)	Mouse (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available

Judgement is based on the relevant ingredients

butanone

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h / day)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h / day)	Rat	No effect	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	2000 ppm		Rat (male / female)	No effect	Experimental value	

acetone

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	Foetus (no effect)	Experimental value	
Developmental toxicity (Inhalation (aerosol))	LOAEC	Equivalent to OECD 414	11000 mg/kg bw/day	14 days (gestation, daily)	Rat	Foetus (fetotoxicity)	Experimental value	
Maternal toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Inhalation (aerosol))	LOAEC	Equivalent to OECD 414	11000 ppm	14 days (gestation, daily)	Rat	Maternal toxicity	Experimental value	
Effects on fertility (Oral (drinking water))	NOAEL		900 mg/kg bw/day	13 week(s)	Rat (male)	No effect	Experimental value	
Effects on fertility (Oral (drinking water))	LOAEL		3400 mg/kg bw/day	13 week(s)	Rat (male)	Male reproductive organ (adverse effects on fertility)	Experimental value	

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

15 / 25

NOVAFILL FLEX 2 ZWART

trizinc bis(orthophosphate)

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (aerosol))	NOAEC	OECD 414	7.5 mg/m ³ air	14 days (6h / day)	Rat	No effect	Experimental value	
Maternal toxicity (Inhalation (aerosol))	NOAEC	OECD 414	1.5 mg/m ³ air	14 days (6h / day)	Rat	No effect	Experimental value	
Effects on fertility (Inhalation (aerosol))	NOEC	OECD 421	9.97 mg/m ³ air		Rat (male / female)	No effect	Experimental value	

n-butyl acetate

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Fetotoxicity	Experimental value	
Maternal toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Maternal toxicity	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEC	OECD 416	2000 ppm	> 90 day(s)	Rat (male / female)	No effect	Experimental value	

2-methoxy-1-methylethyl acetate

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	> 4000 ppm	10 days (gestation, daily)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	500 ppm	10 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Inhalation (vapours))	LOAEL	Equivalent to OECD 414	2000 ppm	10 days (gestation, daily)	Rat	Maternal toxicity	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEL	OECD 416	300 ppm		Rat (male / female)	No effect	Read-across	

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

NOVAFILL FLEX 2 ZWART

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

Toxicity other effects

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available

butanone

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Skin				Skin (skin dryness or cracking)			Literature study	

acetone

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Skin				Skin (skin dryness or cracking)			Literature study	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
	NOEC	EPA OTS 798.6050	1500 ppm	(hypoactivity)	6 h	Rat (male / female)	Experimental value	
	NOAEC	EPA OTS 798.6050	500 ppm	(no neurotoxic effects)	13 week(s)	Rat (male / female)	Experimental value	

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

NOVAFILL FLEX 2 ZWART

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

16 / 25

NOVAFILL FLEX 2 ZWART

SECTION 12: Ecological information

12.1. Toxicity

NOVAFILL FLEX 2 ZWART

No (test)data on the mixture available

Classification is based on the relevant ingredients

butanone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2973 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	308 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1220 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
	NOEC	OECD 201	566 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1150 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value

acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	6210 mg/l - 8120 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	LC50		8800 mg/l	48 h	Daphnia pulex	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEC		530 mg/l		Algae		Fresh water	
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2212 mg/l	28 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value
Toxicity aquatic micro-organisms	EC50	Equivalent to OECD 209	61.15 g/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value
	EC50		1700 mg/l		Pseudomonas putida			Literature study; Inhibition

trizinc bis(orthophosphate)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		0.53 mg/l - 0.96 mg/l		Pisces			Literature study; Zinc ion
Acute toxicity crustacea	EC50		0.71 mg/l		Daphnia magna			Literature study; Zinc ion
Toxicity algae and other aquatic plants	EC50		0.041 mg/l		Pseudokirchneriella subcapitata			Literature study; Zinc ion
	EC10		0.011 mg/l		Pseudokirchneriella subcapitata			Literature study; Zinc ion
Long-term toxicity fish	EC10		0.16 mg/l - 0.77 mg/l		Oncorhynchus mykiss			Literature study; Zinc ion
Long-term toxicity aquatic crustacea	NOEC		14 µg/l		Invertebrata			Literature study; Zinc ion
Toxicity aquatic micro-organisms	IC50	ISO 9509:2006	0.35 mg/l	4 h	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

NOVAFILL FLEX 2 ZWART

n-butyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	18 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	Equivalent to OECD 202	44 mg/l	48 h	Daphnia sp.	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	397 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; GLP
	NOEC	OECD 201	196 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; Growth rate
Long-term toxicity aquatic crustacea	NOEC	OECD 211	23.2 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; Reproduction
Toxicity aquatic micro-organisms	IC50	TETRATOX assay	356 mg/l	40 h	Tetrahymena pyriformis	Static system	Fresh water	Experimental value; Growth

2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	100 mg/l - 180 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	> 500 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	≥ 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 204	48 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; Behaviour
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro-organisms	EC10	Equivalent to OECD 209	> 1000 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

butanone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	98 %; Oxygen consumption	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	96.3 h	1.5E6 /cm ³	Calculated value

acetone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90.9 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	52.431 day(s)	1.5E6 /cm ³	Calculated value

n-butyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	83 %; Oxygen consumption	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	3.3 day(s)	5E5 /cm ³	Experimental value

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

18 / 25

NOVAFILL FLEX 2 ZWART

2-methoxy-1-methylethyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	83 %; Oxygen consumption	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	11 h	1.5E6 /cm ³	Calculated value

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

NOVAFILL FLEX 2 ZWART

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

butanone

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.3	40 °C	Experimental value

acetone

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.69		Pisces	Literature study

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.23		Test data

trizinc bis(orthophosphate)

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (inorganic)			

n-butyl acetate

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.3	25 °C	Experimental value

2-methoxy-1-methylethyl acetate

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		1.2	20 °C	Experimental value

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

butanone

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.65 - 1.3	Calculated value

acetone

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.374 - 0.988	Calculated value

n-butyl acetate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.268 - 1.844	Calculated value

2-methoxy-1-methylethyl acetate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.60 - 1.1	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

19 / 25

NOVAFILL FLEX 2 ZWART

No evidence of endocrine disrupting properties

12.7. Other adverse effects

NOVAFILL FLEX 2 ZWART

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

butanone

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Groundwater

Groundwater pollutant

acetone

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Groundwater

Groundwater pollutant

trizinc bis(orthophosphate)

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

n-butyl acetate

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Groundwater

Groundwater pollutant

2-methoxy-1-methylethyl acetate

Groundwater

Groundwater pollutant

Water ecotoxicity pH

pH shift

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number or ID number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

20 / 25

NOVAFILL FLEX 2 ZWART

Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Rail (RID)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Inland waterways (ADN)

14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Sea (IMDG/IMSBC)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	P

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

21 / 25

NOVAFILL FLEX 2 ZWART

Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

Explosives precursors

Due to the presence of one or more components in this mixture, acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

VOC content Directive 2010/75/EU

VOC content	Remark
76.56 %	
666.0 g/l	

VOC content Directive 2004/42/EC

Maximum value	EC limit value	Category	Subcategory	Notation
642.8 g/l	840 g/l	IIB	e: Special finishes	2004/42/IIB(e)(840)642.8

2-methoxy-1-methylethyl acetate

Product name	Skin resorption
2-Methoxy-1-methylethylacetate	Skin

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500	None	Eco-toxicity

REACH Candidate list

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

22 / 25

NOVAFILL FLEX 2 ZWART

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· butanone · acetone · n-butyl acetate · 2-methoxy-1-methylethyl acetate	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· butanone · acetone · n-butyl acetate · 2-methoxy-1-methylethyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· butanone · acetone	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

23 / 25

NOVAFILL FLEX 2 ZWART

mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

National legislation Belgium

NOVAFILL FLEX 2 ZWART

No data available

2-methoxy-1-methylethyl acetate

Résorption peau	Acétate de 2-(1-méthoxy)propyle; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

National legislation The Netherlands

NOVAFILL FLEX 2 ZWART

Waterbezwaarlijkheid	A (1); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

butanone

Huidopname (wettelijk)	2-Butanon; H
------------------------	--------------

National legislation France

NOVAFILL FLEX 2 ZWART

No data available

butanone

Risque de pénétration percutanée	Méthyléthylcétone; Risque de pénétration percutanée
----------------------------------	---

2-methoxy-1-methylethyl acetate

Risque de pénétration percutanée	Acétate de 2-méthoxy-1-méthyléthyle; Risque de pénétration percutanée
----------------------------------	---

National legislation Germany

NOVAFILL FLEX 2 ZWART

WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

butanone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Butanon; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	Butanon; H; Hautresorptiv

acetone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

trizinc bis(orthophosphate)

TA-Luft	5.2.1
---------	-------

n-butyl acetate

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	n-Butylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

2-methoxy-1-methylethyl acetate

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	2-Methoxy-1-methylethylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation Austria

NOVAFILL FLEX 2 ZWART

No data available

butanone

besondere Gefahr der Hautresorption	Butanon; H
-------------------------------------	------------

2-methoxy-1-methylethyl acetate

besondere Gefahr der Hautresorption	1-Methoxypropylacetat-2; H
-------------------------------------	----------------------------

National legislation United Kingdom

NOVAFILL FLEX 2 ZWART

No data available

butanone

Skin absorption	Butan-2-one (methyl ethyl ketone); Sk
-----------------	---------------------------------------

2-methoxy-1-methylethyl acetate

Skin absorption	1-Methoxypropyl acetate; Sk
-----------------	-----------------------------

National legislation Ireland

NOVAFILL FLEX 2 ZWART

No data available

butanone

Skin resorption	Methyl ethyl ketone; Skin
-----------------	---------------------------

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

24 / 25

NOVAFILL FLEX 2 ZWART

2-methoxy-1-methylethyl acetate

Skin resorption

2-Methoxy-1-methylethylacetate; Skin

Other relevant data

NOVAFILL FLEX 2 ZWART

No data available

butanone

TLV - Skin absorption

Methyl ethyl ketone; Skin; Danger of cutaneous absorption

acetone

TLV - Carcinogen

Acetone; A4

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
Erc50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2; 3; 8; 15

Publication date: 2006-02-27

Date of revision: 2024-11-27

Revision number: 0700

BIG number: 43175

25 / 25