



Clear Lube

SYNTHETIC, CLEAR PTFE BASED GREASE

- ✓ Excellent penetration and unique adherence.
- ✓ Resists and prevents corrosion.
- ✓ Maintains viscosity at high and low temperatures.
- ✓ Extends lubrication intervals and reduces wear.
- ✓ Resists pressure cleaning.

Technical Info

- Composition: acrylic - copolymers is neutral oil; solvent: aliphatic hydrocarbons with some aromatics; additives: PTFE.
- Color: transparent.
- Odour: typical.
- Specific weight: 0.885.
- Solid substances: approx. 30%.
- Temperature range: -25°C until +300°C.
- Viscosity :
 - on application: 48sec. - B6 FLOW cup
 - after 6 min. evaporation of solvent: 6 sec. - B6 Flow cup.
- Shelf life: 36 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Clear Lube - aerosol 400ml

214001000

Product [CLB]

Characteristics

- Clear Lube contains PTFE in order to increase tool life and to reduce sliding resistance.
- Clear Lube offers a high lubricating capacity under high loads and in difficult conditions and protects against corrosion by forming a thin polymer film layer, while still penetrating deep into the objects to be lubricated.
- Clear Lube resists high pressure cleaning and reduces chain friction and wear of chains and extends the service life up to 10 times.

Applications

- For indoor and outdoor heavy duty lubrication, also on intermittent and inaccessible lubrication points.
- On chains, conveyors, open gears, wire-rope, cables, joints, linkages, lead screws, hinges, locking mechanisms.
- Effective on rubber "O"-ring chains.
- Is particularly useful where equipment has to withstand severe conditions such as outdoor exposure or contact with acids, alkalis, hot & cold water, steam and high pressure.

Use

- Shake well before use.
- Apply on a clean surface.
- Use the extension pipe for hard-to-reach applications.
- Allow to evaporate before using the application.

