100



Mastergun







Maintenance free.



Technical Info

Working pressure: from 3 to 8 bar.

Separate pressure control for spray pattern and product flow.

No cleaning - product does not come into contact with the mechanical parts of the gun.

The gun is self-cleaning by slowly releasing the trigger at the end of the job.

Very easy cartridge change.

Cartridges and sausage packaging can be handled with standard nozzle.

Packing

Mastergun

316510000

Product [MGM]

Characteristics

For applying all one-component adhesives and sealants. A patented system with a telescopic piston pushes the product evenly out the cartridge, without any compressed air coming into contact with the product. A quick-venting system in the air pressure supply to the piston immediately stops the flow of product when the trigger is released.

The accessories supplied with the gun allow all single-component products to be processed in plastic cartridges as well as in aluminium cartridges or sausage packages. The pressure for spraying the product is regulated by a micrometric pressure regulator, which results in perfect dosage and extremely uniform flow. This pressure regulator allows products with different viscosities to be sprayed without changing the pressure of the supply line.

With two types of nozzles, all structures can be obtained. A second micrometric pressure regulator allows the spray pattern to be regulated.

Applications

For the application of sprayable sealants in different structures. For easy application of sealants for various applications.

Use

See operating instructions under Downloads.

