



## **Al-Fix Filler**

FILLER FOR AL-FIX GLUES



- To obtain an easy volume for the use of Al-Fix glues.
- To fill damages and bondings where a gap/opening between the materials is required.
- Powder in handy dispensing bottle.

## **Technical Info**

- Base: e.g. glass.
- Form: powder.
- Colour: white.
- Odour: odourless.
- Flammability: not flammable.
- Relative density at 20°C: 2,6.
- Shelf life: 12 months, dry and cool.
- · Safety measures: consult the Safety Data Sheet.

Packing	
Al-Fix Filler - bottle 20ml	501100000

## Use

- Apply in layers: Spread Al-Fix adhesive and then Al-Fix Filler.
- Repeat if necessary.
- If desired, accelerate curing with the help of Al-Fix Aktivator.



Novatio is a registered trademark of Novatech International nv. Industrielaan 5B - B-2250 Olen - Belgium | Tel: +32 14 25 67 40 | info@novatio.be

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV.

## Characteristics

Product [AFI]

Al-Fix is an adhesive which bonds in seconds and has a special formula based on Cyanacrylate. Al-Fix Filler is a one component adhesive which is solventless and consists mainly of Athyl Cyanacrylate Monomer. Al-Fix is temperature resistant in the range from -30°C to +100°C. Al-Fix is resistant to solvents, oils, benzene, temperature fluctuations and atmospheric conditions. Al-Fix Filler joints have a high tensile shear strength and show no shrinkage.