



Al-Fix Aktivator

ACTIVATES CA GLUES

- ✓ Fastens the curing time of the Al-fix glues.
- ✓ Makes adhesion possible on porous materials such as wood.
- ✓ To be used on Al-Fix Gel.

Technical Info

Shelf life: 24 months, protected from light and at ambient temperature.

Packing

Al-Fix Aktivator - aerosol 200ml

501104000

Product [AFA]

Characteristics

Al-Fix glues are adhesives which bond in seconds and have a special formula based on Cyanacrylate. Al-Fix glues are one component adhesives which are solventless and consist mainly of Athyl Cyanacrylate Monomer. Al-Fix glues are temperature resistant in the range from -30°C to +100°C. Al-Fix are resistant to solvents, oils, benzene, temperature fluctuations and atmospheric conditions. Al-Fix glue joints have a high tensile shear strength and show no shrinkage. Al-Fix Aktivator accelerates the hardening considerably and makes the curing of thicker layers of Al-Fix Gel possible.

Applications

Al-Fix glues provide an exceptionally strong bond between almost all kinds of materials, with the exception of polyethylene, polypropylene and fluorine containing materials. Materials which can be bonded with Al-Fix glues: ABS, aluminium, bakelite, bronze, buthyl, celluloid, chloroprene, chrome, delrin, glass, copper, natural rubber, NBR, neoprene, nitril, nylon, phenol, polycarbonate, polystyrene, porcelain, hard pvc, stainless steel. On porous materials we recommend using Al-Fix Aktivator or Al-Fix Aktivator SF.

Use

- Apply on a clean and dry surface and allow to evaporate.
- Apply Al-Fix and bond pieces together.

To facilitate curing of Al-Fix Gel, spray once the pieces that have been joined together. May damage painted surfaces and thermoplastics. The possible white deposit after hardening can be easily removed with the help of Al-fix Remover.

