



Silicon 100

SILICONE OIL

- ✓ Lubricates, protects, prevents adhesion and makes water repellent.
- ✓ Clear, extremely thin, odorless, non-staining and effective on all surfaces.
- ✓ Does not melt, freeze, harden, evaporate or acidify.

Technical Info

- Composition: Silicone oil (Dimethylpolysiloxane).
- Colour: colourless oil.
- Odour: paraffinic odour.
- Pressure resistance: 1400 kg/cm².
- Temperature resistance: continuous: -70°C up to 250°C; peak: up to 280°C, only for dry lubrication.
- Solubility: insoluble in water; soluble in aliphatic hydrocarbons.
- Shelf life: keep dry, cool and frost-proof
 - 400ml = 24 months;
 - 5L = 12 months;
 - 200L = 24 months.
- Safety measures: consult the Safety Data Sheet.

Packing

Silicon 100 - aerosol 400ml	201001000
Silicon 100 - aerosol 400ml - Renson	201001127
Silicon 100 - can 5L	201002000

Product [SIL]

Characteristics

Universal lubricant based on water-repellent, non-conductive, chemically inert silicone oil, for the treatment of metal, rubber, wood, leather, plastics, painted surfaces, textile, vinyl,

Contains no solvents or other chemicals. Optimal, temperature-resistant lubrication and protection with a long service life.

Applications

- Universal lubricant for the processing of synthetic materials - wood - textile.
- Lubricant for garage (e.g. seat and window rails, door-handles), print shops, food and packaging industry.
- Lubricant for office and kitchen equipment and high-tech mechanisms.
- Protective medium and brightener for synthetic materials, rubber and metal.
- Prevents freezing of rubbers of e.g. doors, car boots,

Use

- Apply from 30 cm on a clean surface.
- Removable with Safety Clean.



Lubricants