



Two Way Tape

DOUBLE SIDED FOAM TAPE FOR PERMANENT ATTACHMENT

- ✓ Extra strong, high tensile strength and elasticity.
- ✓ Oil, petrol, diesel, chemical and weather resistant.
- ✓ Clean and simple to use.
- ✓ Permanent adhesion on clean surfaces.
- ✓ Repositionable.

Technical Info

- Foam: black, cross-linked, closed-cell polyethylene.
- Adhesive: acrylic resin, reacts to pressure.
- Backing: one side silicone coated green polyethylene film.
- Density: 100 kg/m³.
- Adhesion to steel: 1365g/20 mm (7 days/20°C).
- Shear strength: 7.5 kg/cm².
- Features: high holding power; excellent resistance to weathering and oil.
- End use temperature range after 7 days: -40°C to +100°C.
- Min. application temperature: +10°C.
- Thickness: 0.9 mm.
- First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape).
- Shelf life: 24 months, keep dry, cool and frost-proof.

Packing

Two Way Tape - roll 6mm / 10m	550068000
Two Way Tape - roll 12mm / 10m	550128000
Two Way Tape - roll 15mm / 10m	550158000
Two Way Tape - roll 19mm / 10m	550198000
Two Way Tape - roll 25mm / 10m	550258000

Product

Characteristics

- Consists of a 0.8 mm black, cross-linked, closed cell, polyethylene foam, coated on both sides with an acrylic adhesive.
- Offers very high adhesive and cohesive properties, with the possibility of repositioning.
- Has a high holding power and an excellent resistance to weathering and oil.
- Available in five different dimensions to make the job easier.

Applications

- mounting of automotive side mouldings and emblems
- mounting of name-plates and letters
- mounting of interior and exterior coverings
- mounting of air-spoilers
- mounting of electronic components
- ideal for use with high fluctuations of temperature

Use