



Nova Structural Tape Tapes

BLACK, SELF-ADHESIVE STRUCTURAL FILM

- ✓ Lasting protection against wear.
- ✓ Increases impact resistance.
- ✓ Temperature resistant and colorfast.

Technical Info

- Film: structured polymeric vinyl.
- Glue: acrylic glue.
- Colour: black.
- Application temp.: +8°C to +50°C.
- Temp. resistance: -40°C to +90°C.
- Tensile strength: 13,5 N/mm².
- Conservation of quality: for 7 years.
- Adherence to: untreated aluminium, anodised aluminium, stainless steel, chromium plated steel, polyurethane, glass, acryl, ABS,...
- Time Grade Bonding 20 min. 90° > 900 N/m 20 min. 180° > 600 N/m 24 uur 90° > 530 N/m 24 uur 180° > 700 N/m
- First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape).
- Shelf life: 36 months, keep dry, cool and frost-proof.

Packing

Nova Structural Tape - roll 15cm / 2m

566515000

Product [NST]

Characteristics

- Is a high quality, polymeric vinylfilm that protects weak spots against rubble, scratches, rust,
- Protects against wear by vibration and friction.
- Adheres to the smoothest plastics, lacquers, aluminium, stainless steel, anodised aluminium,

Applications

- Protects against chemical pollution, crushed stone, rust, scratches, vibration and friction.
- Protects painted body parts in various materials.
- Interior construction: for general maintenance, protection and repairs.

Use

- Cut to desired shape.
- Apply on a clean and dry surface. If necessary, first clean with Safety Clean and / or Multifoam.
- Remove protective film, apply and rub with a plastic spatula.