

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## SKINCOAT AEROSOL

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : SKINCOAT AEROSOL  
**Registration number REACH** : Not applicable (mixture)  
**Product type REACH** : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Wax

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements



Contains: Naphtha (petroleum), hydrotreated heavy.

**Signal word** Danger

##### H-statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

##### P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 3.2, 8, 9, 12, 15

Revision number: 0600

Publication date: 2001-03-07

Date of revision: 2021-10-20

BIG number: 35064

1 / 13

# SKINCOAT AEROSOL

P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves, protective clothing and eye protection/face protection.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butane 01-2119474691-32	106-97-8 203-448-7	C≤30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
Naphtha (petroleum), hydrotreated heavy	64742-48-9 265-150-3	C≤30%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	

- (1) For H- and EUH-statements in full: see section 16  
(2) Substance with a Community workplace exposure limit  
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006  
(21) 1,3-butadiene <0.1%

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Dizziness. Drowsiness.

##### After skin contact:

Tingling/irritation of the skin.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

2 / 13

# SKINCOAT AEROSOL

## 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.  
Major fire: Quantities of water.

## 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

## 5.3. Advice for firefighters

### 5.3.1 Instructions:

Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. If exposed to fire cool the closed containers by spraying with water. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Do not discharge the waste into the drain.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Protect against frost. Keep out of direct sunlight.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### Belgium

Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

3 / 13

# SKINCOAT AEROSOL

## France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>

## Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>

## Austria

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m <sup>3</sup>
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

## UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
-----------------	--	----------

### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

Product name	Test	Number
Petroleum Distillate (Naphthas)	NIOSH	1550
Petroleum Distillates Fractions	OSHA	48

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

If applicable and available it will be listed below.

#### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

# SKINCOAT AEROSOL

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (aerosol)
Explosion limits	1.8 - 9.5 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	Not applicable (aerosol)
Boiling point	-140 °C - 190 °C
Relative vapour density	> 1
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.85 ; 20 °C ; Liquid
Absolute density	853 kg/m <sup>3</sup> ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (non-soluble in water)

### 9.2. Other information

Evaporation rate	0.13 ; Butyl acetate
------------------	----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Unstable on exposure to heat.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### SKINCOAT AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5610 mg/m <sup>3</sup> air	4 h	Rat (male / female)	Experimental value	

#### Conclusion

Not classified for acute toxicity

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

5 / 13

# SKINCOAT AEROSOL

## Corrosion/irritation

### SKINCOAT AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating	OECD 404	4 h	1; 24; 48; 72; 168 hours	Rabbit	Experimental value	

### Conclusion

Causes skin irritation.

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### SKINCOAT AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406	6 h	24; 48 hours	Guinea pig (male)	Experimental value	

### Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

## Specific target organ toxicity

### SKINCOAT AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOEL	Subacute toxicity test	< 500 mg/kg bw/day			4 weeks (daily, 5 days / week)	Rat (male)	Experimental value
Dermal	NOEL	Equivalent to OECD 410	> 2000 mg/kg bw/day		No adverse systemic effects	4 weeks (6h / day, 3 days / week)	Rabbit (male / female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 412	9840 mg/m <sup>3</sup> air		No effect	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

### Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### SKINCOAT AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Yeast (S. cerevisiae)		Experimental value	

## Mutagenicity (in vivo)

### SKINCOAT AEROSOL

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

6 / 13

# SKINCOAT AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	EPA OTS 798.5395	4 weeks (6h / day, 5 days / week)	Rat (male / female)		Experimental value
Negative	Equivalent to OECD 475	5 day(s)	Rat (male)	Bone marrow	Experimental value

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### SKINCOAT AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOAEL	Equivalent to OECD 451	0.05 ml	102 weeks (3 times / week)	Mouse (male)	No carcinogenic effect		Experimental value

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### SKINCOAT AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Naphtha (petroleum), hydrotreated heavy

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	23900 mg/m <sup>3</sup>	14 days (6h / day)	Rat (female)	No effect	Foetus	Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	23900 mg/m <sup>3</sup> air	14 day(s)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEC (P/F1)	Equivalent to OECD 416	≥ 20000 mg/m <sup>3</sup> air	23 weeks (6h / day, 7 days / week)	Rat (male / female)	No effect		Experimental value
	NOAEL (P/F1)	Equivalent to OECD 421	24700 mg/m <sup>3</sup> air	9 weeks (6h / day, 7 days / week)	Rat (male / female)	No effect		Experimental value

## Conclusion

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

### SKINCOAT AEROSOL

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

### SKINCOAT AEROSOL

No effects known.

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### SKINCOAT AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

# SKINCOAT AEROSOL

## Naphtha (petroleum), hydrotreated heavy

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	10 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Similar product; GLP
Acute toxicity crustacea	EC50	OECD 202	4.5 mg/l	48 h	Daphnia magna	Static system	Fresh water	Similar product; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	3.1 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Similar product; GLP
Long-term toxicity fish	NOEL	OECD 204	2.6 mg/l	14 day(s)	Pimephales promelas	Semi-static system	Fresh water	Similar product; GLP
Long-term toxicity aquatic crustacea	NOEL	OECD 211	2.6 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Similar product; GLP

### Conclusion

Toxic to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

### Naphtha (petroleum), hydrotreated heavy

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	77.05 %; GLP	28 day(s)	Experimental value

### Conclusion

#### Water

Does not contain any not readily biodegradable component(s)

## 12.3. Bioaccumulative potential

### SKINCOAT AEROSOL

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

### Naphtha (petroleum), hydrotreated heavy

#### BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFWIN	10 - 2500; Similar product			Calculated value

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

### Conclusion

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

### Naphtha (petroleum), hydrotreated heavy

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	Other	< 2.36	Calculated value

#### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	93.02 %		0.81 %	0.34 %	5.83 %	Calculated value

### Conclusion

Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### SKINCOAT AEROSOL

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)



# SKINCOAT AEROSOL

Naphtha (petroleum), hydrotreated heavy

## Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

12 01 12\* (wastes from shaping and physical and mechanical surface treatment of metals and plastics: spent waxes and fats). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

UN number	1950
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

#### 14.4. Packing group

Packing group	
Labels	2.1

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

#### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

#### 14.1. UN number

UN number	1950
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

#### 14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

#### 14.4. Packing group

Packing group	
Labels	2.1

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

#### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

9 / 13

# SKINCOAT AEROSOL

## Inland waterways (ADN)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

# SKINCOAT AEROSOL

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
72.500 %	
514.678 g/l	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· Naphtha (petroleum), hydrotreated heavy	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· Naphtha (petroleum), hydrotreated heavy	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· Naphtha (petroleum), hydrotreated heavy	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

11 / 13

# SKINCOAT AEROSOL

(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council  
 (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.  
 The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

## National legislation Belgium

SKINCOAT AEROSOL

No data available

## National legislation The Netherlands

SKINCOAT AEROSOL

Waterbezuikbaarheid	Z (2); Algemene Beoordelingsmethodiek (ABM)
---------------------	---

## National legislation France

SKINCOAT AEROSOL

No data available

## National legislation Germany

SKINCOAT AEROSOL

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
<u>Naphtha (petroleum), hydrotreated heavy</u>	
TA-Luft	5.2.5/I

## National legislation Austria

SKINCOAT AEROSOL

No data available

## National legislation United Kingdom

SKINCOAT AEROSOL

No data available

## Other relevant data

SKINCOAT AEROSOL

No data available

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H226 Flammable liquid and vapour.  
 H229 Pressurised container: May burst if heated.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
Erc50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

12 / 13

# SKINCOAT AEROSOL

PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2, 8, 9, 12, 15

Publication date: 2001-03-07

Date of revision: 2021-10-20

Revision number: 0600

BIG number: 35064

13 / 13