





SAFE, QUICK AND EASY BUNDLING AND TYING

- Strong, ultra thin hook and loop tape in polypropylene.
- Low peel resistance and high tensile strength.
- Also safe on the most sensitive materials due to the soft finish.
 - For indoor and outdoor use.

Tie

Technical Info

- · Carrier: polypropylene.
- Width: 15 mm.
- Length: 3 m.
- Average peeling force: new tape: 88,84 g/cm².
- After 3000 closings: 67,11 g/cm²
- Average tensile strength: new tape: 1,46 kg/cm².
- After 3000 closings: 1,31 kg/cm².
- Shelf life: 36 months, keep dry, cool and frost-free.

Packing

HL-Fix Bundle and Tie - dispenser	562999000
HL-Fix Bundle and Tie black - roll 15mm / 3m	562915000
HL-Fix Bundle and Tie yellow - roll 15mm / 3m	562815000

Product [VBT]

Characteristics

HL-Fix BT is a very fine polypropylene Velfix for tying and bundling. This special technology allows for a low peeling force resistance, which guarantees user friendliness that directly opposes its high tensile strength. The soft finish respects the most sensitive materials and even plants. Its humidity and weather resistance makes it perfect to use indoors as well as outdoors. HL-Fix BT can be open and closed hundreds of times. The greater the overlap, the stronger the connection.

Applications

- · black for neutral bundling and tying.
- fluorescent yellow for noticeably safer tying.
- With handy dispenser with belt clip and cutter.



Novatio is a registered trademark of Novatech International nv. Industrielaan 5B - B-2250 Olen - Belgium | Tel: +32 14 85 97 37 | info@novatio.be

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV