



# Shock Spray

THE CHEMICAL WRENCH

- ✓ Breaks rusted connections in seconds by cold shrink effect.
- ✓ Penetrates easily and fast into the smallest cracks.
- ✓ A non-mineral based rust cracker.
- ✓ Dissolves rust crystals in seconds.
- ✓ Contains no greases or acids.
- ✓ Leaves no residue.
- ✓ Can be painted over in seconds.
- ✓ Can be used on bolts, nuts, hinges, ball bearings and all rusted applications.

## Technical Info

- Composition: alcohol with biologic degradable oils and anti-corrosion additives.
- Flashpoint °C: +13.
- Specific weight: 0,82 g/ml.
- Propellant: ozone safe.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

## Packing

Shock Spray - aerosol 400ml

261001000

## Product

### Characteristics

Shock Spray performs where ordinary mineral oil based products fail, and where the screw connections so far could not be loosened other than mechanically: (angel grinder, welding or cutting torches). Its highly effective performance within seconds is based on 2-fold function: when applied Shock Spray generates a chill (cooling) and shrinkage effect on the rusted or corroded parts. This along with its high capillary penetration properties, permits the product to penetrate deeply even into the smallest gaps.

### Applications

Shock Spray can be used on bolts, nuts, hinges, ball bearings and all rusted applications in all industrial and maintenance sectors.

## Use