novatio

TECHNICAL DATA SHEET



XPR-90 Silicon

Remover

REMOVAL OF HARDENED SILICONES

- Does not run or drip.
- Long working time.
- With powerful lime extracts.

Technical Info

- Composition: aliphatic hydrocarbon solvent, binder, and citrus extracts.
- Boiling point/boiling range °C: 130 166.
- Vapour pressure/20°C hPa: 4.6.
- Relative density/20°C: 0.75.
- Physical state/20°C: liquid.
- Flashpoint °C: 24.
- Self-combustion °C: 200.
- Water solubility: insoluble.
- Odour: distinctive.
- Dynamic viscosity mPa.s/20°C: 1.
- Kinematic viscosity, mm²/s/20°C: 1.
- Volatile organic compound (VOC) %: 97.
- Storage life: 36 months dry, cool and frostfree.
- · Safety measures: consult the Safety Data Sheet.

Packing

XPR-90 Silicon Remover - aerosol 500ml683810000

Product [90SR]

Characteristics

- In gel form is safe and versatile and also suitable for vertical applications.
- An aliphatic hydrocarbon solvent with added lime extracts.

Applications

Safe to use on most materials and has been developed for the removal of silicones, even hardened silicones.

Use

- · Apply to silicone and allow time for it to work in in proportion to the amount of grease.
- Rub off the loosened silicone.
- · If necessary, repeat the treatment.
- Rinse the cleaned surface with clean water.



Novatio is a registered trademark of Novatech International nv. Industrielaan 5B - B-2250 Olen - Belgium | Tel: +32 14 25 67 40 | info@novatio.be

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV