



# XPR-90 Wax & Glue Remover

## REMOVAL OF GLUE AND WAX

- ✓ Does not run or drip.
- ✓ Long working time.
- ✓ With powerful lime extracts.

### Technical Info

- Composition: aliphatic hydrocarbon solvent, binder, and citrus extracts.
- Boiling point/boiling range °C: 130 - 166.
- Vapour pressure/20°C hPa: 4.6.
- Relative density/20°C: 0.75.
- Physical state/20°C: liquid.
- Flashpoint °C: 24.
- Self-combustion °C: 200.
- Water solubility: insoluble.
- Odour: distinctive.
- Dynamic viscosity mPa.s/20°C: 1.
- Kinematic viscosity, mm<sup>2</sup>/s/20°C: 1.
- Volatile organic compound (VOC) %: 97.
- Storage life: 36 months dry, cool and frostfree.
- Safety measures: consult the Safety Data Sheet.

### Packing

XPR-90 Wax & Glue Remover - aerosol 500ml 683830000

### Product [90-WG]

#### Characteristics

In gel form is safe and versatile and also suitable for vertical applications.

An aliphatic hydrocarbon solvent with added lime extracts.

#### Applications

Safe to use on most materials and has been developed for the removal of wax and glue, even hardened silicones.

### Use

Apply and allow time for it to work.

Rub off the loosened silicone.

If necessary, repeat the treatment.

Rinse the cleaned surface with Multifoam.