

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## MULTIFIX CLEAR B

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : MULTIFIX CLEAR B  
**Registration number REACH** : Not applicable (mixture)  
**Product type REACH** : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Adhesive: component  
Hardener  
Activator

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 2	H225: Highly flammable liquid and vapour.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Acute	category 1	H400: Very toxic to aquatic life.
Aquatic Chronic	category 1	H410: Very toxic to aquatic life with long lasting effects.

#### 2.2. Label elements



Contains: butanone; dibenzoyl peroxide.

**Signal word** Danger

##### H-statements

H225 Highly flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H410 Very toxic to aquatic life with long lasting effects.

# MULTIFIX CLEAR B

## P-statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves, protective clothing and eye protection/face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

## Supplemental information

EUH066	Repeated exposure may cause skin dryness or cracking. Restricted to professional users.
--------	--

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butanone 01-2119457290-43	78-93-3 201-159-0	75% ≤C≤90%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
dibenzoyl peroxide 01-2119511472-50	94-36-0 202-327-6	10% ≤C≤25%	Org. Perox. B; H241 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(6)(2)(10)	Constituent	M: 10 (Acute, ECHA) M: 10 (Chronic, ECHA)

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Dizziness. Drowsiness. EXPOSURE TO HIGH CONCENTRATIONS: Nausea. Headache. Disturbances of consciousness. Central nervous system depression. Narcosis.

##### After skin contact:

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

##### After eye contact:

Irritation of the eye tissue.

##### After ingestion:

Central nervous system depression. Symptoms similar to those listed under inhalation.

#### 4.2.2 Delayed symptoms

No effects known.

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

2 / 15

# MULTIFIX CLEAR B

## 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.  
Major fire: Class B foam (not alcohol-resistant).

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.  
Major fire: Water; risk of puddle expansion.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Prevent soil and water pollution. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away. Gas/vapour heavier than air at 20°C. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately. Keep container tightly closed. Do not discharge the waste into the drain.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Meet the legal requirements. Store in a cool area. Store in a dry area. Keep container in a well-ventilated place. Fireproof storeroom. Keep only in the original container. Keep out of direct sunlight. Keep locked up. Unauthorized persons are not admitted.

#### 7.2.2 Keep away from:

Heat sources, ignition sources, reducing agents, (strong) acids, (strong) bases.

#### 7.2.3 Suitable packaging material:

No data available

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

# MULTIFIX CLEAR B

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

##### EU

Butanone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	600 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	300 ppm
	Short time value (Indicative occupational exposure limit value)	900 mg/m <sup>3</sup>

##### Belgium

2-Butanone	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	600 mg/m <sup>3</sup>
	Short time value	300 ppm
	Short time value	900 mg/m <sup>3</sup>
Peroxyde de dibenzoyl	Time-weighted average exposure limit 8 h	5 mg/m <sup>3</sup>

##### The Netherlands

2-Butanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	197 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	590 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	300 ppm
	Short time value (Public occupational exposure limit value)	900 mg/m <sup>3</sup>

##### France

Méthyléthylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	600 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	300 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	900 mg/m <sup>3</sup>
Peroxyde de dibenzoyl	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	5 mg/m <sup>3</sup>

##### Germany

Butanon	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	600 mg/m <sup>3</sup>
Dibenzoylperoxid	Time-weighted average exposure limit 8 h (TRGS 900)	5 mg/m <sup>3</sup>

##### UK

Butan-2-one (methyl ethyl ketone)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	899 mg/m <sup>3</sup>
Dibenzoyl peroxide	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	5 mg/m <sup>3</sup>

##### USA (TLV-ACGIH)

Benzoyl peroxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m <sup>3</sup>
Methyl ethyl ketone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	300 ppm

##### b) National biological limit values

If limit values are applicable and available these will be listed below.

##### Germany

2-Butanon (Methylethylketon) (2-Butanon)	Urin: expositionsende, bzw. schichtende	2 mg/l	
--	---	--------	--

##### UK

Butan-2-one (butan-2-one)	Urine: post shift	70 µmol/L	
---------------------------	-------------------	-----------	--

##### USA (BEI-ACGIH)

Methyl ethyl ketone (Methyl ethyl ketone)	urine: end of shift	2 mg/L	Nonspecific
---	---------------------	--------	-------------

# MULTIFIX CLEAR B

## 8.1.2 Sampling methods

Product name	Test	Number
2-Butanone (MEK) (Methyl ethyl ketone)	NIOSH	2500
2-Butanone (Methyl ethyl ketone)	OSHA	84
2-Butanone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
2-Butanone (Volatile Organic compounds)	NIOSH	2549
2-Butanone	OSHA	1004
2-Butanone	OSHA	13
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Benzoyl Peroxide	NIOSH	5009
MEK	NIOSH	8002
Methyl Ethyl Ketone (ketones I)	NIOSH	2555
Methyl Ethyl Ketone	OSHA	16

## 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

## 8.1.4 Threshold values

### DNEL/DMEL - Workers butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	600 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	1161 mg/kg bw/day	

### dibenzoyl peroxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	39 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	13.3 mg/kg bw/day	
	Long-term local effects dermal	34 µg/cm <sup>2</sup>	

### DNEL/DMEL - General population

#### butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	106 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	412 mg/kg bw/day	
	Long-term systemic effects oral	31 mg/kg bw/day	

#### dibenzoyl peroxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	2 mg/kg bw/day	

### PNEC

#### butanone

Compartments	Value	Remark
Fresh water	55.8 mg/l	
Fresh water (intermittent releases)	55.8 mg/l	
Marine water	55.8 mg/l	
STP	709 mg/l	
Fresh water sediment	284.74 mg/kg sediment dw	
Marine water sediment	284.7 mg/kg sediment dw	
Soil	22.5 mg/kg soil dw	
Oral	1000 mg/kg food	

#### dibenzoyl peroxide

Compartments	Value	Remark
Fresh water	0.02 µg/l	
Marine water	0.002 µg/l	
Fresh water (intermittent releases)	0.602 µg/l	
STP	0.35 mg/l	
Fresh water sediment	0.013 mg/kg sediment dw	
Marine water sediment	0.001 mg/kg sediment dw	
Soil	0.003 mg/kg soil dw	

## 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

5 / 15

# MULTIFIX CLEAR B

Materials	Measured breakthrough time	Thickness	Protection index	Remark
fluor rubber	> 240 minutes	0.7 mm	Class 5	
butyl rubber	> 480 minutes	0.7 mm	Class 6	
nitrile rubber	> 240 minutes		Class 5	

**c) Eye protection:**

Protective goggles (EN 166).

**d) Skin protection:**

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

**8.2.3 Environmental exposure controls:**

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Almost odourless
Odour threshold	No data available in the literature
Colour	Yellow
Particle size	Not applicable (liquid)
Explosion limits	1.8 - 11.5 vol %
Flammability	Highly flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available in the literature
Kinematic viscosity	No data available in the literature
Melting point	< 0 °C
Boiling point	> 75 °C
Relative vapour density	> 1
Vapour pressure	100 hPa
Solubility	Water ; 20 °C ; poorly soluble
Relative density	0.87 ; 25 °C
Absolute density	870 kg/m <sup>3</sup> ; 25 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	> 500 °C
Flash point	-4 °C
pH	Not applicable (non-soluble in water)

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

**Precautionary measures**

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away.

### 10.5. Incompatible materials

Reducing agents, (strong) acids, (strong) bases.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

**Acute toxicity**

MULTIFIX CLEAR B

No (test)data on the mixture available

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

6 / 15

# MULTIFIX CLEAR B

Judgement is based on the relevant ingredients

## butanone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	2193 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 8100 mg/kg bw/day	24 h	Rabbit (male)	Experimental value	
Inhalation						Data waiving	

## dibenzoyl peroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LC0	OECD 401	> 2000 mg/kg bw		Mouse (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC0	Equivalent to OECD 403	24.3 mg/l air	4 h	Rat (male)	Experimental value	

## **Conclusion**

Not classified for acute toxicity

## **Corrosion/irritation**

### MULTIFIX CLEAR B

No (test)data on the mixture available

Classification is based on the relevant ingredients

## butanone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single exposure
Skin	Not irritating	OECD 404	4 h	4; 24; 48; 72 hours	Rabbit	Read-across	

## dibenzoyl peroxide

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Moderately irritating	Equivalent to OECD 405	24 h	1; 24; 48; 72 hrs; 7 days	Rabbit	Experimental value	Single treatment with rinsing
Eye	Irritating; category 2						
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 72 hours	Rabbit	Experimental value	

## **Conclusion**

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

## **Respiratory or skin sensitisation**

### MULTIFIX CLEAR B

No (test)data on the mixture available

Classification is based on the relevant ingredients

## butanone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	

## dibenzoyl peroxide

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Sensitizing	Equivalent to OECD 429	3 day(s)		Mouse (female)	Experimental value	

## **Conclusion**

May cause an allergic skin reaction.

Not classified as sensitizing for inhalation

## **Specific target organ toxicity**

### MULTIFIX CLEAR B

No (test)data on the mixture available

Classification is based on the relevant ingredients

# MULTIFIX CLEAR B

## butanone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	5041 ppm		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)			STOT SE cat.3	Central nervous system	Drowsiness, dizziness			Annex VI

## dibenzoyl peroxide

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOEL	OECD 422	500 mg/kg bw/day		No effect		Rat (male)	Experimental value
Oral (stomach tube)	NOEL	OECD 422	1000 mg/kg bw/day		No effect		Rat (female)	Experimental value
Dermal								Data waiving

## Conclusion

May cause drowsiness or dizziness.  
Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### MULTIFIX CLEAR B

No (test) data on the mixture available  
Classification is based on the relevant ingredients

## butanone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Rat liver cells	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

## dibenzoyl peroxide

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value	
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	

## Mutagenicity (in vivo)

### MULTIFIX CLEAR B

No (test) data on the mixture available  
Classification is based on the relevant ingredients

## butanone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

## dibenzoyl peroxide

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative		8 week(s)	Mouse (male / female)		Experimental value

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### MULTIFIX CLEAR B

No (test) data on the mixture available  
Classification is based on the relevant ingredients



# MULTIFIX CLEAR B

## dibenzoyl peroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Carcinogenic toxicity study	40 mg/animal	53 weeks (2 times / week)	Mouse (female)	No carcinogenic effect		Weight of evidence
Oral	NOAEL	Carcinogenic toxicity study	2800 mg/kg bw/day	120 week(s)	Rat (male / female)	No carcinogenic effect		Weight of evidence
Oral	NOAEL	Carcinogenic toxicity study	2800 mg/kg bw/day	80 week(s)	Mouse (male / female)	No carcinogenic effect		Weight of evidence

### **Conclusion**

Not classified for carcinogenicity

### **Reproductive toxicity**

#### MULTIFIX CLEAR B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

#### butanone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation)	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h / day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Inhalation)	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h / day)	Rat (female)	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 416	1644 mg/kg bw/day - 1771 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

## dibenzoyl peroxide

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	OECD 422	500 mg/kg bw/day		Rat (male / female)	No effect		Experimental value
Effects on fertility	LOEL	OECD 422	1000 mg/kg bw/day		Rat (male / female)		Testes	Experimental value

### **Conclusion**

Not classified for reprotoxic or developmental toxicity

### **Toxicity other effects**

#### MULTIFIX CLEAR B

Classification is based on the relevant ingredients

#### butanone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study Skin

### **Conclusion**

Repeated exposure may cause skin dryness or cracking.

### **Chronic effects from short and long-term exposure**

#### MULTIFIX CLEAR B

Skin rash/inflammation.

### **11.2. Information on other hazards**

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### **12.1. Toxicity**

#### MULTIFIX CLEAR B

No (test) data on the mixture available

Classification is based on the relevant ingredients

# MULTIFIX CLEAR B

## butanone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2993 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	OECD 202	308 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1972 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1150 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value

## dibenzoyl peroxide

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	0.06 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	0.11 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	0.071 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
	NOEC	OECD 201	0.02 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	EC10	OECD 211	0.001 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC50	OECD 209	35 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

## Conclusion

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

### butanone

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	98 %; Oxygen consumption	28 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	96.295 h	1.5E6 /cm <sup>3</sup>	Calculated value

### dibenzoyl peroxide

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	71 %; GLP	28 day(s)	Experimental value

#### Half-life water (t1/2 water)

Method	Value	Primary degradation/mineralisation	Value determination
OECD 111	< 1 day(s); GLP	Primary degradation	Experimental value

## Conclusion

### Water

Does not contain any not readily biodegradable component(s)

## 12.3. Bioaccumulative potential

### MULTIFIX CLEAR B

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

### butanone

#### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.3	40 °C	Experimental value

# MULTIFIX CLEAR B

dibenzoyl peroxide

## BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
					Data waiving

## Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		3.2	22 °C	Experimental value

## Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

butanone

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.654 - 1.281	Calculated value

dibenzoyl peroxide

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	OECD 121	3.8	Experimental value

## Conclusion

Contains component(s) with potential for mobility in the soil  
Contains component(s) that adsorb(s) into the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

MULTIFIX CLEAR B

### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

butanone

### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.  
Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09\* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

UN number 1193

#### 14.2. UN proper shipping name

Proper shipping name ethyl methyl ketone (methyl ethyl ketone), solution

#### 14.3. Transport hazard class(es)

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

11 / 15

# MULTIFIX CLEAR B

Hazard identification number	33
Class	3
Classification code	F1
<b>14.4. Packing group</b>	
Packing group	II
Labels	3
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	yes
<b>14.6. Special precautions for user</b>	
Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Rail (RID)

<b>14.1. UN number</b>	
UN number	1193
<b>14.2. UN proper shipping name</b>	
Proper shipping name	ethyl methyl ketone (methyl ethyl ketone), solution
<b>14.3. Transport hazard class(es)</b>	
Hazard identification number	33
Class	3
Classification code	F1
<b>14.4. Packing group</b>	
Packing group	II
Labels	3
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	yes
<b>14.6. Special precautions for user</b>	
Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

<b>14.1. UN number</b>	
UN number	1193
<b>14.2. UN proper shipping name</b>	
Proper shipping name	ethyl methyl ketone (methyl ethyl ketone), solution
<b>14.3. Transport hazard class(es)</b>	
Class	3
Classification code	F1
<b>14.4. Packing group</b>	
Packing group	II
Labels	3
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	yes
<b>14.6. Special precautions for user</b>	
Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

<b>14.1. UN number</b>	
UN number	1193
<b>14.2. UN proper shipping name</b>	
Proper shipping name	ethyl methyl ketone (methyl ethyl ketone), solution
<b>14.3. Transport hazard class(es)</b>	
Class	3
<b>14.4. Packing group</b>	
Packing group	II
Labels	3
<b>14.5. Environmental hazards</b>	
Marine pollutant	P
Environmentally hazardous substance mark	yes
<b>14.6. Special precautions for user</b>	
Special provisions	
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	
Annex II of MARPOL 73/78	Not applicable, based on available data

## Air (ICAO-TI/IATA-DGR)

14.1. UN number

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

12 / 15

# MULTIFIX CLEAR B

UN number	1193
14.2. UN proper shipping name	
Proper shipping name	methyl ethyl ketone, solution
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	II
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	1 L

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
75 % - 90 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· butanone	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· butanone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· butanone · dibenzoyl peroxide	Substances falling within one or more of the following points: (a) substances classified as any of the	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

13 / 15

# MULTIFIX CLEAR B

following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:

- carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation
- reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation
- skin sensitiser category 1, 1A or 1B
- skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2
- serious eye damage category 1 or eye irritant category 2

(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council

(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.

The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

## National legislation Belgium

MULTIFIX CLEAR B

No data available

## National legislation The Netherlands

MULTIFIX CLEAR B

Waterbezwaarlijkheid	B (1); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

butanone

Huidopname (wettelijk)	2-Butanon; H
------------------------	--------------

## National legislation France

MULTIFIX CLEAR B

No data available

butanone

Risque de pénétration percutanée	Méthyléthylcétone; Risque de pénétration percutanée
----------------------------------	---

## National legislation Germany

MULTIFIX CLEAR B

Lagerklasse (TRGS510)	3: Entzündbare Flüssigkeiten
-----------------------	------------------------------

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

butanone

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	Butanon; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

Hautresorptive Stoffe	Butanon; H; Hautresorptiv
-----------------------	---------------------------

dibenzoyl peroxide

TA-Luft	5.2.5/I
---------	---------

## National legislation United Kingdom

MULTIFIX CLEAR B

No data available

butanone

Skin absorption	Butan-2-one (methyl ethyl ketone); Sk
-----------------	---------------------------------------

## Other relevant data

MULTIFIX CLEAR B

No data available

dibenzoyl peroxide

IARC - classification	3; Benzoyl peroxide
-----------------------	---------------------

TLV - Carcinogen	Benzoyl peroxide; A4
------------------	----------------------

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 2, 3.2, 8, 9, 12

Publication date: 2001-01-06

Date of revision: 2021-07-18

Revision number: 0900

BIG number: 33431

14 / 15

# MULTIFIX CLEAR B

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

- H225 Highly flammable liquid and vapour.
- H241 Heating may cause a fire or explosion.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.