



Tire Sealant

LIQUID RUBBER TO SEAL TIRE BEADS OF TUBELESS TIRES

- ✓ Seals holes in wheel rims due to damage or oxidation.
- ✓ Apply to the tire and not to the wheel rim.
- ✓ Adapts to each shape and seals immediately.

Technical Info

Base: rubber.
 Form: liquid.
 Smell: solvent.
 Colour: black.
 Boiling point: +98°C.
 Flash point: -4°C.
 Relative vapor density: > 1.
 Vapor pressure at +20°C: 53 hPa.
 Relative density: 0.84.
 Shelf life: 24 months, dry, cool and frost-free.
 Safety measures: Please consult the safety data sheet.

Packing

Tire Sealant - bottle 0.95L

711000000

Product [TRS]

Characteristics

Tire Sealant is a black sealant based on rubber and is developed specially for solving a lot of sealant problems. Tire Sealant is the ideal solution for strong leaks between tubeless tires and wheel rims: for private cars, truck, busses, motorcycles, Tire Sealant sticks to the tire and not to the wheel rim, so that the dismantling is easy.

Use

- Clean the tire bead and the wheel rim with a clean cloth, moistened by Novatio Safety Clean.
- Apply a small layer of the Tire Sealant to the tire bead. You can use the brush which is attached to the cap. For larger damages you need to apply a second layer.
- Let it dry for +/- 5 minutes.
- Mount the tire, inflate the tire to the right tension and check for leaks.

