



Seal & Bond Flex-Sil

Adhesives and sealants

S

LIQUID, NON-HARDENING GASKET

- ✓ Snelle ingebruikname: 10 tot 15 minuten.
- ✓ Ook makkelijk verticaal toepasbaar.
- ✓ Weerstaat hoge en lage temperaturen.
- ✓ Voor alle metalen en kunststoffen.

Technical Info

- Base: polyurethane.
- Colour: red.
- Isocyanate and siliconefree.
- Resistant to: all mineral and synthetic oils, greases, fuel, diesel, petrol, water, sea water, gas, air, coolant, antifreeze, ...
- Temperature resistance: from -55°C to +270°C, with peaks up to +300°C.
- Shelf life: 60 months, keep dry, cool and frost-free.

Packing

Seal & Bond Flex-Sil S red - cartridge 200ml 570005000

Product [SBFS]

Characteristics

Seal & Bond Flex-Sil S is a singlecomponent sealant that does not harden, is easy to remove, which provides the perfect sealing solution. Seal & Bond Flex-Sil S replaces other seals or improves them and can therefore be universally used for clearances up to 0.2 mm. Seal & Bond Flex-Sil S is ideal for applications with different combinations of materials subject to temperature fluctuations and movements.

Applications

- Suitable for applications such as in gear boxes and crankcases, flange joints, oil pans, and differentials.
- Application areas: automotive, chemical, and petrochemical industry, gas, water, and power plants.

Use

- Clean and degrease material requiring sealing using Safety Clean or Kleenspray-S.
- Apply sufficient Seal & Bond Flex-Sil S and let evaporate for 10 minutes before attaching.
- Observe a drying time of 10 to 15 minutes before putting into operation.