



Nova Clear Tape

TRANSPARENT AND SELF-ADHESIVE PU-FILM

- ✓ High quality polyurethane film with acrylic glue.
- ✓ Protects against chemical pollution, grit, rust, scratches,...
- ✓ Protects against wear by vibration and friction.
- ✓ Thanks to its elasticity of 75% it can be moulded into many shapes.
- ✓ Temperature resistance of -40°C to +90°C.
- ✓ Long-life product.
- ✓ Ideal on hard surface.
- ✓ Can be lacquered and/or varnished.
- ✓ Protects aluminium, stainless steel, chromium plate, PU, glass, lacquer, acrylic plastic, ABS,...
- ✓ Prevents squeaking and improves the impact resistance.

Technical Info

- Film: polyurethane.
- Glue: acrylic glue.
- Colour: transparent.
- Application temp.: +8°C to +50°C.
- Temp. resistance: -40°C to +90°C.
- Tensile strength: 13,5 N/mm².
- Elasticity: > 75%.
- Conservation of quality: for 7 years.
- Adherence to: raw aluminium, anodised aluminium, stainless steel, chromed steel, polyurethane, glass, acrylic, ABS,...
- Important: do not apply on soft surfaces or surfaces that can brake, peel, shrink or expand.
- Time Grade Bonding 20 min. 90° >900 N/m 20 min. 180° >600 N/m 24 h 90° >530 N/m 24 h 180° >700 N/m.
- First test foundations based on PE, PP, silicones and bitumen for adhesion.
- Shelf life: 24 months, keep dry, cool and frost-proof.

Packing

Nova Clear Tape - roll 15cm / 2m	566315000
Nova Clear Tape - roll 30cm / 2m	566330000

Product

Characteristics

- A high quality, transparent polyurethane film with acrylic glue.
- Adheres to most synthetics, lacquers, types of metal,... and protects against rust, grit, scratches, friction, vibration, ...
- Is 100% transparent and can be moulded and painted.

Applications

Protects against:

- rust
- grit
- scratches
- friction
- vibrations

