



XPR-90 Wax & Glue Remover Fenster und Türen

REMOVAL OF GLUE AND WAX

- ✓ Does not run or drip.
- ✓ Long working time.
- ✓ With powerful lime extracts.

Technische Informationen

- Composition: aliphatic hydrocarbon solvent, binder, and citrus extracts.
- Boiling point/boiling range °C: 130 - 166.
- Vapour pressure/20°C hPa: 4.6.
- Relative density/20°C: 0.75.
- Physical state/20°C: liquid.
- Flashpoint °C: 24.
- Self-combustion °C: 200.
- Water solubility: insoluble.
- Odour: distinctive.
- Dynamic viscosity mPa.s/20°C: 1.
- Kinematic viscosity, mm²/s/20°C: 1.
- Volatile organic compound (VOC) %: 97.
- Storage life: 36 months dry, cool and frostfree.
- Safety measures: consult the Safety Data Sheet.

Verpackung

XPR-90 Wax & Glue Remover Fenster und Türen 683830112

Produkt [90-WG R&D]

Eigenschaften

In gel form is safe and versatile and also suitable for vertical applications.

An aliphatic hydrocarbon solvent with added lime extracts.

Anwendungen

Safe to use on most materials and has been developed for the removal of wax and glue, even hardened silicones.

Verwendung

- Apply and allow time for it to work.
- Rub off the loosened silicone.
- If necessary, repeat the treatment.

- Rinse the cleaned surface with Multifoam.