SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

NANO CARE TEXTILE AEROSOL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: NANO CARE TEXTILE AEROSOL Product name **Registration number REACH** : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Moisture-repellent compound

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*

Industrielaan 5B

B-2250 Olen

2 +32 14 25 76 40

4 +32 14 22 02 66

info@novatio.be

*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements







Contains: hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; hydrocarbons, C6, isoalkanes, < 5% n-hexane.

ignal word	Danger
------------	--------

H-statements

Extremely flammable aerosol. H222

H229 Pressurised container: May burst if heated.

Causes skin irritation. H315

May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

P-statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: 2; 3; 5; 15 Revision number: 0400

Publication date: 2013-08-08 Date of revision: 2019-04-02

1/19

Product number: 44063

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves, protective clothing and eye protection/face protection.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 01-2119475515-33		C ≤ 50%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent
hydrocarbons, C6, isoalkanes, <5% n-hexane 01-2119484651-34		C ≤ 30 %	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent
n-hexane 01-2119480412-44	110-54-3 203-777-6	C ≤ 2 %	Flam. Liq. 2; H225 Repr. 2; H361f Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(8)(10)	Constituent
cyclohexane 01-2119463273-41	110-82-7 203-806-2	C ≤ 0.4 %	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(10)	Constituent
propane 01-2119486944-21	74-98-6 200-827-9	C ≤ 30%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant

⁽¹⁾ For H-statements in full: see heading 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Do not apply (chemical) neutralizing agents without medical advice. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Headache. Dizziness. Narcosis.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 2 / 19

⁽²⁾ Substance with a Community workplace exposure limit

⁽⁸⁾ Specific concentration limits, see heading 16

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Redness of the eye tissue.

After ingestion:

Headache. Abdominal pain. Vomiting. Diarrhoea.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (not alcohol-resistant).

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Prevent evaporation by covering with: sand, saw dust, kieselguhr. Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Protect against frost. Ventilation at floor level. Fireproof storeroom. Keep out of direct sunlight. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08
Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 3 / 19

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Cyclohexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	700 mg/m³
n-Hexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	72 mg/m³

Belgium

Cyclohexane	Time-weighted average exposure limit 8 h	100 ppm
	Time-weighted average exposure limit 8 h	350 mg/m³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
n-Hexane	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	72 mg/m³

The Netherlands

Cyclohexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	700 mg/m³
	Short time value (Public occupational exposure limit value)	400 ppm
	Short time value (Public occupational exposure limit value)	1400 mg/m³
n-Hexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	72 mg/m ³
	Short time value (Public occupational exposure limit value)	40 ppm
	Short time value (Public occupational exposure limit value)	144 mg/m³

France

Cyclohexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	700 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	375 ppm
	Short time value (VL: Valeur non réglementaire indicative)	1300 mg/m³
n-Hexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	72 mg/m³

Germany

Cyclohexan	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm	
	Time-weighted average exposure limit 8 h (TRGS 900)	700 mg/m³	
n-Hexan	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm	
	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m³	
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm	
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³	

UK

OK .		
Cyclohexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	100 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	350 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1050 mg/m³
n-Hexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	20 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	72 mg/m³

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08
Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 4 / 19

USA (TLV-ACGIH)

Cyclohexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	100 ppm
n-Hexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Cyclohexan (1,2-Cyclohexandiol (nach Hydrolyse))	5 1	Kreatinin	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Hexan (n-Hexan) (2,5-Hexandion plus 4,5-Dihydroxy-2-Hexanon (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende		5/2013 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG

USA (BEI-ACGIH)

n-Hexane (2,5-Hexanedion) Urine: end of shift 0,5 mg/L

8.1.2 Sampling methods

Product name	Test	Number
Cyclohexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
Cyclohexane	OSHA	1022
Cyclohexane	OSHA	7
n-Hexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
n-Hexane (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
n-Hexane (Volatile Organic compounds)	NIOSH	2549
n-Hexane	OSHA	2248
n-Hexane	OSHA	7

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

cyclohexane

<u>DNEL/DMEL - Workers</u> <u>hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</u>

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	2085 mg/m³	
	Long-term systemic effects dermal	300 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Effect level (DNEL/DMEL)	Туре	Value	Remark
	DNEL	Long-term systemic effects inhalation	5306 mg/m³	
		Long-term systemic effects dermal	13964 mg/kg bw/day	
n	<u>-hexane</u>			

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	75 mg/m³	
	Long-term systemic effects dermal	11 mg/kg bw/day	

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	700 mg/m³	
	Acute systemic effects inhalation	1400 mg/m³	
	Long-term local effects inhalation	700 mg/m³	
	Acute local effects inhalation	1400 mg/m³	
	Long-term systemic effects dermal	2016 mg/kg bw/day	

<u>DNEL/DMEL - General population</u> hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	447 mg/m ³	
	Long-term systemic effects dermal	149 mg/kg bw/day	
	Long-term systemic effects oral	149 mg/kg bw/day	
hydrocarbons, C6, isoalkanes, < 5% n-hexane			

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	1131 mg/m³	
	Long-term systemic effects dermal	1377 mg/kg bw/day	
	Long-term systemic effects oral	1301 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	16 mg/m³	
	Long-term systemic effects dermal	5.3 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Revision number: 0400 Product number: 44063

Date of revision: 2019-04-02

5/19

cyclohexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	206 mg/m³	
	Acute systemic effects inhalation	412 mg/m³	
	Long-term local effects inhalation	206 mg/m³	
	Acute local effects inhalation	412 mg/m³	
	Long-term systemic effects dermal	1186 mg/kg bw/day	
	Long-term systemic effects oral	59.4 mg/kg bw/day	

PNEC

cyclohexane

Compartments	Value	Remark
Fresh water	0.207 mg/l	
Marine water	0.207 mg/l	
Aqua (intermittent releases)	0.207 mg/l	
STP	3.24 mg/l	
Fresh water sediment	16.68 mg/kg sediment dw	
Marine water sediment	16.68 mg/kg sediment dw	
Soil	3.38 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN374).

	Measured breakthrough time	Thickness	Protection index
nitrile rubber	> 480 minutes	0.35 mm	Class 6

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid in aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour
Particle size	No data available
Explosion limits	1.1 - 9.5 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C
Kinematic viscosity	1 mm²/s ; 20 °C
Melting point	0 °C
Boiling point	-42 °C - 95 °C
Evaporation rate	7 ; Butyl acetate ; Liquid
Relative vapour density	No data available
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.689 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	413 °C
Flash point	-20 °C
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08
Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 6 / 19

9.2. Other information

Absolute density 689 kg/m³; 20 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50		> 5840 mg/kg bw		Rat (male /	Read-across	
					female)		
Dermal	LD50	Other	> 2800 mg/kg bw	24 h	Rat (male /	Read-across	
					female)		
Inhalation (vapours)	LC50	Equivalent to OECD	> 23.3 mg/l air	4 h	Rat (male /	Read-across	
		403	_		female)		

drocarbons, C6, isoalkanes, < 5% n-hexane									
Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark		
						determination			
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across			
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across			
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.354 mg/l	4 h	Rat (male)	Read-across			

<u>exane</u>							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	16000 mg/kg bw		Rat (male /	Experimental value	
		401			female)		
Dermal	LD50	Equivalent to OECD	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
		402					
Inhalation (vapours)	LC50	Equivalent to OECD	> 5000 ppm	24 h	Rat (male)	Experimental value	
		403					

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08
Date of revision: 2019-04-02

 Revision number: 0400
 Product number: 44063
 7 / 19

cyclohexane

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw		Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 32.88 mg/l air	4 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 19.07 mg/l	4 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Not irritating			7 days	Rabbit	Read-across	Single treatment
Skin	0	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye		Equivalent to OECD 405	72 h	72 hours	Rabbit	Read-across	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Not irritating	Equivalent to OECD 405		72 hours	Rabbit	Read-across	
Skin	Slightly irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Read-across	
Skin	Irritating; category 2					Annex VI	

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

cyclohexane

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Slightly irritating	Equivalent to OECD 405		1 hour	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating; category 2					Annex VI	
Inhalation	Irritating					Literature study	

Conclusion

Causes skin irritation.

Not classified as irritating to the eyes

Respiratory or skin sensitisation

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method		Species	Value determination	Remark
			point			
Skin	Not sensitizing	Equivalent to OECD 406	24; 48 hours	Guinea pig (male / female)	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark
				point			
Skin	Not sensitizing	Equivalent to OECD			Mouse (male /	Read-across	
		429			female)		

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08 Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 8/19

n-hexane

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429		Mouse	Read-across	

cyclohexane

Route of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark
				point			
Skin	Not sensitizing	EU Method B.6		24; 48 hours	Guinea pig (male	Experimental value	
					/ female)		

Conclusion

Not classified as sensitizing for skin

Specific target organ toxicity

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	12350 mg/m³ air			26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (vapours)	LOAEL		1650 mg/m³ air	Central nervous system		26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10504 mg/m³ air			13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 413	31652 mg/m ³ air	Liver; kidney	6	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across

n-hexane

Route of	Parameter	Method	Value	Organ	Effect	Exposure time		Value
exposure								determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	567 mg/kg bw/day - 1135 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rat (male)	Experimental value
Oral (stomach tube)	LOAEL	Subchronic toxicity test	3956 mg/kg bw/day			17 weeks (5 days / week)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Subchronic toxicity test	3000 ppm	Central nervous system	Impairment of the nervous system	16 weeks (daily)	Rat (male)	Experimental value
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Literature study

cyclohexane

Route of	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
exposure								
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)		EPA OPPTS 870.3465	7000 ppm			13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)		EPA OPPTS 870.3465	500 mg/m³ air	Central nervous system	No effect	6 h	Rat (male / female)	Experimental value

Conclusion

May cause drowsiness or dizziness. Not classified for subchronic toxicity

Mutagenicity (in vitro)

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Date of revision: 2019-04-02

 Revision number: 0400
 Product number: 44063
 9 / 19

lesult	Method	Test substrate	Effect	Value determination
Negative with metabolic	OECD 476	Human lymphocytes	No effect	Read-across
activation, negative without				
metabolic activation				
ocarbons, C6, isoalkanes, < 59	<u>% n-hexane</u>	•		•
Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across
activation, negative without				
metabolic activation				
<u>exane</u>				·
Result	Method	Test substrate	Effect	Value determination
Negative	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
<u>ohexane</u>			•	<u> </u>
Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
activation, negative without				'
metabolic activation				
Negative with metabolic	Equivalent to OECD 476	Mouse (lymphoma L5178Y	No effect	Experimental value
activation, negative without		cells)		
metabolic activation			1	

Mutagenicity (in vivo)

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

<u>hydrocarbons, C6, isoalkanes, < 5% n-hexane</u>

	Result	Method	Exposure time	Test substrate	Organ	Value determination
	Negative (Inhalation (vapours))	Equivalent to OECD	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value
		475				
<u>n-h</u>	<u>exane</u>					
	Result	Method	Exposure time	Test substrate	Organ	Value determination
	Negative		8 weeks (6h / day, 5	Mouse (male)		Experimental value
			days / week)			
cyc	<u>lohexane</u>					
	Result	Method	Exposure time	Test substrate	Organ	Value determination
	Negative	Equivalent to OECD 475	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

il Ocal Bolls, C7	, 11 dikunca, 130	aikaries, cyclies						
Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation	NOAEC	Equivalent to	9016 ppm	104 weeks (6h / day,	Rat (male /	No carcinogenic		Experimental
(vapours)		OECD 451		5 days / week)	female)	effect		value

n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
exposure								
Inhalation	NOAEC	Equivalent to	3000 ppm	104 weeks (6h / day,	Mouse (female)	No carcinogenic		Read-across
(vapours)		OECD 451		5 days / week)		effect		
Inhalation	LOAEC	Equivalent to	9018 ppm	104 weeks (6h / day,	Mouse (female)	Tumor	Liver	Read-across
(vapours)		OECD 451		5 days / week)		formation		
Inhalation	NOAEC	Equivalent to	9018 ppm	104 weeks (6h / day,	Mouse (male)	No carcinogenic		Read-across
(vapours)		OECD 451		5 days / week)		effect		

Conclusion

Reason for revision: 2; 3; 5; 15

Publication date: 2013-08-08

Date of revision: 2019-04-02

 Revision number: 0400
 Product number: 44063
 10 / 19

Not classified for carcinogenicity

Reproductive toxicity

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients <u>hydrocarbons</u>, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	31680 mg/m³ air	10 days (6h / day)	Mouse	No effect		Read-across
Maternal toxicity	NOAEL	Equivalent to OECD 414	10560 mg/m³ air	10 days (6h / day)	Rat (female)	No effect		Read-across
	LOAEL	Equivalent to OECD 414	31680 mg/m³ air	10 days (6h / day)	Rat (female)	Lung tissue affection/degen eration	Lungs	Read-across
Effects on fertility	NOAEL (P/F1)	Equivalent to OECD 416	31680 mg/m³ air		Rat (male / female)	No effect		Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	- 0.	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	> 7000 ppm	10 days (6h / day)	Rat	No effect		Read-across
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h / day)	Rat (female)	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm		Rat (male / female)	No effect		Read-across

<u>n-hexane</u>

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEC	Equivalent to OECD 414	3000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	LOAEL	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	Weight gain		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm	≥ 13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

cyclohexane

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	7000 ppm	10 days (6h / day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h / day)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEC	Equivalent to OECD 416	7000 ppm	> 11 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
							determination
NOAEC	Equivalent to OECD 424	9000 ppm	Central nervous system		13 weeks (6h / day, 5 days / week)	l _ ' ' ' ' . ' . ' ' '	Experimental value

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08 Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 11 / 19

<u>cyclohexane</u>

Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
NOAEC	Other	2000 ppm		neurotoxic effects	6 h	 Experimental value
LOAEC	Other	7000 ppm		neurotoxic effects	6 h	 Experimental value

Chronic effects from short and long-term exposure

NANO CARE TEXTILE AEROSOL

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

NANO CARE TEXTILE AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 13.4 mg/l WAF	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	3.0 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	29 mg/I WAF	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR		1.534 mg/l	28	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	0.17 mg/l WAF	21 day(s)	Daphnia magna	Static system	Fresh water	Read-across; GLP
	EL50	OECD 211	1.6 mg/l WAF	21 day(s)	Daphnia magna	Static system	Fresh water	Read-across
Toxicity aquatic micro- organisms	EL50		26.81 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth rate

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		18.27 mg/l	96 h	Oncorhynchus mykiss		Fresh water	QSAR
Acute toxicity crustacea	EL50		31.9 mg/l	48 h	Daphnia magna		Fresh water	QSAR
Toxicity algae and other aquatic plants	EL50		13.56 mg/l	72 h	Pseudokirchneri ella subcapitata		Fresh water	QSAR
Long-term toxicity fish	NOELR		4.089 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		7.138 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

Classification of this substance is debatable as it does not correspond to the conclusion from the test

<u>n-hexan</u>e

<u>i-nexane</u>								
	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		12.51 mg/l	96 h	Oncorhynchus mykiss		Fresh water	Estimated value; Nominal concentration
Acute toxicity crustacea	EL50		21.85 mg/l	48 h	Daphnia magna		Fresh water	Estimated value; Nominal concentration
Toxicity algae and other aquatic plants	EL50		9.285 mg/l	72 h	Pseudokirchneri ella subcapitata		Fresh water	Estimated value; Growth rate
Long-term toxicity fish	NOELR		2.8 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	Estimated value; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		4.888 mg/l	21 day(s)	Daphnia magna		Fresh water	Estimated value; Nominal concentration

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 12 / 19

cyclohexane

	Davamatas	Method	Value	Duration	Cuasias	Took dealers	Funch /nalk	Value determination
	Parameter	Ivietnoa	value	Duration	Species	Test design	Fresh/salt water	value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	4.53 mg/l	96 h	Pimephales promelas	Flow- through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	EC50	Equivalent to OECD 202	0.9 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	Equivalent to OECD 201	9.317 mg/l	72 h	Pseudokirchneri ella subcapitata			Experimental value; GLP
	NOEC	OECD 201	0.94 mg/l	72 h	Pseudokirchneri ella subcapitata			Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro- organisms	IC50		29 mg/l	15 h	Aerobic micro- organisms			Experimental value; Nominal concentration

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation water

Method	Value	Duration	Value determination	
OECD 301F: Manometric Respirometry Test	98 %; GLP	28 day(s)	Experimental value	
OLCD 301F. Manometric Respirometry Test	36 %, GLF		Experimental value	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Biodegradation water

Method	Value	Duration	Value determination	
OECD 301F: Manometric Respirometry Test	98 %; GLP	28 day(s)	Read-across	

n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	98 %; GLP	28 day(s)	Read-across

Biodegradation soil

Method	Value	Duration	Value determination
			Data waiving

cyclohexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	77 %; GLP	28 day(s)	Experimental value

Half-life soil (t1/2 soil)

Method		Primary degradation/mineralisation	Value determination
	28 day(s) - 180 day(s)		Literature study

Conclusion

Does not contain any not readily biodegradable component(s)

12.3. Bioaccumulative potential

NANO CARE TEXTILE AEROSOL

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Log Kow

Method	Remark	Value	Temperature	Value determination
		> 3		

Reason for revision: 2; 3; 5; 15

Publication date: 2013-08-08

Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 13 / 19

hydrocarbons, C6, isoalkanes, < 5% n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		501.187		Pimephales promelas	Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		3.6	20 °C	Read-across

n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	Other	501.187		Pimephales promelas	QSAR

Log Kow

Method	Remark	Value	Temperature	Value determination	
Equivalent to OECD 107		4	20 °C	Experimental value	

cyclohexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		167		Pimephales promelas	QSAR

Log Kow

Method	Remark	Value	Temperature	Value determination
Other			25 °C	Experimental value

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	96 %	0 %	1.8 %	0.55 %	1.4 %	Calculated value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

(log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	Calculated value

Percent distribution

	Method	Fraction air	Fraction biota	Fraction	Fraction soil	Fraction water	Value determination	
				sediment				
	Mackay level III	93.6 %	0 %	2.1 %	0.5 %	3.8 %	Calculated value	
n-h	n-hexane							

(log) Koc

0/			
Parameter	Method	Value	Value determination
log Koc		3.34	QSAR

Percent distribution

. c. cciic aisti ibation	Citati distribution					
Method	Fraction air	Fraction biota	Fraction	Fraction soil	Fraction water	Value determination
			sediment			
Mackay level III	91.6 %	0 %	0.7 %	2.8 %	4.9 %	Calculated value

cyclohexane

(log) Koc

-			
Parameter	Method	Value	Value determination
log Koc		2.89	QSAR

Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

NANO CARE TEXTILE AEROSOL

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

cyclohexane

Groundwater

Groundwater pollutant

Reason for revision: 2; 3; 5; 15

Publication date: 2013-08-08

Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 14 / 19

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

14 06 03* (waste organic solvents, refrigerants and foam/aerosol propellants: other solvents and solvent mixtures). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road	(ADR)	١
------	-------	---

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	yes
14. <u>6. Special precautions for user</u>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

an (mb)	
14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number	
UN number	1950

Reason for revision: 2; 3; 5; 15

Publication date: 2013-08-08

Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 15 / 19

14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	ACT 03013
Class	2
Classification code	5F
	jor
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	yes
14. <u>6. Special precautions for user</u>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
Limited quantities	liquids. A package shall not weigh more than 30 kg. (gross mass)
(IMDG/IMSBC)	
14.1. UN number	
UN number	1950
14.2. UN proper shipping name	-
Proper shipping name	aerosols
14.3. Transport hazard class(es)	1
Class	2.1
	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Annex II of MARPOL 73/78	Not applicable
(ICAO-TI/IATA-DGR) I4.1. UN number	
UN number	1950
14.2. UN proper shipping name	1
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	, ici osolo, nummuoic
Class	2.1
	L.1
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
95.12 %	

Reason for revision: 2; 3; 5; 15

Publication date: 2013-08-08

Date of revision: 2019-04-02

Revision number: 0400 Product number: 44063 16 / 19

636.752 g/l

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	substances, mixtures and articles.	n (EC) No 1907/2006: restrictions on the manufacture, placing on the market
and use of certain dangerous	Designation of the substance, of the group of	Conditions of restriction
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics hydrocarbons, C6, isoalkanes, < 5% n-hexane n-hexane cyclohexane	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the pre
		ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public.
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics hydrocarbons, C6, isoalkanes, < 5% n-hexane n-hexane cyclohexane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· cyclohexane	Cyclohexane	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g. 2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010. 3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows: "— This product is not to be used under conditions of poor ventilation. — This product is not to be used for carpet laying.".

NANO CARE TEXTILE AEROSOL

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Date of revision: 2019-04-02

 Revision number: 0400
 Product number: 44063
 17 / 19

No data available

National legislation The Netherlands NANO CARE TEXTILE AEROSOL

	Waterbezwaarlijkheid	A (2); Algemene Beoordelingsmethodiek (ABM)
<u>n</u>	<u>-hexane</u>	
	SZW - Lijst van voor de	n-Hexaan; 2; Suspected of damaging fertility.
	voortplanting giftige stoffen	
	(vruchtbaarheid)	

National legislation France

NANO CARE TEXTILE AEROSOL

No data available

n-hexane

Catégorie toxique pour la	n-Hexane; R2
reproduction	

National legislation Germany NANO CARE TEXTILE AEROSOL

WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
TA-Luft	5.2.5/I	
hydrocarbons, C6, isoalkanes, < 5% n-hexane		
TA-Luft	5.2.5/I	
<u>n-hexane</u>		
TA-Luft	5.2.5/I	
TRGS900 - Risiko der	n-Hexan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen	
Fruchtschädigung	Grenzwertes nicht befürchtet zu werden	
cyclohexane		
TA-Luft	5.2.5/I	

National legislation United Kingdom

NANO CARE TEXTILE AEROSOL

No data available

Other relevant data

NANO CARE TEXTILE AEROSOL

No data available

n-hexane

in absorution In Ha	ICI:
in ansorbiion in-ne	I NKI
in absorption In-Hex	lSki

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(*) INTERNAL CLASSIFICATION BY BIG ADI Acceptable daily intake

AOEL Acceptable operator exposure level

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level DNEL Derived No Effect Level EC50 Effect Concentration 50 %

FrC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

Persistent, Bioaccumulative & Toxic PRT

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Revision number: 0400 Product number: 44063

Date of revision: 2019-04-02

18 / 19

PNEC Predicted No Effect Concentration
STP Sludge Treatment Process
vPvB very Persistent & very Bioaccumulative

M-factor

cyclohexane 1 Acute ECHA

Specific concentration limits CLP

n-hexane C≥ 5 % STOT RE 2; H373 CLP Annex VI (ATP 0)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2; 3; 5; 15 Publication date: 2013-08-08

Date of revision: 2019-04-02

 Revision number: 0400
 Product number: 44063
 19 / 19