

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

POWERSOLV

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : POWERSOLV
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Cleansing product

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)
Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2166 (Public 8 am- 10 pm)
Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2566 (Professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 2	H225: Highly flammable liquid and vapour.
Acute Tox.	category 4	H332: Harmful if inhaled.
Skin Irrit.	category 2	H315: Causes skin irritation.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.

2.2. Label elements



Contains: 4-hydroxy-4-methylpentan-2-one; propan-2-ol; n-butyl acetate; 2-methoxy-1-methylethyl acetate; 2-butoxyethanol.

Signal word Danger

H-statements

H225 Highly flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

POWERSOLV

P-statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves, protective clothing and eye protection/face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
4-hydroxy-4-methylpentan-2-one	123-42-2 204-626-7	C≤40%	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Eye Irrit. 2; H319: C≥10%, (CLP Annex VI (ATP 0))	(1)(2)(6)(10)	Constituent	
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C≤30%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
n-butyl acetate 01-2119485493-29	123-86-4 204-658-1	C≤20%	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
2-methoxy-1-methylethyl acetate 01-2119475791-29	108-65-6 203-603-9	C≤20%	Flam. Liq. 3; H226 STOT SE 3; H336	(1)(2)(6)(10)	Constituent	
2-butoxyethanol 01-2119475108-36	111-76-2 203-905-0	C≤10%	Acute Tox. 3; H331 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(2)(10)	Constituent	ATE inhalation (vapour): 3 mg/l ATE oral: 1200 mg/kg

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Dizziness. Drowsiness.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

2 / 25

POWERSOLV

Irritation of the eye tissue.

After ingestion:

Gastrointestinal complaints. Headache. Drowsiness.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (not alcohol-resistant).

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers.

Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Observe normal hygiene standards. Keep container tightly closed. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Protect against frost. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents, reducing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

POWERSOLV

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	98 mg/m ³
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	246 mg/m ³
2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	275 mg/m ³
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	550 mg/m ³
n-Butyl acetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	241 mg/m ³
	Short time value (Indicative occupational exposure limit value)	150 ppm
	Short time value (Indicative occupational exposure limit value)	723 mg/m ³

Belgium

2-Butoxyéthanol	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	98 mg/m ³
	Short time value	50 ppm
	Short time value	246 mg/m ³
4-Hydroxy-4-méthyl-2-pentanone	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	241 mg/m ³
Acétate de 2-(1-méthoxy)propyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	275 mg/m ³
	Short time value	100 ppm
	Short time value	550 mg/m ³
Acétate de butyle, tous isomères: n-, iso, sec, tert	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	238 mg/m ³
	Short time value	150 ppm
	Short time value	712 mg/m ³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m ³
	Short time value	400 ppm
	Short time value	1000 mg/m ³

The Netherlands

1-Methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	550 mg/m ³
2-Butoxyethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20.4 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 mg/m ³
	Short time value (Public occupational exposure limit value)	50 ppm
	Short time value (Public occupational exposure limit value)	246 mg/m ³
n-Butylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	241 mg/m ³
	Short time value (Public occupational exposure limit value)	150 ppm
	Short time value (Public occupational exposure limit value)	723 mg/m ³

POWERSOLV

France

2-Butoxyéthanol	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	10 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	49 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	246 mg/m ³
Acétate de 2-méthoxy-1-méthyléthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	275 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	550 mg/m ³
Acétate de n-butyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	241 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	150 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	723 mg/m ³
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m ³
Diacétone-alcool	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	50 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	240 mg/m ³

Germany

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TRGS 900)	10 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	49 mg/m ³ (1)
2-Methoxy-1-methylethylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	270 mg/m ³ (2)
	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm (2)
4-Hydroxy-4-methyl-pentan-2-on	Time-weighted average exposure limit 8 h (TRGS 900)	20 ppm (3)
	Time-weighted average exposure limit 8 h (TRGS 900)	96 mg/m ³ (3)
n-Butylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	300 mg/m ³ (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	62 ppm (1)
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm (4)
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m ³ (4)

- (1) UF: 2 (I)
 (2) UF: 1 (I)
 (3) UF: 2 (I)
 (4) UF: 2 (II)

Austria

1-Methoxypropylacetat-2	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	275 mg/m ³
	Kurzzeitwert 5(Mow) 8x (MAK)	100 ppm
	Kurzzeitwert 5(Mow) 8x (MAK)	550 mg/m ³
2-Butoxyethanol	Tagesmittelwert (MAK)	20 ppm
	Tagesmittelwert (MAK)	98 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	40 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	200 mg/m ³
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m ³
4-Hydroxy-4-methylpentan-2-on	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	240 mg/m ³
Butylacetat alle Isomere (außer tert-Butylacetat): Isobutylacetat n-Butylacetat sec-Butylacetat	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	241 mg/m ³
	Kurzzeitwert Mow (MAK)	100 ppm
	Kurzzeitwert Mow (MAK)	480 mg/m ³

POWERSOLV

UK

1-Methoxypropyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	274 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	548 mg/m ³
2-Butoxyethanol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	25 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	123 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	50 ppm
	Short time value (Workplace exposure limit (EH40/2005))	246 mg/m ³
4-Hydroxy-4-methylpentan-2-one	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	241 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	75 ppm
	Short time value (Workplace exposure limit (EH40/2005))	362 mg/m ³
Butyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	150 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	724 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	966 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m ³

Ireland

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	20 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	98 mg/m ³
	Short time value (Binding occupational exposure limit values)	50 ppm
	Short time value (Binding occupational exposure limit values)	246 mg/m ³
2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	50 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	275 mg/m ³
	Short time value (Binding occupational exposure limit values)	100 ppm
	Short time value (Binding occupational exposure limit values)	550 mg/m ³
Diacetone alcohol	Time-weighted average exposure limit 8 h (Advisory occupational exposure limit values)	50 ppm
	Time-weighted average exposure limit 8 h (Advisory occupational exposure limit values)	240 mg/m ³
Isopropyl alcohol	Time-weighted average exposure limit 8 h (Advisory occupational exposure limit values)	200 ppm
	Short time value (Advisory occupational exposure limit values)	400 ppm
n-Butyl acetate	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	50 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	241 mg/m ³
	Short time value (Binding occupational exposure limit values)	150 ppm
	Short time value (Binding occupational exposure limit values)	723 mg/m ³

USA (TLV-ACGIH)

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Butyl acetates, all isomers	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
	Short time value (TLV - Adopted Value)	150 ppm
Diacetone alcohol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	10 ppm
Propylene Glycol Monomethyl Ether Acetate	Time-weighted average exposure limit 8 h (WEEL)	50 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Reason for revision: 1; 2; 3; 4; 7; 8; 10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

6 / 25

POWERSOLV

Germany

2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))	Urin: am schichtende, bei langzeitexposition nach mehreren vorangegangenen schichten	150 mg/g Kreatinin	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

UK

2-Butoxyethanol (butoxyacetic acid)	Urine: post shift	240 mmol/mol creatinine	
-------------------------------------	-------------------	-------------------------	--

USA (BEI-ACGIH)

2-butoxyethanol (Butoxyacetic acid (BAA))	Urine: end of shift	200 mg/g creatinine	With hydrolysis
2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific

8.1.2 Sampling methods

Product name	Test	Number
1-Methoxy-2-Propyl Acetate	OSHA	99
2-Butoxyethanol (Alcohols IV)	NIOSH	1403
2-Butoxyethanol (Butyl Cellosolve solvent)	OSHA	83
2-Butoxyethanol	OSHA	5001
Butoxyacetic acid	NIOSH	8316
Butyl acetate (Volatile Organic compounds)	NIOSH	2549
Butyl cellosolve (Volatile Organic compounds)	NIOSH	2549
Butyl Cellosolve	OSHA	83
diacetone alcohol (Alcohols Combined)	NIOSH	1405
Diacetone Alcohol (Alcohols III)	NIOSH	1402
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	NIOSH	3900
Isopropyl Alcohol	OSHA	5001
n-Butyl Acetate (Esters I)	NIOSH	1450
n-Butyl Acetate	OSHA	1009
n-Butyl Acetate	OSHA	5000
Propylene glycol monomethyl ether acetate (glycol ethers)	NIOSH	2554

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

4-hydroxy-4-methylpentan-2-one

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	32.6 mg/m ³	
	Long-term local effects inhalation	240 mg/m ³	
	Long-term systemic effects dermal	467 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m ³	
	Acute systemic effects inhalation	1000 mg/m ³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	300 mg/m ³	
	Acute systemic effects inhalation	600 mg/m ³	
	Long-term local effects inhalation	300 mg/m ³	
	Acute local effects inhalation	600 mg/m ³	
	Long-term systemic effects dermal	11 mg/kg bw/day	
	Acute systemic effects dermal	11 mg/kg bw/day	

2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	275 mg/m ³	
	Acute local effects inhalation	550 mg/m ³	
	Long-term systemic effects dermal	796 mg/kg bw	

2-butoxyethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m ³	
	Acute systemic effects inhalation	1091 mg/m ³	
	Acute local effects inhalation	246 mg/m ³	

DNEL/DMEL - General population

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

7 / 25

POWERSOLV

4-hydroxy-4-methylpentan-2-one

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5.8 mg/m ³	
	Long-term systemic effects dermal	167 mg/kg bw/day	
	Long-term systemic effects oral	1.67 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m ³	
	Acute systemic effects inhalation	178 mg/m ³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	
	Acute systemic effects oral	51 mg/kg bw/day	

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	35.7 mg/m ³	
	Acute systemic effects inhalation	300 mg/m ³	
	Long-term local effects inhalation	35.7 mg/m ³	
	Acute local effects inhalation	300 mg/m ³	
	Long-term systemic effects dermal	6 mg/kg bw/day	
	Acute systemic effects dermal	6 mg/kg bw/day	
	Long-term systemic effects oral	2 mg/kg bw/day	
	Acute systemic effects oral	2 mg/kg bw/day	

2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	33 mg/m ³	
	Long-term local effects inhalation	33 mg/m ³	
	Long-term systemic effects dermal	320 mg/kg bw	
	Long-term systemic effects oral	36 mg/kg bw	
	Acute systemic effects oral	500 mg/kg bw/day	

2-butoxyethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m ³	
	Acute systemic effects inhalation	426 mg/m ³	
	Acute local effects inhalation	147 mg/m ³	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

PNEC

4-hydroxy-4-methylpentan-2-one

Compartments	Value	Remark
Fresh water	2 mg/l	
Marine water	0.2 mg/l	
Fresh water (intermittent releases)	1 mg/l	
STP	10 mg/l	
Fresh water sediment	7.4 mg/kg sediment dw	
Marine water sediment	0.74 mg/kg sediment dw	
Soil	0.31 mg/kg soil dw	

n-butyl acetate

Compartments	Value	Remark
Fresh water	0.18 mg/l	
Marine water	0.018 mg/l	
Fresh water (intermittent releases)	0.36 mg/l	
STP	35.6 mg/l	
Fresh water sediment	0.981 mg/kg sediment dw	
Marine water sediment	0.098 mg/kg sediment dw	
Soil	0.09 mg/kg soil dw	

2-methoxy-1-methylethyl acetate

Compartments	Value	Remark
Fresh water	0.635 mg/l	
Marine water	0.064 mg/l	
Fresh water (intermittent releases)	6.35 mg/l	
STP	100 mg/l	
Fresh water sediment	3.29 mg/kg sediment dw	
Marine water sediment	0.329 mg/kg sediment dw	
Soil	0.29 mg/kg soil dw	

POWERSOLV

2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Fresh water (intermittent releases)	26.4 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	0.02 g/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Colour	Colourless
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	No data available in the literature
Boiling point	82 °C - 173 °C
Flammability	Highly flammable liquid and vapour.
Explosion limits	1 - 15 vol %
Flash point	11 °C
Auto-ignition temperature	230 °C
Decomposition temperature	No data available in the literature
pH	Not applicable (non-soluble in water)
Kinematic viscosity	1 mm ² /s ; 40 °C
Dynamic viscosity	1 mPa.s ; 20 °C
Solubility	Water ; insoluble
Log Kow	Not applicable (mixture)
Vapour pressure	43 hPa ; 20 °C
Absolute density	883 kg/m ³ ; 20 °C
Relative density	0.88 ; 20 °C
Relative vapour density	No data available in the literature
Particle size	Not applicable (liquid)

9.2. Other information

Evaporation rate	1.3 ; Butyl acetate
------------------	---------------------

POWERSOLV

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges.

10.5. Incompatible materials

Oxidizing agents, reducing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

POWERSOLV

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
	ATE		< 20 mg/l				

Classification is based on the relevant ingredients

4-hydroxy-4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	3002 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC0	Equivalent to OECD 403	≥ 7.6 mg/l	4 h	Rat (male / female)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	13120 mg/kg bw/day	24 h	Rabbit	Experimental value	Converted value
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	10760 mg/kg bw - 12789 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 14112 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	OECD 403	> 21 mg/l	4 h	Rat (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	6190 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC0	Equivalent to OECD 403	> 1728 ppm	4 h	Rat (male / female)	Experimental value	

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

10 / 25

POWERSOLV

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	ATE		1200 mg/kg bw			Annex VI	
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50	OECD 401	1414 mg/kg bw		Guinea pig (male / female)	Experimental value	
Dermal	LC0	OECD 402	> 2000 mg/kg bw	24 h	Guinea pig (male / female)	Experimental value	
Inhalation (vapours)	ATE		3 mg/l			Annex VI	
Inhalation (saturated vapour)	Dose level	Equivalent to OECD 433	2.25 mg/l	4 h	Guinea pig (male / female)	Experimental value	No effect

Conclusion

Harmful if inhaled.

Not classified as acute toxic in contact with skin

Not classified as acute toxic if swallowed

Corrosion/irritation

POWERSOLV

No (test) data on the mixture available

Classification is based on the relevant ingredients

4-hydroxy-4-methylpentan-2-one

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	1 h	24; 48; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Eye	Irritating	Human observation	8 h		Human	Experimental value	100 ppm
Skin	Slightly irritating	Equivalent to OECD 404	24 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating; category 2					Literature study	
Inhalation	Irritating	Human observation	15 minutes		Human	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

n-butyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Respiratory or skin sensitisation

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

11 / 25

POWERSOLV

POWERSOLV

No (test)data on the mixture available

Judgement is based on the relevant ingredients

4-hydroxy-4-methylpentan-2-one

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Experimental value	

2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

POWERSOLV

No (test)data on the mixture available

Classification is based on the relevant ingredients

4-hydroxy-4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 408	600 mg/kg bw/day	No effect	13 weeks (daily)	Rat (male / female)	Experimental value	
Inhalation (vapours)	NOAEC	Equivalent to OECD 412	4685 mg/m ³ air	No effect	6 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral							Data waiving	
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm	No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system (drowsiness, dizziness)	6 h	Rat (male / female)	Experimental value	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	EPA OTS 798.2650	125 mg/kg bw/day	No effect	13 weeks (daily)	Rat (male / female)	Read-across	
Oral (stomach tube)	LOAEL	EPA OTS 798.2650	500 mg/kg bw/day	Central nervous system (central nervous system depression)	13 weeks (daily)	Rat (male / female)	Read-across	
Inhalation (vapours)	NOAEC	EPA OTS 798.2450	500 ppm	No adverse systemic effects	13 weeks (daily, 5 days / week)	Rat (male / female)	Experimental value	

Reason for revision: 1; 2; 3; 4; 7; 8; 10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

12 / 25

POWERSOLV

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 422	≥ 1000 mg/kg	No effect	41 day(s) - 45 day (s)	Rat (male / female)	Experimental value	
Oral (stomach tube)	Dose level	US EPA	500 mg/kg bw/day	Drowsiness, dizziness		Rat (male / female)	Experimental value	
Dermal	NOAEL	Equivalent to OECD 411	1838 mg/kg bw/day	No effect	13 weeks (5 days / week)	Rabbit (male)	Read-across	
Dermal	LOAEL	Equivalent to OECD 411	3676 mg/kg bw/day	Overall effects	13 weeks (6h / day, 5 days / week)	Rabbit (male)	Read-across	
Inhalation (vapours)	NOEL	OECD 453	300 ppm	No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 69 mg/kg bw/day	No effect	90 days (continuous)	Rat (male)	Experimental value	
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 82 mg/kg bw/day	No effect	90 day(s)	Rat (female)	Experimental value	
Dermal	NOAEL	Equivalent to OECD 411	> 150 mg/kg bw/day	No effect	13 weeks (5 days / week)	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	< 31 ppm	No effect	14 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value	
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	62.5 ppm	No effect	14 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value	

Conclusion

May cause drowsiness or dizziness.
Not classified for subchronic toxicity

Mutagenicity (in vitro)

POWERSOLV

No (test) data on the mixture available
Judgement is based on the relevant ingredients
4-hydroxy-4-methylpentan-2-one

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S. typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

n-butyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S. typhimurium)		Experimental value	

POWERSOLV

2-methoxy-1-methylethyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative without metabolic activation	Equivalent to OECD 482	Rat liver cells	No effect	Experimental value	

2-butoxyethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)		Experimental value	

Mutagenicity (in vivo)

POWERSOLV

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)	No effect	Experimental value	Single intraperitoneal injection

n-butyl acetate

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)	No effect	Read-across	Single treatment

2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474	3 dose(s)/24-hour interval	Mouse (male)	No effect	Experimental value	

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

POWERSOLV

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	> 125 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

POWERSOLV

No (test)data on the mixture available

Judgement is based on the relevant ingredients

POWERSOLV

4-hydroxy-4-methylpentan-2-one

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	≥ 1000 mg/kg bw/day	15 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	≥ 1000 mg/kg bw/day	15 days (gestation, daily)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 422	100 mg/kg bw/day	41 day(s) - 45 day (s)	Rat (male / female)	No effect	Experimental value	

propan-2-ol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 416	> 1000 mg/kg bw/day		Rat (male / female)	No effect	Experimental value	

n-butyl acetate

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Fetotoxicity	Experimental value	
Maternal toxicity (Inhalation (vapours))	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Maternal toxicity	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEC	OECD 416	2000 ppm	> 90 day(s)	Rat (male / female)	No effect	Experimental value	

2-methoxy-1-methylethyl acetate

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	> 4000 ppm	10 days (gestation, daily)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	500 ppm	10 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Inhalation (vapours))	LOAEL	Equivalent to OECD 414	2000 ppm	10 days (gestation, daily)	Rat	Maternal toxicity	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEL	OECD 416	300 ppm		Rat (male / female)	No effect	Read-across	

2-butoxyethanol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEC	Equivalent to OECD 414	200 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect	Experimental value	
Effects on fertility (Oral (drinking water))	NOAEL	Fertility Assessment	720 mg/kg bw/day		Mouse (male / female)	No effect	Experimental value	

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

POWERSOLV

Judgement is based on the relevant ingredients
Not classified for aspiration toxicity

Toxicity other effects

POWERSOLV

No (test)data on the mixture available

POWERSOLV

n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
	NOEC	EPA OTS 798.6050	1500 ppm	(hypoactivity)	6 h	Rat (male / female)	Experimental value	
	NOAEC	EPA OTS 798.6050	500 ppm	(no neurotoxic effects)	13 week(s)	Rat (male / female)	Experimental value	

Chronic effects from short and long-term exposure

POWERSOLV

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

POWERSOLV

No (test) data on the mixture available

Judgement of the mixture is based on the relevant ingredients

4-hydroxy-4-methylpentan-2-one

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oryzias latipes	Semi-static system	Fresh water	Experimental value
Acute toxicity crustacea	EC50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Semi-static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	Toxicity threshold	Other	825 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value
	EC50	OECD 209	> 1000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish	NOELR	Petrotox computer model	> 1000 mg/l	28 day(s)	Brachydanio rerio			Estimated value
Long-term toxicity aquatic crustacea	NOEC		141 mg/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

16 / 25

POWERSOLV

n-butyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	18 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	Equivalent to OECD 202	44 mg/l	48 h	Daphnia sp.	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	397 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; GLP
	NOEC	OECD 201	196 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; Growth rate
Long-term toxicity aquatic crustacea	NOEC	OECD 211	23.2 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; Reproduction
Toxicity aquatic micro-organisms	IC50	TETRATOX assay	356 mg/l	40 h	Tetrahymena pyriformis	Static system	Fresh water	Experimental value; Growth

2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	100 mg/l - 180 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	> 500 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	≥ 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 204	48 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; Behaviour
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro-organisms	EC10	Equivalent to OECD 209	> 1000 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1840 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	286 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

POWERSOLV

4-hydroxy-4-methylpentan-2-one

Biodegradation water

Method	Value	Duration	Value determination
Equivalent to OECD 301A	98.5 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	33 h	1.5E6 /cm ³	Calculated value

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	18 h	1.5E6 /cm ³	Calculated value

n-butyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D	83 %; Oxygen consumption	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	3.3 day(s)	5E5 /cm ³	Experimental value

2-methoxy-1-methylethyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	83 %; Oxygen consumption	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	11 h	1.5E6 /cm ³	Calculated value

2-butoxyethanol

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90 %; Carbon dioxide	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.5 h	1.5E6 /cm ³	QSAR

Conclusion

Water

Does not contain any not readily biodegradable component(s)

12.3. Bioaccumulative potential

POWERSOLV

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

4-hydroxy-4-methylpentan-2-one

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.09	20 °C	Calculated

propan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

n-butyl acetate

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.3	25 °C	Experimental value

2-methoxy-1-methylethyl acetate

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		1.2	20 °C	Experimental value

2-butoxyethanol

Log Kow

Method	Remark	Value	Temperature	Value determination
BASF test		0.81	25 °C	Experimental value

Conclusion

Does not contain bioaccumulative component(s)

POWERSOLV

12.4. Mobility in soil

4-hydroxy-4-methylpentan-2-one

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1	QSAR

propan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.19 - 0.54	Calculated value

n-butyl acetate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.268 - 1.844	Calculated value

2-methoxy-1-methylethyl acetate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.60 - 1.1	Calculated value

2-butoxyethanol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.5 - 0.9	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.31 %	0 %	0.01 %	0.59 %	99 %	QSAR

Conclusion

Highly mobile in soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

PMT conclusion

Does not contain component(s) that meet(s) the criteria of PMT and/or vPvM as listed in Annex I of Regulation (EC) No 1272/2008

POWERSOLV

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

4-hydroxy-4-methylpentan-2-one

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

propan-2-ol

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

n-butyl acetate

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

POWERSOLV

2-methoxy-1-methylethyl acetate

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

Water ecotoxicity pH

pH shift

2-butoxyethanol

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number or ID number

UN number	1993
-----------	------

14.2. UN proper shipping name

Proper shipping name	flammable liquid, n.o.s. (4-hydroxy-4-methylpentan-2-one; propan-2-ol)
----------------------	--

14.3. Transport hazard class(es)

Hazard identification number	33
Class	3
Classification code	F1

14.4. Packing group

Packing group	II
Labels	3

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	274
Special provisions	601
Special provisions	640D
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Rail (RID)

14.1. UN number or ID number

UN number	1993
-----------	------

14.2. UN proper shipping name

Proper shipping name	flammable liquid, n.o.s. (4-hydroxy-4-methylpentan-2-one; propan-2-ol)
----------------------	--

14.3. Transport hazard class(es)

POWERSOLV

Hazard identification number	33
Class	3
Classification code	F1
14.4. Packing group	
Packing group	II
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Special provisions	601
Special provisions	640D
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Inland waterways (ADN)

14.1. UN number or ID number	
UN number/ID number	1993
14.2. UN proper shipping name	
Proper shipping name	flammable liquid, n.o.s. (4-hydroxy-4-methylpentan-2-one; propan-2-ol)
14.3. Transport hazard class(es)	
Class	3
Classification code	F1
14.4. Packing group	
Packing group	II
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Special provisions	601
Special provisions	640D
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Sea (IMDG/IMSBC)

14.1. UN number or ID number	
UN number	1993
14.2. UN proper shipping name	
Proper shipping name	flammable liquid, n.o.s. (4-hydroxy-4-methylpentan-2-one; propan-2-ol)
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	II
Labels	3
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable, based on available data

Air (ICAO-TI/IATA-DGR)

14.1. UN number or ID number	
UN number/ID number	1993
14.2. UN proper shipping name	
Proper shipping name	flammable liquid, n.o.s. (4-hydroxy-4-methylpentan-2-one; propan-2-ol)
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	II
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A3

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

21 / 25

POWERSOLV

Passenger and cargo transport

Limited quantities: maximum net quantity per packaging

1 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
100 %	
883 g/l	

2-methoxy-1-methylethyl acetate

Product name	Skin resorption
2-Methoxy-1-methylethylacetate	Skin

2-butoxyethanol

Product name	Skin resorption
2-Butoxyethanol	Skin

Directive 2012/18/EU (Seveso III)

Threshold values under special circumstances

Substance or category	Special circumstances	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P5a FLAMMABLE LIQUIDS	Maintained at a temperature above the boiling point	10	50	None	Flammability
P5b FLAMMABLE LIQUIDS	Particular processing conditions, such as high pressure or high temperature, may create major-accident hazards	50	200	None	Flammability

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P5c FLAMMABLE LIQUIDS	5000	50000	None	Flammability

REACH Candidate list

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> · 4-hydroxy-4-methylpentan-2-one · propan-2-ol · n-butyl acetate · 2-methoxy-1-methylethyl acetate · 2-butoxyethanol 	<p>Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>1. Shall not be used in:</p> <ul style="list-style-type: none"> — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none"> — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may</p>

Reason for revision: 1; 2; 3; 4; 7; 8; 10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

22 / 25

POWERSOLV

		lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
<ul style="list-style-type: none"> · 4-hydroxy-4-methylpentan-2-one · propan-2-ol · n-butyl acetate · 2-methoxy-1-methylethyl acetate 	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopee” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”.</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
<ul style="list-style-type: none"> · 4-hydroxy-4-methylpentan-2-one · propan-2-ol · 2-butoxyethanol 	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

National legislation Belgium

POWERSOLV

No data available

propan-2-ol

Agents cancérigènes, mutagènes et reprotoxiques et aux agents possédant des propriétés perturbant le système endocrinien (Code du bien-être au travail, Livre VI, titre 2)	alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à l'acide fort dans la fabrication d'alcool isopropylique.
--	---

2-methoxy-1-methylethyl acetate

Résorption peau	Acétate de 2-(1-méthoxy)propyle; D; La mention “D” signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

2-butoxyethanol

Résorption peau	2-Butoxyéthanol; D; La mention “D” signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

National legislation The Netherlands

POWERSOLV

Waterbezwaarlijkheid	B (5); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

23 / 25

POWERSOLV

2-butoxyethanol

Huidopname (wettelijk)	2-Butoxyethanol; H
------------------------	--------------------

National legislation France

POWERSOLV

No data available

2-methoxy-1-methylethyl acetate

Risque de pénétration percutanée	Acétate de 2-méthoxy-1-méthyléthyle; Risque de pénétration percutanée
----------------------------------	---

2-butoxyethanol

Risque de pénétration percutanée	2-Butoxyéthanol; Risque de pénétration percutanée
----------------------------------	---

National legislation Germany

POWERSOLV

Lagerklasse (TRGS510)	3: Entzündbare Flüssigkeiten
-----------------------	------------------------------

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

4-hydroxy-4-methylpentan-2-one

TA-Luft	5.2.5
---------	-------

Hautresorptive Stoffe	4-Hydroxy-4-methyl-pentan-2-on; H; Hautresorptiv
-----------------------	--

propan-2-ol

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

n-butyl acetate

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	n-Butylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

2-methoxy-1-methylethyl acetate

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	2-Methoxy-1-methylethylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

2-butoxyethanol

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

Hautresorptive Stoffe	2-Butoxyethanol; H; Hautresorptiv
-----------------------	-----------------------------------

National legislation Austria

POWERSOLV

No data available

4-hydroxy-4-methylpentan-2-one

besondere Gefahr der Hautresorption	4-Hydroxy-4-methylpentan-2-on; H
-------------------------------------	----------------------------------

2-methoxy-1-methylethyl acetate

besondere Gefahr der Hautresorption	1-Methoxypropylacetat-2; H
-------------------------------------	----------------------------

2-butoxyethanol

besondere Gefahr der Hautresorption	2-Butoxyethanol; H
-------------------------------------	--------------------

National legislation United Kingdom

POWERSOLV

No data available

2-methoxy-1-methylethyl acetate

Skin absorption	1-Methoxypropyl acetate; Sk
-----------------	-----------------------------

2-butoxyethanol

Skin absorption	2-Butoxyethanol; Sk
-----------------	---------------------

National legislation Ireland

POWERSOLV

No data available

propan-2-ol

Skin resorption	Isopropyl alcohol; Skin
-----------------	-------------------------

2-methoxy-1-methylethyl acetate

Skin resorption	2-Methoxy-1-methylethylacetate; Skin
-----------------	--------------------------------------

2-butoxyethanol

Skin resorption	2-Butoxyethanol; Skin
-----------------	-----------------------

Other relevant data

POWERSOLV

No data available

POWERSOLV

propan-2-ol

TLV - Carcinogen	2-propanol; A4
IARC - classification	3; Isopropanol

2-butoxyethanol

TLV - Carcinogen	2-Butoxyethanol; A3
IARC - classification	3; 2-butoxyethanol

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
HS	Harmonized System of Nomenclature, a standardized international system for classifying goods under the Harmonized System Convention, as drawn up by the World Customs Organization Secretariat
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 1; 2; 3; 4; 7 ;8 ;10; 11; 12; 14; 15; 16

Publication date: 2020-07-05

Date of revision: 2026-01-29

Revision number: 1100

BIG number: 32103

25 / 25