



Report No. 392-2014-00163501B_02

Eurofins Product Testing A/S Smedeskovvej 38 8464 Galten Denmark

voc@eurofins.com www.eurofins.com/voc-testing

Date 18 December 2014

Novatech International N.V. Industrielaan 5 B 2250 Olen Belgique

VOC Emissions Test report

1. Sample Information

Sample identification	MS Construct
Product type	Sealant
Batch no.	142013344723XT7
Production date	-
Date when sample was received	13/08/2014
Testing (start - end)	15/08/2014 - 12/09/2014

2. Resulting VOC Emissions Class Label

This recommendation is based on French regulation of March 23, 2011 (décret DEVL1101903D) and of April 19, 2011 (arrêté DEVL1104875A). For details please see www.eurofins.com/france-voc



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

The product was assigned a VOC emission class without taking into account the measurement uncertainty associated with the result. As specified in French Decree no. 2011-321 of March 23, 2011, correct assignment of the VOC emission class is the sole responsibility of the party responsible for distribution of the product in the French market.



3. Test Method

Method		Principle	Parar	neter	Quantification limit	Uncer	tainty				
ISO 16000 parts -3, -6, -9, -11		GC/MS	VOC		2 µg/m³	22% (RSD)				
Internal method numbers: 9810, 9811, 9812, 2808, 8400		HPLC/UV	Volatile alde- hydes		3 µg/m³	Um = 2 x RSD= 45 %					
Test chamber parameter											
Chamber volume, I	119	Temperature, °C 23±1		23±1	Relative humidity, %		50±5				
Air change rate, 1/h	0.5	Loading ratio, m ² /m ³		0.007							
Test condition: Sample stayed in test chamber during the whole 28 days testing period.											
Sample preparation											
The sample was applied onto a glass plate and drawn off over a model giving a 3 mm thick and uniform layer with a broadness of 10 mm.											
Thickness, mm		3									





4. Results

	Concentration after 28 days µg/m³	С	В	A	A+
TVOC	560	>2000	<2000	<1500	<1000
Formaldehyde	<3	>120	<120	<60	<10
Acetaldehyde	<3	>400	<400	<300	<200
Toluene	<2	>600	<600	<450	<300
Tetrachloroethylene	<2	>500	<500	<350	<250
Ethylbenzene	<2	>1500	<1500	<1000	<750
Xylene	<2	>400	<400	<300	<200
Styrene	<2	>500	<500	<350	<250
2-Butoxyethanol	<2	>2000	<2000	<1500	<1000
1,2,4- Trimethylbenzene	<2	>2000	<2000	<1500	<1000
1,4-Dichlorobenzene	<2	>120	<120	<90	<60

< Means less than

> Means higher than

もす

Thomas Bjerring Analytical Service Manager

Søren Ryom Villadsen Analytical Service Manager