



Nova PTFE Care

DURABLE PTFE-TREATMENT FOR ENGINE, GEARBOX AND DIFFERENTIAL

- ✓ Prevents metal-metal friction by the PTFE-formula.
- ✓ Protects all lubricating, rotating and moving parts.
- ✓ Prolongs the life span of the engine, gearbox and differential.
- ✓ Appropriate for diesel and petrol engines.
- ✓ Applicable in all manually changed gear boxes.
- ✓ Prevents sludge and protects against acids.
- ✓ Increases the performance capacity of the car.
- ✓ Reduces exhaust emission.
- ✓ Works efficiently and durable.
- ✓ A PTFE-treatment does not require working hours.

Technical Info

- Boiling point: 48 °C.
- Flashpoint: 215°C.
- Melting point: 300 °C.
- pH:4-8.
- Relative density (at 20°C): 0,89.
- Relative vapour density: > 1.
- Water solubility: insoluble.
- Odour: ether-like.
- Colour: colourless.
- NOVA PTFE CARE treats up to 5 litres of oil.
- Shelf life: 36 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Nova PTFE Care - bottle 300ml

741403000

Product

Characteristics

- A durable PTFE treatment for engine, gearbox and differential.
- Formulated for the heaviest performances, 1 treatment is sufficient for 80,000 km.
- A concentrated friction reducer and improves the durability of the engine and prolongs the life span of all moving parts of the engine, gearbox and differential by covering them with a PTFE-film that prevents friction.
- Reduces the oil consumption.

Use

- Bring the engine at operating temperature.
- Add half of the bottle in the engine to the clean engine oil.
- Shake the bottle powerfully and add the rest.

For optimal result: clean first with Novaflush Engine.