

# Nova Finish Primer

## FINE PRIMER



- ✓ Saves times and is user-friendly.
- ✓ Contains: undercoat, elastifier and anti-corrosive elements.
- ✓ Nozzle is adjustable in width and flow.
- ✓ Perfect adhesion on synthetic materials, on metal, galvanised metal, lacquered surfaces, wood, ... without using a primer.
- ✓ Extreme adhesion on PVC.
- ✓ Fast and simply sanding.

### Technical Info

- Base: acrylic.
- Odour: characteristic.
- Vapour pressure at 20 °C: 8300 hPa.
- Density at 20 °C: 0,89 g/cm³.
- Solubility in water: none.
- Mixability in water: small mixable.
- VOC (EU): 791,7 g/l.
- Filling capacity: +/- 40 micron.
- Shelf life: 120 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

### Packing

Nova Finish Primer dark grey - aerosol 500ml	120812000
Nova Finish Primer black - aerosol 500ml	120822000
Nova Finish Primer white - aerosol 500ml	120832000

### Product [FPR]

#### Characteristics

Nova Finish Primer is a fine primer specially developed to lacquer it with the newest water-based lacquers afterwards. Nova Finish Primer combines elastisator and adhesive capacities with rust-proof elements. Thans to Nova Finish Primer you don't have to throw away paints residues anymore and clean guns for small repairs. Nova Finish Primer is easy to use. To guarantee the covering capacity of the lacquer you use, Nova Finish Primer is available in 3 colours. Nova finish Primer has a fine covering that makes the finishin easier and needs less sanding. Nova Finish Primer is capable for drying fast with infrared.

### Use

Thanks to the adjustable nozzle this aerosol can also be used as a spraying gun: the nozzle is adjustable in width and flow. It is suitable for accelerated with infrared.

- Shake well before using
- Degrease surface with safety Clean and/or Multifoam, then sand until matte.
- Always apply Nova Finish Primer in several thin layers. Spray distance: +/- 25 cm
- After drying (+/- 20 min) Nova Finish Primer can be sanded (wet and dry)
- Can be painted over with most common paints
- After use, turn spray can around and empty to keep the spray head clean.

With synthetic materials that contains PE or PP, Nova Finish Primer can have less or even bad adhesion. On these synthetic surfaces we recommend, after sanding, to use first Seal & Bond Special Primer before using Nova Finish Primer.

Which Novafill Flex to use?

- On metal as first layer: Nova Finish Primer, because of its rust-proof capacity.
- On other surfaces (as well as synthetic materials) as first layer: Novafill Flex or Novafill Flex 2, because of their adhesive capacities (apply first Seal & Bond Special Primer on difficult synthetic materials).
- Following layers according to the filling needed: Novafiller, Novafill Flex or Novafill Flex 2.
- As a final layer, before painting, Nova Finish Primer is recommended by its fine structure: the finish is easy, saves time by less sanding