



Sealflux

WATERPROOF PINCH AND SHRINK CONNECTION

- ✓ Cable connector provided with insulation and hot melt adhesive.
- ✓ Insulated, highly conductive and strong connection.
- ✓ Highly resistant to temperature, vibrations, wear and tear,
- ✓ Resistant to hydraulic oil, solvents, diesel fuel, petrol, salt water, battery acids, brake fluid,...

Technical Info

- Insulation resistance: Megohms 103.
- Dielectric resistance: 2,5 Kilovolt.
- Chemical resistance: diesel fuel, brake fluid, antifreeze, 5% salt water, motor oil,...
- Solvent resistance: isopropyl alcohol, trichloroethylene, gasoline.
- Constant temperature: from -55°C to 125°C.
- Minimum shrink temperature: 180°C.
- Voltage rating: 600 Volt maximum.
- Shrink ratio: approximately 2:1.
- Electrical properties: disruptive strength 1000 Volt, insulation resistance 103 Megohms.

Packing

Sealflux - sliding connector - red 6,35mm - 50pcs	834610000
Sealflux - sliding connector - red 4,80mm - 50pcs	834410000
Sealflux - sliding connector - blue 6,35mm - 50pcs	834620000
Sealflux - sliding connector - yellow 6,35mm - 50pcs	834630000
Sealflux - leaf connector - red 6,35mm - 50pcs	835610000
Sealflux - leaf connector - blue 6,35mm - 50pcs	835620000
Sealflux - fork cable - red 4,30mm - 50pcs	833410000
Sealflux - fork cable - blue 4,30mm - 50pcs	833420000
Sealflux - fork cable - blue 5,30mm - 50pcs	833520000
Sealflux - fork cable - yellow 5,30mm - 50pcs	833530000
Sealflux - ring tongue - red 4,30mm - 50pcs	832410000

Product [SUX]

Characteristics

- Insulates and protects electrical connections from mechanical abuse and wire pull-out.
- Provides a tough, environment friendly sealed wire connection. Their crimp barrel or terminal, encased in a rugged nylon tubing with a special hot-melt adhesive, resists damage from abrasions and cuts.
- Sealflux are colour-coded for easy wire diameter identification, yet they are transparent for the inspection of the finished connection.

Sealflux - ring tongue - red 5,30mm - 50pcs	832510000
Sealflux - ring tongue - red 6,50mm - 50pcs	832610000
Sealflux - ring tongue - blue 4,30mm - 50pcs	832420000
Sealflux - ring tongue - blue 5,30mm - 50pcs	832520000
Sealflux - ring tongue - blue 6,50mm - 50pcs	832620000
Sealflux - ring tongue - blue 8,40mm - 50pcs	832820000
Sealflux - ring tongue - blue 10,50mm - 50pcs	832120000
Sealflux - ring tongue - yellow 5,30mm - 50pcs	832530000
Sealflux - ring tongue - yellow 6,50mm - 50pcs	832630000
Sealflux - ring tongue - yellow 8,40mm - 50pcs	832830000
Sealflux - ring tongue - yellow 10,50mm - 50pcs	832130000
Sealflux - connector - red - 50pcs	831010000
Sealflux - connector - blue - 50pcs	831020000
Sealflux - connector - yellow - 50pcs	831030000
Sealflux - cinch male - red - 50pcs	836110000
Sealflux - cinch male - blue - 50pcs	836120000
Sealflux - cinch female - red - 50pcs	836010000
Sealflux - cinch female - blue - 50pcs	836020000

Use

- Dismantle the cable to +/- 6 mm and place it in the appropriate Sealflux.
- Pinch Sealflux mechanically.
- Heat up Sealflux isolator with a heat source (such as the Novaflame Multi Torch).