



Surface Renewer

CLEANING, RENEWING AND PROTECTING PAINT AND PVC

- ✓ Cleans, revives the original color and gives a deep shine.
- ✓ Protects against pollution, UV fading and aging.
- ✓ Easy to apply with immediate results.

Technical Info

- Look: liquid.
- Odour: characteristic.
- Viscosity (20°C): 1mPa.s.
- Relative density (20°C) 0.790 kg/L.
- Flash point: 27°C.
- Water solubility: insoluble.
- Boiling point/Boiling range: 130-300°C.
- Melting point/Melting range: <-20°C.
- Volatile organic components, %: 68,220.
- Volatile organic components, gr/l: 538,2.
- Working temperature: +10°C - +30°C.
- Shelf life: 36 months, keep dry, cool and frost-proof.
- Safety measures and storage: please consult the Safety Data Sheet.

Packing

Surface Renewer - bottle 400ml	485302000
Surface Renewer - bottle 100ml	485301000

Product [SUR]

Characteristics

Surface Renewer is a ready-to-use cleaner for renewing UV-weathered coating of aluminum joinery or other painted surfaces and powder coatings.

With a regular treatment with Surface Renewer, the substrate is nourished and a new look is retained.

Applications

- suitable for all coated (unvarnished) or powdercoated materials: windows and doors, garage doors, verandas, roof windows, terraces, carports, railings, ...
- on plastics: roller blinds, mobile homes, caravans, leisure boats, sport planes, ...

Use

- Preventive: Apply to healthy, clean and dry surfaces with a soft, clean and dry sponge. Wipe with a clean, soft cloth.
- Curative: thoroughly clean dirty, weathered surfaces with Novakleen and dry before treatment with Surface Renewer.

Dosage: only use pure.



Surface Protection & Treatment