

Butaseal

DOUBLE-SIDED ADHESIVE ON ROLL BASED ON FLEXIBLE BUTYL RUBBER



- ✓ Direct adhesion, even in difficult materials.
- ✓ For bonding and sealing.
- ✓ Well mouldable, remains flexible.
- ✓ For both permanent and temporary fixings.
- ✓

Technical Info

Butaseal Black:

- Thickness: 1,5 mm.
- Width: 15 mm.
- Length/roll: 25 m.
- 180° Peel adhesion: 20 N/cm.
- 180° Peel adhesion at +5°C on concrete: 17 N/cm.
- Probe Tack: 8 N.
- Application temperature: between 0°C and +40°C.
- Temperature resistance: from -30°C to +90°C.
- Shelf life: 36 months, keep dry, cool and frost-free.

Packing

Butaseal black - roll 15mm / 25m

551158000

Product [BSL]

Characteristics

- Butalu Circular is a double-sided adhesive and sealing band on roll.
- Remains flexible and does not harden due to its unique composition based on modified butylene rubbers.
- Butalu Circular offers a very high immediate bonding strength, even on materials that are difficult to bond.
- Adapts perfectly to any surface.

Applications

- flexible bonding - temporary or permanent - also on difficult materials.
- gives an immediate adhesion in combination with Seal & Bond MS60.
- prevents galvanic action in metal constructions.
- bonding of PE foil in doors and roof covering.
- sealing of cable passages, rear lights, surface mounted sliding roofs.
- eliminates vibrations.

Use

- Apply to dry and clean surfaces, clean if necessary with Safety Clean and/or Multif foam.
- Remove protective paper, apply and press firmly.
- Test substrates based on PE, PP, silicone and bitumen for adhesion first.