



MGM-130 MGM Primer Fast

FAST-DRYING ADHESIVE PRIMER

- ✓ For adhesives and coatings
- ✓ On metal

Technical Info

- Basis: solvent-based siloxane.
- Colour: light yellow – yellow.
- Density: 0.95-1.0.
- pH: 10.
- Drying time: 10 to 20 minutes, depending on temperature and humidity.
- Shelf life: 12 months, store in a dry place between +5 °C and +25 °C.
- Safety measures: please refer to the safety data sheet.

Packing

MGM-130 MGM Primer Fast - can 5L	590955000
----------------------------------	-----------

Product [MGM-130]

Characteristics

MGM-130 MGM Primer Fast is a fast adhesion promoter for adhesives and coatings on all inorganic substrates, such as metals, glass and other mineral substrates. It is used in combination with epoxy, MS polymers and silicones. MGM-130 MGM Primer Fast is ideal for pre-treating hard-to-adhere ceramic materials, polymer concrete or old epoxy layers, in combination with Poxyccon.

Applications

- Improves adhesion to old epoxy layers, contaminated polymer concrete and glazed ceramic floors.
- Primer for bonding or coating on all inorganic (mineral) substrates: glass, metals, natural stone, granite, limestone, ceramic materials, concrete and cement-based substrates.

Use

- Apply to a clean and stable substrate. Clean, if necessary, with Safety Clean and/or Multifoam. Clean old epoxy layers first with Megaclean.
 - Apply MGM-130 MGM Primer Fast with a brush, roller or nebuliser.
 - Apply adhesive or coating when the surface is dry to the touch.
- Consumption: 12 m² per liter.

Adhesion test results		
Poxycon on:	MGM-130	MGM-170
• Ceramic tile (food grade)	+/-	++
• Glazed tile	+	+
• Glass	+	++
• Aluminium	+	+/-
• Stainless steel	+	+/-
• Volkern (HPL)	+	-
• Polyester	+	+
• Polycarbonate	-	-
• Plexi opal	-	-
• Polystyrene	-	-
• Shockproof PVC	-	-
• Fixapox	++	+/-
• Megapox (*)	-	-
• Poxycon	++	+/-
• Coatapox	++	++
• Multipox	++	++
• Q-Fix	++	++

(*)Megapox has an oily top layer (amine blush) that makes adhesion impossible.