

# **Nanocare Protect**

WATER REPELLENT, DURABLE PROTECTION FOR ALL POROUS MATERIALS AND TEXTILES

- Protects against oil, grease, dirt, pollution...
- For indoor and outdoor use.
- Colourless, odourless and safe.
- Vapor permeable.

## **Technical Info**

- Form: liquid.
- Odour: weak, characteristic.
- Melting point/Melting range: < 0°C.
- Boiling point/Boiling point range: > 100°C.
- Auto ignition: no.
- Explosion hazard: none.
- Vapour pressure at 20°C: approx. 23 hPa.
- Density at 20°C: approx. 1.07 g/cm<sup>3</sup>.
- · Solubility in/Miscibility with water: complete.
- pH value at 20°C: ± 6.
- Shelf life: dry, cool and frost free
- 1L and 5L: 12 months
- 20L: 36 months

## Packing

Nanocare Protect - bottle 1L	486301000
Nanocare Protect - can 5L	486305000
Nanocare Protect - can 20L	486320000
Nanocare Protect - sticker univ	L30545901

# Product [PTT]

#### Characteristics

- Nanocare Protect prevents the infiltration of dirt and moisture into porous materials and textiles.
- This durable protection against frost, slows discolouration due to UV radiation and works against moss and mould formation.
- Nanocare Protect improves thermal insulation by 30% and makes woven fabrics more durable.
- Ready for use, contains no solvents and is not flammable.

### Use

- Clean, rinse and dry the surface if necessary. (after cleaning and before treatment with Nanocare Protect, rinse and dry thoroughly).
- · Apply Nanocare Protect in an upward motion, from bottom to top, in two successive coats, wet on wet.
- Allow to dry.

Apply with a brush or using a low-pressure pump fitted with a flat spray nozzle. The substrate's temperature should be at least +5°C. Do not apply when it is raining or frosty. Make sure the work area is well ventilated and always wear a mask with type A filter



Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV.

during application. Dry in 24 hours, depending on substrate, temperature and amount applied. Maximum protection after 7 days. The equipment used can be directly cleaned with water. Immediately wipe off Nanocare Protect from window panes or frames with a damp cloth.

One litre of Nanocare Protect can treat a surface of between 2 and 10 m<sup>2</sup>, depending on the porosity of the substrate.

novatio<sup>®</sup>

Novatio is a registered trademark of Novatech International nv. Industrielaan 5B - B-2250 Olen - Belgium | Tel: +32 14 25 67 40 | info@novatio.be

Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV.