



Novastop Oil HD

SEALS OIL LEAKS FROM HEAVY EQUIPMENT

- ✓ Stops and prevents drying and hardening of all plastic seals and gaskets.
- ✓ Makes rubbers soft in one treatment.
- ✓ Compatible with all Heavy Duty oil types, including thick differential oil.
- ✓ Free from chlorides, solvents and oil thickeners.

Technical Info

- Composition: liquid oily mixture of selected rubber softeners.
- Odour: slight oily smell.
- Density: ca 1.15 +/- 0.1 kg/dm³.
- Solubility: mixable with all oils; soluble in solvents and insoluble in water.
- Flashpoint: 235°C.
- Consumption: 30 ml/l oil.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Novastop Oil HD - can 5L

742153000

Product [NOH]

Characteristics

Novastop Oil HD prevents expensive disassembly and assembly costs for replacement of leaking seals. Novastop Oil HD conditions seals, protects them against dehydration, hardening, shrinking and crystallisation. Novastop Oil HD impregnates the leaking seals, makes them elastic again, lets them swell in a controlled way and rules out oil leakages for a long time. Novastop Oil HD as a curative treatment does not need to be repeated. Once its work is done, the condition of the seals is as new. Also suitable for ATF, hydraulic and mineral oils. Novastop Oil HD as a preventive treatment is recommended for engines and installations as from 3 years old.

Applications

- Combating oil leaks in closed oils systems
- Effective on all rubber seals and most cork seals in diesel and petrol engines, hydraulic systems, hydro-pneumatic spring systems, gearboxes,...

Use

Add 30 ml per liter of fresh oil.

Do this after oil change to make Novastop Oil work better and longer.

Use the vehicle or application regularly to heat up the oil and circulate to promote the effect of Novastop Oil.