



Fix Primer

TRANSPARENT PRIMER TO GLUE DIFFICULT PLASTICS

- ✓ Opens the pores in plastics.
- ✓ Improves adhesion strength.
- ✓ Easy to use.

Technical Info

- Solvent base: heptane.
- Colour: transparent.
- Vaporisation time: < 10 seconds.
- Viscosity: 3-6 cps.
- Flash point: -12°C.
- Drying time: < 30 seconds.
- Drawing strength: depending on the material 3-10 N/mm.
- Optimum drawing strength: after 24 hours.
- Shelf life: 18 months at 20°C (keep dry).
- Safety measures: consult the Safety Data Sheet.

Packing

Fix Primer - aerosol 50ml

502110000

Product [FIP]

Characteristics

Fix Primer promotes adhesion to difficult materials such as: polyethylene (PE), polypropylene (PP), PMMA, bakelite, polycarbonate, Viton rubber, polyolefins, PTFE, silicone, Fix Primer rarely leaves traces.

Applications

- For bonding with Al-Fix, Al-Fix Gel, Al-Fix Flexible and Al-Fix Black.
- Also good results in combination with High Tech Tape, High Tech Transparent Tape, HCS Tape,

Use

- Apply on pure and dry surface.
 - Apply thinly on both surfaces and allow to dry.
- Gives no added value on metals.