

Al-Fix Aktivator SF



SUPER FAST ACTIVATOR OF CA GLUES

- ✓ Fastens the curing time of the Al-fix glues.
- ✓ Makes adhesion possible on porous materials such as wood.
- ✓ Ideal combination with Al-Fix Gel.

Technical Info

- Shelf life: 24 months, protected from light and at ambient temperature.

Packing

Al-Fix Aktivator SF - aerosol 150ml

501111000

Product [AFA SF]

Characteristics

Al-Fix glues are adhesives which bond in seconds and have a special formula based on Cyanacrylate. Al-Fix glues are one component adhesives which are solventless and consist mainly of Athyl Cyanacrylate Monomer. Al-Fix glues are temperature resistant in the range from -30°C to +100°C. Al-Fix glues are resistant to solvents, oils, benzene, temperature fluctuations and atmospheric conditions. Al-Fix glue joints have a high tensile shear strength and show no shrinkage. Al-Fix Aktivator SF accelerates the hardening considerably and therefore can have white markings, which are easy to remove with Al-Fix Remover.

Applications

Al-Fix glues provide an exceptionally strong bond between almost all kinds of materials, with the exception of polyethylene, polypropylene and fluorine containing materials. Materials which can be bonded with Al-Fix glues: ABS, aluminium, bakelite, bronze, buthyl, celluloid, chloroprene, chrome, delrin, glass, copper, natural rubber, NBR, neoprene, nitril, nylon, phenol, polycarbonate, polystyrene, porcelain, hard pvc, stainless steel.

Use

- Apply on a clean and dry surface and allow to evaporate.
- Apply Al-Fix and bond pieces together.

To facilitate curing of Al-Fix Gel, spray once the pieces that have been joined together. May damage painted surfaces and thermoplastics. The possible white deposit after hardening can be easily removed with the help of Al-fix Remover.