



Stripfix

TRANSPARENT GLUE ON ROLL FOIL, FOR INSTANT BONDING

- ✓ Requires no drying time.
- ✓ Safe to use, contains no solvents.
- ✓ Holds up to 8 kg/cm².
- ✓ Cut a suitable piece, press together and it's ready!
- ✓ Good resistance to water, diluted acids, alkalines, mineral oils, ...
- ✓ Does not dry out or harden.
- ✓ Can be used as a sealant.

Technical Info

- Composition: rubber / resin.
- Elongation: 1000%.
- Initial adhesive strength: 52 N/cm².
- Tensile strength: 60 N/cm² after 10 min.; 80 N/cm² after 24 hours.
- Application weight: 405 g/m².
- Temperature resistance: -10°C to +50°C.
- Static shear FTM8: 0,5kg -25mm x 25mm/+20°C.
- Application temperature: > +10°C.
- Water absorption: 0%.
- Thickness: 0,4 mm.
- Pressure needed to achieve 20% compression: 1,6 kg/cm².
- U.V. resistance: bad - exposure to UV light should be avoided.
- Tolerance: thickness and width < 10%.
- Shelf life: 24 months, keep dry, cool and frost-proof.

Packing

Stripfix - roll 12mm / 0,4mm / 30m	521208000
Stripfix - roll 19mm / 0,4mm / 30m	521908000

Product [SFX]

Characteristics

- A synthetic, pressure-sensitive transparent adhesive on roll. It has been designed to provide a very strong bond between a wide variety of materials and substrates.
- Can be used immediately on clean, dry and grease-proof surfaces.
- Is excellent for bonding "difficult" materials such as glass, metal, wood, rubber and plastics including polyethylene.

Applications

Building

- mounting of connections for protective plates of drain pipes, insulating material in polypropylene, filter membranes for road construction
- bonding of light insulating plates, connections in synthetic material,...

Furniture industry

- mounting of laminated decorative frames
- fixing of corners on furniture

Car industry

- fixing of insulating material, name-plates and signs,...

Construction

- bonding of side and roof panels on caravans

Use