novatio



Novastop Oil

PREVENTS AND SEALS OIL LEAKS

- Compatible with all oil types.
- Stops and prevents drying or hardening of all seals.
 - Makes rubbers soft and supple in one treatment.
 - Safe in use, free from chlorides, solvents or oil thickeners.

Technical Info

- Appearance: liquid.
- Colour: amber.
- Relative density: 1.03.
- Dosage: 1%.
- · Shelf life: 36 months, dry, cool and frost-free.
- Safety measures: please consult the safety data sheet.

Packing

Novastop Oil - bottle 250ml

742303000

Product [NOL]

Characteristics

Novastop Oil is a universal synthetic additive for engine and gearbox oil, ATF, power steering fluid and hydraulic oils. Seals swell to their original size and become flexible, stopping oil leaks and preventing costly repairs, lowering oil consumption, improving engine performance by optimising engine compression, preventing or reducing blue exhaust emissions and extending the life of the engine or installation. Novastop Oil does not contain any harmful solvents or solids, does not clog filters and is harmless for catalysers.

Applications

For valve stem seals, crankshaft seals, oil filter O-rings and crankcase seals and all other plastic or rubber based seals.

Use

- Add 10 ml per litre of fresh oil.
- Do this after an oil change to allow Novastop Oil to work better and longer.
- $\cdot\;$ Use the vehicle regularly to allow the engine to warm up, to circulate the oil and to improve efficiency.



Novatech International NV produces all information with the utmost care but cannot give any guarantees as to its nature, content and/or use. The company does not accept any liability for direct or indirect damage caused by the contents of the information included. All images included are for indicative purposes only. No rights may be derived from them. None of the published data may be copied, stored in an automated database and/or made public, in any form or manner, without the explicit prior written consent of Novatech International NV.