

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



## POXY DC

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : POXY DC  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Thinner

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 3	H226: Flammable liquid and vapour.
Asp. Tox.	category 1	H304: May be fatal if swallowed and enters airways.
STOT SE	category 3	H335: May cause respiratory irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements



Contains: hydrocarbons, C9, aromatics.

**Signal word** Danger

##### H-statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

##### P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves and eye protection/face protection.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 8, 9, 12

Revision number: 0100

Publication date: 2016-03-04

Date of revision: 2021-06-20

BIG number: 57116

1 / 14

878-16239-022-en

# POXY DC

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P331 Do NOT induce vomiting.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

## Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

No other hazards known

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
hydrocarbons, C9, aromatics 01-2119455851-35	918-668-5	80% <C<100%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 EUH066	(1)(10)	Constituent	
2-methoxy-1-methylethyl acetate 01-2119475791-29	108-65-6 203-603-9	5%<C<10%	Flam. Liq. 3; H226	(1)(2)(10)	Constituent	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Headache. Nausea. EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Drowsiness. Disturbances of consciousness.

##### After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

##### After eye contact:

No effects known.

##### After ingestion:

Risk of aspiration pneumonia.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

2 / 14

# POXY DC

## 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.  
Major fire: Class B foam (not alcohol-resistant).

## 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.  
Major fire: Water; risk of puddle expansion.

## 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed.

## 5.3. Advice for firefighters

### 5.3.1 Instructions:

Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Safety glasses (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Safety glasses (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Prevent soil and water pollution. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away. Avoid prolonged and repeated contact with skin. Remove contaminated clothing immediately. Keep container tightly closed. Do not discharge the waste into the drain.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Meet the legal requirements. Store at room temperature. Keep container in a well-ventilated place. Fireproof storeroom. Provide for a tub to collect spills.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

No data available

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
--------------------------------	---	--------

# POXY DC

2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	275 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	550 mg/m <sup>3</sup>

## Belgium

Acétate de 2-(1-méthoxy)propyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	275 mg/m <sup>3</sup>
	Short time value	100 ppm
	Short time value	550 mg/m <sup>3</sup>

## The Netherlands

1-Methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
1-methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	550 mg/m <sup>3</sup>

## France

Acétate de 2-méthoxy-1-méthyléthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	275 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	550 mg/m <sup>3</sup>

## Germany

2-Methoxy-1-methylethylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	270 mg/m <sup>3</sup>

## UK

1-Methoxypropyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	274 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	548 mg/m <sup>3</sup>

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### 8.1.2 Sampling methods

Product name	Test	Number
1-Methoxy-2-Propyl Acetate	OSHA	99
Propylene glycol monomethyl ether acetate (glycol ethers)	NIOSH	2554

### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 Threshold values

#### DNEL/DMEL - Workers

hydrocarbons, C9, aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	150 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	25 mg/kg bw/day	

#### 2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	275 mg/m <sup>3</sup>	
	Acute local effects inhalation	550 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	796 mg/kg bw	

#### DNEL/DMEL - General population

hydrocarbons, C9, aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	32 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	11 mg/kg bw/day	
	Long-term systemic effects oral	11 mg/kg bw/day	

#### 2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	33 mg/m <sup>3</sup>	
	Long-term local effects inhalation	33 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	320 mg/kg bw	
	Long-term systemic effects oral	36 mg/kg bw	
	Acute systemic effects oral	500 mg/kg bw/day	

## PNEC

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

4 / 14

# POXY DC

## 2-methoxy-1-methylethyl acetate

Compartment	Value	Remark
Fresh water	0.635 mg/l	
Marine water	0.064 mg/l	
Fresh water (intermittent releases)	6.35 mg/l	
STP	100 mg/l	
Fresh water sediment	3.29 mg/kg sediment dw	
Marine water sediment	0.329 mg/kg sediment dw	
Soil	0.29 mg/kg soil dw	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

### 8.2.2 Individual protection measures, such as personal protective equipment

Avoid prolonged and repeated contact with skin. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

#### c) Eye protection:

Face shield (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Aromatic odour
Odour threshold	No data available in the literature
Colour	Colourless
Particle size	Not applicable (liquid)
Explosion limits	1.5 - 10.8 vol %
Flammability	Flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available in the literature
Kinematic viscosity	No data available in the literature
Melting point	No data available in the literature
Boiling point	167 °C
Relative vapour density	No data available in the literature
Vapour pressure	No data available in the literature
Solubility	Water ; insoluble
Relative density	0.87 ; 20 °C
Absolute density	870 kg/m <sup>3</sup> ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	315 °C
Flash point	48 °C
pH	Not applicable (non-soluble in water)

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks.

### 10.2. Chemical stability

No data available.

### 10.3. Possibility of hazardous reactions

No data available.

# POXY DC

## 10.4. Conditions to avoid

### Precautionary measures

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away.

## 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### POXY DC

No (test) data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 6984 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50		3492 mg/kg bw		Rat (female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 6.193 mg/l air	4 h	Rat (male / female)	Experimental value	

##### 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	6190 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation	LC0	Equivalent to OECD 403	10.8 mg/l	3 h	Rat (male)	Experimental value	

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### POXY DC

No (test) data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9, aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Inhalation (vapours)	Irritating; STOT SE cat.3					Literature study	

##### 2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

#### Conclusion

May cause respiratory irritation.

Not classified as irritating to the skin

Not classified as irritating to the eyes

#### Respiratory or skin sensitisation

##### POXY DC

No (test) data on the mixture available

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

6 / 14

# POXY DC

Judgement is based on the relevant ingredients  
hydrocarbons, C9, aromatics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	

## 2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Experimental value	

### **Conclusion**

Not classified as sensitizing for inhalation  
Not classified as sensitizing for skin

### **Specific target organ toxicity**

#### POXY DC

No (test) data on the mixture available

Classification is based on the relevant ingredients  
hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 408	600 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 452	1800 mg/m <sup>3</sup> air		No effect	52 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 452	900 mg/m <sup>3</sup> air		No effect	52 weeks (6h / day, 5 days / week)	Rat (female)	Read-across
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Literature study

## 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 422	≥ 1000 mg/kg		No effect	41 day(s) - 45 day(s)	Rat (male / female)	Experimental value
Oral (stomach tube)	Dose level	US EPA	500 mg/kg bw/day		Drowsiness, dizziness		Rat (male / female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	1838 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rabbit (male)	Read-across
Dermal	LOAEL	Equivalent to OECD 411	3676 mg/kg bw/day		Overall effects	13 weeks (6h / day, 5 days / week)	Rabbit (male)	Read-across
Inhalation (vapours)	NOEL	OECD 453	300 ppm		No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

### **Conclusion**

May cause drowsiness or dizziness.  
Not classified for subchronic toxicity

### **Mutagenicity (in vitro)**

#### POXY DC

No (test) data on the mixture available

Judgement is based on the relevant ingredients  
hydrocarbons, C9, aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

7 / 14

# POXY DC

## 2-methoxy-1-methylethyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative without metabolic activation	Equivalent to OECD 482	Rat liver cells	No effect	Experimental value	

### Mutagenicity (in vivo)

#### POXY DC

No (test)data on the mixture available  
Judgement is based on the relevant ingredients  
hydrocarbons, C9, aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male)	Bone marrow	Experimental value

#### Conclusion

Not classified for mutagenic or genotoxic toxicity

### Carcinogenicity

#### POXY DC

No (test)data on the mixture available  
Judgement is based on the relevant ingredients  
hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Unknown								Data waiving

## 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Read-across

#### Conclusion

Not classified for carcinogenicity

### Reproductive toxicity

#### POXY DC

No (test)data on the mixture available  
Judgement is based on the relevant ingredients  
hydrocarbons, C9, aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	100 ppm	10 days (6h / day)	Mouse	No effect		Experimental value
	LOAEC	Developmental toxicity study	500 ppm	10 days (6h / day)	Mouse	Reduced foetal bodyweights	Foetus	Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	100 ppm	10 day(s)	Mouse	No effect		Experimental value
	LOAEC	Developmental toxicity study	500 ppm	10 day(s)	Mouse	Body weight reduction	General	Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	3 generation study	7500 mg/m <sup>3</sup>		Rat (male / female)	No effect		Experimental value

## 2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation)	NOAEL	Equivalent to OECD 414	> 4000 ppm	10 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
Developmental toxicity (Inhalation (vapours))								
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	500 ppm	10 days (gestation, daily)	Rat	No effect		Experimental value
	LOAEL	Equivalent to OECD 414	2000 ppm	10 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEL	OECD 416	300 ppm		Rat (male / female)	No effect		Read-across

#### Conclusion

Not classified for reprotoxic or developmental toxicity

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

8 / 14



# POXY DC

## Aspiration hazard

Classification is based on the relevant ingredients  
May be fatal if swallowed and enters airways.

## Toxicity other effects

### POXY DC

Classification is based on the relevant ingredients  
hydrocarbons, C9, aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study

### Conclusion

Repeated exposure may cause skin dryness or cracking.

## Chronic effects from short and long-term exposure

### POXY DC

Dry skin. Cracking of the skin.

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### POXY DC

No (test)data on the mixture available

Classification is based on the relevant ingredients  
hydrocarbons, C9, aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	10 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	3.2 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EL50	OECD 201	2.9 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	0.07 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		1.228 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		2.144 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

#### 2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	100 mg/l - 180 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	> 500 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	≥ 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 204	47.5 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; Behaviour
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC10	Equivalent to OECD 209	> 1000 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Respiration

### Conclusion

Toxic to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

9 / 14

# POXY DC

hydrocarbons, C9, aromatics

## Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	78 %	28 day(s)	Experimental value

2-methoxy-1-methylethyl acetate

## Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	83 %; Oxygen consumption	28 day(s)	Experimental value

## Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	10.818 h	1.5E6 /cm <sup>3</sup>	Calculated value

## Biodegradation soil

Method	Value	Duration	Value determination
Equivalent to OECD 304A	> 57 %; GLP	1 day(s)	Experimental value

## Conclusion

### Water

Contains readily biodegradable component(s)

## 12.3. Bioaccumulative potential

POXY DC

### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C9, aromatics

## BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBFAF v3.01	39.8 l/kg - 177.8 l/kg; Fresh weight		Pisces	QSAR

## Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN		2.92 - 3.59	20 °C	QSAR

2-methoxy-1-methylethyl acetate

## Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		1.2	20 °C	Experimental value

## Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

hydrocarbons, C9, aromatics

### (log) Koc

Parameter	Method	Value	Value determination
log Koc		2.68	QSAR

2-methoxy-1-methylethyl acetate

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.602 - 1.079	Calculated value

## Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	10.22 %	0 %	0.02 %	0.03 %	89.73 %	Calculated value

## Conclusion

Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

POXY DC

### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

# POXY DC

## Groundwater

Groundwater pollutant

hydrocarbons, C9, aromatics

## Groundwater

Groundwater pollutant

2-methoxy-1-methylethyl acetate

## Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

07 06 04\* (wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics: other organic solvents, washing liquids and mother liquors). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

UN number	1263
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	paint related material
----------------------	------------------------

#### 14.3. Transport hazard class(es)

Hazard identification number	30
Class	3
Classification code	F1

#### 14.4. Packing group

Packing group	III
Labels	3

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

#### 14.6. Special precautions for user

Special provisions	163
Special provisions	367
Special provisions	650
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

#### 14.1. UN number

UN number	1263
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	paint related material
----------------------	------------------------

#### 14.3. Transport hazard class(es)

Hazard identification number	30
Class	3
Classification code	F1

#### 14.4. Packing group

Packing group	III
Labels	3

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

#### 14.6. Special precautions for user

Special provisions	163
--------------------	-----

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

11 / 14

# POXY DC

Special provisions	367
Special provisions	650
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

14.1. UN number	
UN number	1263
14.2. UN proper shipping name	
Proper shipping name	paint related material
14.3. Transport hazard class(es)	
Class	3
Classification code	F1
14.4. Packing group	
Packing group	III
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	163
Special provisions	367
Special provisions	650
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1263
14.2. UN proper shipping name	
Proper shipping name	paint related material
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	III
Labels	3
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	163
Special provisions	223
Special provisions	367
Special provisions	955
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable, based on available data

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1263
14.2. UN proper shipping name	
Proper shipping name	paint related material
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	III
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A192
Special provisions	A3
Special provisions	A72
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	10 L

# POXY DC

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
100 %	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC, 2004/37/EC and amendments)

#### 2-methoxy-1-methylethyl acetate

Product name	Skin resorption
2-Methoxy-1-methylethylacetate	Skin

#### REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· hydrocarbons, C9, aromatics · 2-methoxy-1-methylethyl acetate	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· hydrocarbons, C9, aromatics · 2-methoxy-1-methylethyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

#### National legislation Belgium

##### POXY DC

No data available

#### 2-methoxy-1-methylethyl acetate

Résorption peau	Acétate de 2-(1-méthoxy)propyle; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	--

#### National legislation The Netherlands

##### POXY DC

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

13 / 14

# POXY DC

Waterbezwaarlijkheid	B (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

## National legislation France

POXY DC

No data available

### 2-methoxy-1-methylethyl acetate

Risque de pénétration percutanée	Acétate de 2-méthoxy-1-méthyléthyle; Risque de pénétration percutanée
----------------------------------	---

## National legislation Germany

POXY DC

Lagerklasse (TRGS510)	3: Entzündbare Flüssigkeiten
-----------------------	------------------------------

WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

hydrocarbons, C9, aromatics

TA-Luft	5.2.5/I
---------	---------

### 2-methoxy-1-methylethyl acetate

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	2-Methoxy-1-methylethylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

## National legislation United Kingdom

POXY DC

No data available

### 2-methoxy-1-methylethyl acetate

Skin absorption	1-Methoxypropyl acetate; Sk
-----------------	-----------------------------

## Other relevant data

POXY DC

No data available

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 8, 9, 12

Publication date: 2016-03-04

Date of revision: 2021-06-20

Revision number: 0100

BIG number: 57116

14 / 14