



White Supreme Grease

WATERPROOF AND HEAT RESISTANT GREASE

- ✓ Unique 360° jet spray. Can be applied at any angle.
- ✓ Good penetrating characteristics.
- ✓ Reduces friction and wear to a minimum.
- ✓ Cannot be rinsed away, not even with hot water.
- ✓ Does not dry out, does not harden.
- ✓ Prevents corrosion.
- ✓ Excellent for high and low temperature applications (between -35°C and +185°C)
- ✓ Contains no acids.
- ✓ Safe on plastics and rubber.
- ✓ Excellent for hard to reach areas, subject to heat and moisture.

Technical Info

- Appearance: white grease in aerosol.
- Base: calcium.
- Specific weight at 20°C: 1.120 g/cm³ DIN51757.
- Flow temperature: 185°C.
- Solidification temperature: -35°C.
- 4 Ball test DIN 51350: 300-320 kg.
- Water resistance DIN 51807 at +90°C: total.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

White Supreme Grease - aerosol 400ml 231111000

Product [WSG]

Characteristics

White Supreme Grease is a multi-purpose heavy-duty lubricant, based on calcium. It is easy to use, the spray can deliver an even coverage, prevents waste and contamination. White Supreme Grease has a high penetrating capacity. The product flows out as a thin oil which then becomes a grease. The premium quality gives a superior film strength and very high water and temperature resistance.

Applications

Especially adapted for use on:

- hinges
- window-slides
- lock mechanisms
- machine parts and chains

Cars

- window-slides, locks, hinges, windscreen wipers and wiper motors, clutches, brakes, gas regulators, heater cocks, wheel bearings, water pumps, generator bearings, ...

Motorcycles - bicycles

- clutch and gas regulators, rev. counters and speedometer cables, driving chains, gearings, pedals, ball-bearings, bicycle gears,

Industry

- everywhere where the exposure to heat, water or dampness is frequent.
- for ventilators, gears, bearings, conveyors,

Use
