

Lubrifine

FINE MACHINE OIL

- 100% pure high quality mineral oil.
- Replaces oiling can.
- Ideal for fine atomized lubrication on hard to reach areas.
- Appropriate for lubrication of pneumatic tools.
- No more flowing out, leaking and refilling.

## **Technical Info**

- Basis: mineral naphtenic oil.
- Kinematic viscosity: at 40°C : 26.1; at 100°C : 3.9. Pour point: -33°C.
- Shelf life: 24 months, keep dry, cool and frost-
- proof. Safety measures: consult the Safety Data Sheet.

### Packing

Lubrifine - aerosol 400ml

231121000

# Product [LBF]

### Characteristics

- · A low viscosity mineral lubricating oil of high quality. Due to its low viscosity and high penetrating capacity, it may be used perfectly on areas where a normal lubricating oil cannot be used.
- A high quality universal lubricant. It offers an easy, accurate and economical lubrication, on all types of machines, small bearings with a light load, ...
- Replaces the traditional oiling can in workshops, garages and on the road and is appropriate for the daily lubrication of pneumatic tools.

novatio

### Applications

- All types of machines.
- Small bearings with a light load. •
- Classic oil injector in workshops, garages, ....
- Lubrication of pneumatic equipment.

Use