



NSP-2700

Novaquaspray

VERSATILE PROTECTION AND SEALING

- ✓ Quick sealing of water leaks.
- ✓ Protect metal against corrosion.
- ✓ Repaintable rubber film.
- ✓ For indoor and outdoor use.

Technical Info

- Composition: SBR: styrene butadiene rubber; bitumen and silicone free.
- Odour: solvent.
- Colour: grey.
- Chemical resistance: sea water, oil, weak bases and weak acids.
- Repaintable: after 20 minutes.
- Drying time: 2 - 4 hours.
- Temperature resistance: from -50°C to +100°C.
- Shelf-life: 24 months in the original packaging, if stored in a cool, dry place.

Packing

NSP-2700 Novaquaspray grey - aerosol 400ml	602000000
--	-----------

Product [NSP-2700]

Characteristics

Novaquaspray seals leaks in most materials. It is a spray rubber with a high adhesion and fast curing properties. After drying for 20 minutes, Novaquaspray is perfectly watertight, forming a flexible, waterproof elastomer film once it has fully cured.

Applications

- Seals leaks in roofs, gutters and drains.
- Protects metals against corrosion.
- Protects timber that is exposed to moisture and in contact with soil.
- Closes cracks in bodywork, caravans, mobile homes, etc.

Use

- Shake can well before use.
 - Apply onto a clean, stable and dry substrate. If necessary, clean with Safety Clean and/or Multifoam.
 - Apply from a distance of 25 cm. Observe a pause between coats in order to build up the required thickness.
- Test the adhesion to plastics, powder coatings, exotic woods and bituminous materials. Repaintable after 20 minutes. May be cleaned with Safety Clean. Do not use in ponds; Novaquaspray is not water pressure resistant.

