



# Seal & Bond Flex-Sil

Adhesives and sealants

## S

LIQUID, NON-HARDENING GASKET

- ✓ Quick start-up: 10 to 15 minutes.
- ✓ Also easy to install vertically.
- ✓ Resistant to high and low temperatures.
- ✓ For all metals and plastics.

### Technical Info

- Base: polyurethane.
- Colour: red.
- Isocyanate and silicone free.
- Resistant to: all mineral and synthetic oils, greases, fuel, diesel, petrol, water, sea water, gas, air, coolant, antifreeze, ...
- Temperature resistance: from -55°C to +270°C, with peaks up to +300°C.
- Shelf life: 60 months, keep dry, cool and frost-free.

### Packing

Seal & Bond Flex-Sil S red - cartridge 200ml      570005000

### Product [SBFS]

#### Characteristics

Seal & Bond Flex-Sil S is a singlecomponent sealant that does not harden, is easy to remove, which provides the perfect sealing solution. Seal & Bond Flex-Sil S replaces other seals or improves them and can therefore be universally used for clearances up to 0.2 mm. Seal & Bond Flex-Sil S is ideal for applications with different combinations of materials subject to temperature fluctuations and movements.

#### Applications

- Suitable for applications such as in gear boxes and crankcases, flange joints, oil pans, and differentials.
- Application areas: automotive, chemical, and petrochemical industry, gas, water, and power plants.

### Use

- Clean and degrease material requiring sealing using Safety Clean or Kleenspray-S.
- Apply sufficient Seal & Bond Flex-Sil S and let evaporate for 10 minutes before attaching.
- Observe a drying time of 10 to 15 minutes before putting into operation.