

Shock Spray

THE CHEMICAL WRENCH

- ✓ Releases rusted connections in a few seconds thanks to the cold shrink effect.
- ✓ Contains no oil, no fats or acids and leaves no residue.
- ✓ Can be painted immediately.



Technical Info

- Composition: alcohol with biologic degradable oils and anti-corrosion additives.
- Flashpoint °C: +13.
- Specific weight: 0,82 g/ml.
- Propellant: ozone safe.
- Shelf life: 24 months, keep dry, cool and frost-proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Shock Spray - aerosol 400ml

261001000

Product [SCK]

Characteristics

Shock Spray performs where ordinary mineral oil based products fail, and where the screw connections so far could not be loosened other than mechanically: (angel grinder, welding or cutting torches). Its highly effective performance within seconds is based on 2-fold function: when applied Shock Spray generates a chill (cooling) and shrinkage effect on the rusted or corroded parts. This along with its high capillary penetration properties, permits the product to penetrate deeply even into the smallest gaps.

Applications

Shock Spray can be used on bolts, nuts, hinges, ball bearings and all rusted applications in all industrial and maintenance sectors.

Use

- Apply and allow to react 10 counts.
- Loosen with suitable tools.

