novatio



Novalube

THE BEST SOLUTION FOR RUST, CORROSION AND WEAR PROBLEMS

- Contains no nickel special blend of metal powders.
- Resists high pressure (2300 kg/cm²).
- Extreme temperature range (-180°C / +1200°C).
- Prevents galvanic action and corrosion.
- Unique lubrication characteristics reduces friction and wear Ball bearing effect.
- Resists water, chemical vapours, salt, solvents, atmospheric action, etc.
- Prevents seizing. Even in extreme circumstances, the viscosity does not change.
- Saves time and money.
- Simplifies assembly and disassembly.
- Economical in use.

Technical Info

- Solidity: NLGI Class 1 test method.
- Specific weight at 20°C: 1.6 g/cm³ DIN 51757.
- Pressure test: 4000 N VKA TEST.
- Flow temperature: 1200°C.
- Freezing temperature: -180°C.
- Water resistance test according to DIN 51807-1.
 Shelf life: 24 months, keep dry, cool and frost-
- proof.
- Safety measures: consult the Safety Data Sheet.

Packing

Novalube - tube 10gr	221000000
Novalube - pot 120gr	221002000
Novalube - can 450gr	221302000
Novalube - pot 1,8kg	221404000
Novalube - aerosol 100ml	221001000
Novalube - aerosol 400ml	221101000

Product [NLB]

Characteristics

- A protective and lubricating compound made of micronized pure metal particles and a synthetic carrier which protects against corrosion and oxidation.
- Penetrates the smallest pores and crevices of the metal and forms a fine dividing film that is protective and long lasting. Assembled units can be easily taken apart with standard tools, even after years. There are no more problems with corrosion or seizure.
- A heat conductor. It resists temperatures ranging from -180°C to +1200°C and withstands exposure to water, salt water, acids, caustic solutions, vapours, gases, oils, most chemical products and solvents. It may not be used on oxygen or acetylen installations.
- Is non-toxic, it does not contain any lead or nickel. Novalube seals, does not drip and is very economical in use.

Applications

Multiple uses in the following areas:

Steel, paper, chemical, gas works, refineries and petrochemical plants, power plants, the automobile industry, in the production of sanitary installations, water treatment equipment, workshops for the repair of engines, equipment for road construction, maintenance shops, garages, the food and packaging industry, marine workshops, mines, glass factories,



