



Trimfix

UNIVERSAL SPRAY GLUE

- ✓ Ideal for bonding of large surfaces.
- ✓ Heat, cold and moisture resistant, and does not dry.
- ✓ Ideal for permanent or temporary bonding.

Technical Info

- Basis: synthetic rubber in a solution.
- Specific weight: 0,77 kg/dm³.
- Solid materials: 22,5 - 24,5%.
- Viscosity: 100-300 Cps at 20°C.
- Colour: milky white.
- Drying time: ca. 5 minutes at 20°C.
- Open working time: max. 45 minutes.
- Temp. resistance: 80°C constant - peak load: 100°C.
- Consumption: 1,5 to 2 m² per aerosol (onesided).
- Detergent: Novatio Safety Clean.
- Shelf life: 36 months, keep dry, cool and frost-free
- Safety measures: consult the Safety Data Sheet

Packing

Trimfix - aerosol 500ml

511001000

Product [TFX]

Characteristics

Trimfix is an air spray adhesive based on synthetic rubber. Trimfix offers a wide variety of applications. Trimfix bonds durably, quick and without any strings or dripping. Trimfix is appropriate for bonding large surfaces where a thin and transparent glue is recommended.

Applications

Is suitable for gluing: paper, textile, cardboard, foam plastics, polyurethane, cork, polystyrene, felt, vinyl, plastic foil, reproductions... to glass, metal, ceramics, wood, concrete, ...

Use

- Shake before use.
- Apply on a clean, dry substrate; if necessary, clean with Multif foam and/or Safety Clean first.
- Spray a thin, even film on the surface. In the case of porous materials, spray on one side and immediately join the two surfaces together; in the case of smooth materials, spray on both surfaces and allow to dry for +/- 3 minutes before bonding them together.
- After use, empty the spray head by holding the can upside down.

Use Trimfix WT on very porous materials. Remove excess glue using Novatio Safety Clean.

