



Megaclean

CLEANING, DELUTING AND ETCHING OF EPOXY RESIN

- Super strong and fast evaporating cleaner.
- Ideal etching agent before glueing, for lacquers,
- Diluent for epoxys.

Technical Info

- · Ccomposition: butanone.
- · Colour: colourless.
- · Odour: charcateristic.
- · Vapour pressure at 20°C (hPa): 105.
- · Boiling point: 80°C.
- · Solidification point: -86°C.
- Flash point: -4°C.
- · Soluble in: water, alcohol, ether.
- Density at 20°C: 0,804 0,808 kg/l (ASTMD 4052).
- Shelf life: 36 months, keep dry, cool and frostproof.
- · Safety measures: consult the Safety Data Sheet.

Packing

 Megaclean - bottle 1I
 689001000

 Megaclean - can 5L
 689005000

Product [MCL]

Characteristics

- Strong cleaner and solvent, ideal for cleaning tools after working with epoxy resin.
- Excellent diluent for epoxys, for a better impregnation in porous materials.
- Excellent etching agent before glueing, for lacquers and reparations on old epoxy coatings, industrial coatings and synthetic materials.

Applications

- Ideal to use for the finishing of epoxys and to clean tools.
- · Fluid abrasive for hardened epoxys and hard plastics.
- · Removes hardened polyurethane.

Use

Thinner: add a maximum of 4% Megaclean to the Novatio epoxy resins if thinner is desired.

Etchant: Apply Megaclean on a dry cloth and rub on the surface.

First test the substrate for durability and color fastness.

Safe to use on carbon steel, stainless steel, polyester, aluminum and Teflon.

