

PCO-270 Peelcoat



REMOVABLE PROTECTIVE COATING

- ✓ For use on PVC, glass, metal and powder coating.
- ✓ Easy to apply and remove.
- ✓ For indoor and outdoor use.

Technical Info

- Basis: modified natural resins.
- Appearance: thick liquid emulsion.
- Colour: white.
- Smell: almost odorless.
- pH: 9.
- Density: approx. 1 kg / l.
- Application temperature: + 5 ° C to + 30 ° C.
- Touch dry: 2 to 8 hours.
- Weather resistant: after 6 to 48 hours, depending on T ° and RH.
- Rain resistant: 12 hours after application.
- Minimum total layer thickness: 600 microns.
- Maximum total layer thickness: 1500 microns.
- Maximum protection period: within 12 months and outside 6 months.
- Shelf life: 12 months, stored cool and dry in original packaging.

Packing

PCO-270 Peelcoat - jar 5,5L

115305934

Product [PCO-270]

Characteristics

This fast-drying, solvent-free resin emulsion forms a flexible protective coating. Apply with airless spray equipment or a soft brush. Waterproof and resistant to wind and weather. Peelcoat is completely removable like a film by simply peeling it off, without leaving any residue.

Applications

- Protects against mechanical weathering (such as grinding dust) and the effects of construction chemicals (such as cement).
- Translucent for protecting glass and windows during construction works.

Use

- Protect ventilation grilles, blinds, brushes of sliding windows and other sensitive materials or structures by covering.
- Stir well and apply undiluted on a hand-dry surface at a temperature between + 5 ° C and + 30 ° C, without the prospect of rain or frost within 12 hours. Ventilate well when used indoors.
- Application with airless gun: spray pressure 100-150 bar, opening 0.38 mm to 0.48 mm.
- Apply with a soft brush: in 2 to 3 cross coats. Apply the next layer when the previous one is touch dry (2-8h).
- Check the layer thickness: minimum 0.6mm and maximum 1.5mm.
- Consumption between 0,6 and 1,5 l/m².

- Remove masking tape immediately after applying Peelcoat. Clean tools and spilled product immediately with water.

Maximum protection time: outside 6 months and inside 12 months. Remove Peelcoat before the end of the protection time.

Minimum temperature during removal: +5°C.

Do not use on bluestone, bare wood, plexiglass and rough surfaces. When in doubt, apply to a less visible area and test removal after 24 hours.