

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## SILICON 100 AEROSOL

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : SILICON 100 AEROSOL  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Lubricant

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements



Signal word : Danger

##### H-statements

H222 : Extremely flammable aerosol.  
H229 : Pressurised container: May burst if heated.  
H412 : Harmful to aquatic life with long lasting effects.

##### P-statements

P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 : Do not spray on an open flame or other ignition source.  
P251 : Do not pierce or burn, even after use.  
P273 : Avoid release to the environment.  
P410 + P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

#### 2.3. Other hazards

# SILICON 100 AEROSOL

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
isobutane 01-2119485395-27	75-28-5 200-857-2	30% ≤C<50%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
butane 01-2119474691-32	106-97-8 203-448-7	20% ≤C<30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	10% ≤C<20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
pentane 01-2119459286-30	109-66-0 203-692-4	2.5% ≤C<10%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411 EUH066	(1)(2)(10)	Constituent	
hydrocarbons, C6, isoalkanes, < 5% n-hexane 01-2119484651-34	931-254-9	2.5% ≤C<10%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent	
hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane 01-2119486291-36	926-605-8	2.5% ≤C<10%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411 EUH066	(1)(10)	Constituent	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(21) 1,3-butadiene <0.1%

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, consult a doctor/medical service.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Headache. Nausea. Vomiting. Feeling of weakness. Coordination disorders. Respiratory difficulties. Disturbances of consciousness.

##### After skin contact:

Slight irritation.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

2 / 16

# SILICON 100 AEROSOL

## 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Keep container in a well-ventilated place. Fireproof storeroom. Meet the legal requirements.

#### 7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

# SILICON 100 AEROSOL

## EU

Pentane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	3000 mg/m <sup>3</sup>

## Belgium

Butane, tous isomères: iso-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
Pentane, tous isomères	Time-weighted average exposure limit 8 h	600 ppm
	Time-weighted average exposure limit 8 h	1800 mg/m <sup>3</sup>
	Short time value	750 ppm
	Short time value	2250 mg/m <sup>3</sup>

## The Netherlands

n-Pentaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	600 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1800 mg/m <sup>3</sup>

## France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>
n-Pentane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1000 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	3000 mg/m <sup>3</sup>

## Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Pentan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	3000 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>

## Austria

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m <sup>3</sup>
Pentan (alle Isomeren): n-Pentan Isopentan (2-Methylbutan)	Tagesmittelwert (MAK)	600 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	1200 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

## UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
--------	---	---------

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

4 / 16

# SILICON 100 AEROSOL

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>
Pentane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1800 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
Pentane, all isomers	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	1000 ppm

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### 8.1.2 Sampling methods

Product name	Test	Number
N-PENTANE (HYDROCARBONS, BP 36 TO 126 °C)	NIOSH	1500
n-Pentane (Volatile Organic compounds)	NIOSH	2549
Pentane	OSHA	7

### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 Threshold values

#### DNEL/DMEL - Workers

pentane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	3000 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	432 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5306 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	13964 mg/kg bw/day	

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5306 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	13964 mg/kg bw/day	

#### DNEL/DMEL - General population

pentane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	643 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	214 mg/kg bw/day	
	Long-term systemic effects oral	214 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1131 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	1377 mg/kg bw/day	
	Long-term systemic effects oral	1301 mg/kg bw/day	

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1131 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	1377 mg/kg bw/day	
	Long-term systemic effects oral	1301 mg/kg bw/day	

#### PNEC

pentane

Compartments	Value	Remark
Fresh water	230 µg/l	
Fresh water (intermittent releases)	880 µg/l	
Marine water	230 µg/l	
STP	3600 µg/l	
Fresh water sediment	1.2 mg/kg sediment dw	
Marine water sediment	1.2 mg/kg sediment dw	
Soil	0.55 mg/kg soil dw	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

5 / 16

# SILICON 100 AEROSOL

Observe normal hygiene standards. Do not eat, drink or smoke during work.

**a) Respiratory protection:**

Full face mask with filter type A at conc. in air > exposure limit.

**b) Hand protection:**

Protective gloves against chemicals (EN 374).

**c) Eye protection:**

Eye protection not required in normal conditions.

**d) Skin protection:**

Protective clothing (EN 14605 or EN 13034).

**8.2.3 Environmental exposure controls:**

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	Colourless
Particle size	Not applicable (aerosol)
Explosion limits	1.5 - 11.2 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	Not applicable (aerosol)
Boiling point	No data available in the literature
Relative vapour density	> 1
Vapour pressure	> 1200 hPa ; 20 °C ; Propellant
Solubility	Water ; insoluble
Relative density	0.60 ; 20 °C ; Liquid
Absolute density	600 kg/m <sup>3</sup> ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (non-soluble in water)

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

**Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

Oxidizing agents.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

**Acute toxicity**

**SILICON 100 AEROSOL**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

6 / 16

# SILICON 100 AEROSOL

## pentane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 2000 mg/kg		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (vapours)	LC50		> 20 mg/l air	4 h	Rat (male / female)	Experimental value	

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.354 mg/l	4 h	Rat (male)	Read-across	

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.35 mg/l air	4 h	Rat (male)	Read-across	

## Conclusion

Not classified for acute toxicity

## Corrosion/irritation

### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

## pentane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	Single exposure
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Human observation	24 h		Human	Experimental value	

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405	72 h	72 hours	Rabbit	Read-across	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405	72 h	1; 24; 48; 72 hours	Rabbit	Read-across	
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

## pentane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (female)	Experimental value	

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

7 / 16

# SILICON 100 AEROSOL

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (male / female)	Read-across	

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse	Read-across	

### Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

### Specific target organ toxicity

#### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### pentane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	Dose level	Subacute toxicity test	2000 mg/kg bw/day	Kidney	No adverse systemic effects	4 weeks (5 days / week)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (gases)	NOAEC	OECD 413	20000 mg/m <sup>3</sup>		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation			STOT SE cat.3		Drowsiness, dizziness			Annex VI

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10504 mg/m <sup>3</sup> air		No effect	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 413	31652 mg/m <sup>3</sup> air	Liver; kidney	Organ damage	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10504 mg/m <sup>3</sup>		No effect	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 413	31652 mg/m <sup>3</sup>	Liver; kidney	Impairment/d egeneration	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	31652 mg/m <sup>3</sup>		No effect	13 weeks (6h / day, 5 days / week)	Rat (female)	Read-across
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Literature study

### Conclusion

Not classified for subchronic toxicity

### Mutagenicity (in vitro)

#### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### pentane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

8 / 16



# SILICON 100 AEROSOL

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Read-across	

## Mutagenicity (in vivo)

### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

pentane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	EU Method B.12	13 weeks (6h / day, 5 days / week)	Rat (male / female)		Experimental value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

pentane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Unknown								Data waiving

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9016 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	3000 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	No carcinogenic effect		Experimental value
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	Weight changes	Liver	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (male)	No carcinogenic effect		Experimental value

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### SILICON 100 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

9 / 16

# SILICON 100 AEROSOL

## pentane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL (P)	OECD 414	1000 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC (P/F1)	Equivalent to OECD 416	24.08 mg/m <sup>3</sup>		Rat (male / female)	No effect		Read-across

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	> 7000 ppm	10 days (6h / day)	Rat	No effect		Read-across
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h / day)	Rat (female)	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm		Rat (male / female)	No effect		Read-across

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	3000 ppm	10 days (6h / day)	Mouse	No effect		Read-across
	LOAEC	Equivalent to OECD 414	9000 ppm	10 days (6h / day)	Mouse	Minor skeletal variations	Skeleton	Read-across
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	900 ppm	10 days (6h / day)	Rat	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm	13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

## Conclusion

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

### SILICON 100 AEROSOL

#### hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation	NOAEC	Equivalent to OECD 424	9000 ppm	Central nervous system	Overall effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

#### hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Skin				Skin	Skin dryness or cracking			Literature study

## Chronic effects from short and long-term exposure

### SILICON 100 AEROSOL

No effects known.

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### SILICON 100 AEROSOL

No (test) data on the mixture available

Classification is based on the relevant ingredients

# SILICON 100 AEROSOL

## pentane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	4.26 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50		2.7 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value
Toxicity algae and other aquatic plants	ErC50	OECD 201	10.7 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
	NOEC	OECD 201	7.51 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		6.165 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Growth rate
Long-term toxicity aquatic crustacea	NOELR		10.76 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Reproduction
Toxicity aquatic micro-organisms	EL50		105.9 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		18.27 mg/l	96 h	Oncorhynchus mykiss		Fresh water	QSAR
Acute toxicity crustacea	EL50		31.9 mg/l	48 h	Daphnia magna		Fresh water	QSAR
Toxicity algae and other aquatic plants	EL50		13.56 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	QSAR
Long-term toxicity fish	NOELR		4.089 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		7.138 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

Classification of this substance is debatable as it does not correspond to the conclusion from the test

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	12 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50		17.06 mg/l	48 h	Daphnia magna		Fresh water	QSAR; Locomotor effect
Toxicity algae and other aquatic plants	EL50	OECD 201	55 mg/l	72 h	Pseudokirchneriella subcapitata	Static system		Experimental value; Growth rate
Long-term toxicity fish	NOELR		2.187 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Growth rate
Long-term toxicity aquatic crustacea	NOELR		3.818 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Reproduction
Toxicity aquatic micro-organisms	EL50		37.91 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth inhibition

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

## Conclusion

Harmful to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

### pentane

#### Biodegradation water

Method	Value	Duration	Value determination
Equivalent to OECD 301F	87 %; Oxygen consumption	28 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
	3.95 day(s)	5E5 /cm <sup>3</sup>	Calculated value

### hydrocarbons, C6, isoalkanes, < 5% n-hexane

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Read-across

### hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Experimental value

## Conclusion

### Water

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

11 / 16

# SILICON 100 AEROSOL

Does not contain any not readily biodegradable component(s)

## 12.3. Bioaccumulative potential

### SILICON 100 AEROSOL

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

pentane

#### Log Kow

Method	Remark	Value	Temperature	Value determination
		3.45	25 °C	Experimental value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

#### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		501.187		Pimephales promelas	Calculated value

#### Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		3.34	20 °C	Read-across

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

#### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	35.8 l/kg - 552 l/kg			QSAR

#### Log Kow

Method	Remark	Value	Temperature	Value determination
		3.6	20 °C	Conclusion by analogy

#### Conclusion

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

pentane

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		2.9	QSAR

hydrocarbons, C6, isoalkanes, < 5% n-hexane

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	Calculated value

#### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	93.6 %	0 %	2.1 %	0.5 %	3.8 %	Calculated value

hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		2.5 - 3.16	QSAR

#### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	97 %	0 %	1 %	0.7 %	1.5 %	Calculated value

#### Conclusion

Contains component(s) that adsorb(s) into the soil  
Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### SILICON 100 AEROSOL

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

# SILICON 100 AEROSOL

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 06\* (waste engine, gear and lubricating oils: synthetic engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

UN number	1950
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

#### 14.4. Packing group

Packing group	
Labels	2.1

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

#### 14.1. UN number

UN number	1950
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

#### 14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

#### 14.4. Packing group

Packing group	
Labels	2.1

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Inland waterways (ADN)

#### 14.1. UN number

UN number	1950
-----------	------

# SILICON 100 AEROSOL

14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Marine pollutant	-
	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	277
	Special provisions	327
	Special provisions	344
	Special provisions	381
	Special provisions	63
	Special provisions	959
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	A145
	Special provisions	A167
	Special provisions	A802
Passenger and cargo transport	Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
67.5 % - 100 %	

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

14 / 16

# SILICON 100 AEROSOL

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> <li>· pentane</li> <li>· hydrocarbons, C6, isoalkanes, &lt; 5% n-hexane</li> <li>· hydrocarbons, C6-C7, isoalkanes, cyclics, &lt; 5% n-hexane</li> </ul>	<p>Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>1. Shall not be used in:</p> <ul style="list-style-type: none"> <li>— ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,</li> <li>— tricks and jokes,</li> <li>— games for one or more participants, or any article intended to be used as such, even with ornamental aspects,</li> </ul> <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none"> <li>— can be used as fuel in decorative oil lamps for supply to the general public, and,</li> <li>— present an aspiration hazard and are labelled with H304,</li> </ul> <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p>
<ul style="list-style-type: none"> <li>· pentane</li> <li>· hydrocarbons, C6, isoalkanes, &lt; 5% n-hexane</li> <li>· hydrocarbons, C6-C7, isoalkanes, cyclics, &lt; 5% n-hexane</li> </ul>	<p>Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> <li>— metallic glitter intended mainly for decoration,</li> <li>— artificial snow and frost,</li> <li>— "whoopie" cushions,</li> <li>— silly string aerosols,</li> <li>— imitation excrement,</li> <li>— horns for parties,</li> <li>— decorative flakes and foams,</li> <li>— artificial cobwebs,</li> <li>— stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>"For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>

## National legislation Belgium

SILICON 100 AEROSOL

No data available

## National legislation The Netherlands

SILICON 100 AEROSOL

Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

## National legislation France

SILICON 100 AEROSOL

No data available

## National legislation Germany

SILICON 100 AEROSOL

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

15 / 16

# SILICON 100 AEROSOL

## pentane

TA-Luft	5.2.5/I
TRGS900 - Risiko der Fruchtschädigung	Pentan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

## hydrocarbons, C6, isoalkanes, < 5% n-hexane

TA-Luft	5.2.5/I
---------	---------

## hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

TA-Luft	5.2.5/I
---------	---------

### **National legislation Austria**

#### SILICON 100 AEROSOL

No data available

### **National legislation United Kingdom**

#### SILICON 100 AEROSOL

No data available

### **Other relevant data**

#### SILICON 100 AEROSOL

No data available

## **15.2. Chemical safety assessment**

No chemical safety assessment has been conducted for the mixture.

## **SECTION 16: Other information**

### **Full text of any H- and EUH-statements referred to under section 3:**

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2, 4, 8, 9

Publication date: 2001-09-25

Date of revision: 2022-04-20

Revision number: 0800

BIG number: 36225

16 / 16