



Butaseal

DOUBLE-SIDED ADHESIVE ON ROLL BASED ON FLEXIBLE BUTYL RUBBER

- ✓ Very high "immediate" bonding strength.
- ✓ For both bonding and sealing.
- ✓ Temperature resistant from -30°C to +80°C.
- ✓ Remains flexible, does not harden.
- ✓ Follows perfectly the unevennesses of the substrate.
- ✓ Well mouldable.
- ✓ For both permanent and temporary fixings.
- ✓ Easy and clean application.
- ✓ Very good adhesion, also on "difficult" materials.
- ✓ Available in black and grey.

Technical Info

Butaseal Black:

- Thickness: 1,5 mm.
- Width: 15 mm.
- Length/roll: 25 m.
- 180° Peel adhesion: 20 N/cm.
- 180° Peel adhesion at +5°C on concrete: 17 N/cm.
- Probe Tack: 8 N.
- Application temperature: between 0°C and +40°C.
- Temperature resistance: from -30°C to +90°C.

Butaseal Grey:

- Thickness: 1 mm.
- Width: 25 mm.
- Length/roll: 35 m.
- Mass/m²: 1600g/m².
- Tensile strength 100 mm/min.: 0.19 Mpa.
- Shear strength 10 mm/min.: 0.026 Mpa.
- Flow at 70°C: 0%.
- Application temperature: between +5°C and +35°C.
- Temperature resistance: from -30°C to +80°C.

Shelf life: 24 months, keep dry, cool and frost-free.

Packing

Product

Characteristics

- A double-sided adhesive and sealing band on roll.
- Remains flexible and does not harden due to its unique composition based on modified butylene rubbers.
- Offers a very high immediate bonding strength, even on materials that are difficult to bond. Due to its flexible composition,
- Adapts itself perfectly to any substrate and can be used perfectly in combination with one-component adhesives that harden much 'slower'.

Applications

Industry

- flexible bonding - temporary or permanent - also on difficult materials
- gives an immediate adhesion in combination with Seal & Bond MS60
- sealing of wire and cable passages
- prevents galvanic action in metal constructions
- prevents vibrations
- makes water- and dampproof
- bonding and sealing of PE foil
- "instant" sealing on difficult places
- as mouldable mastic for problematic cases

Automotive

- bonding of plastic foil in doors and roof covering
- sealing of front mudguards and bodywork parts

Butaseal black - roll 15mm / 25m	551158000
Butaseal grey- roll 25mm / 35m	552258000

- ideal for eliminating vibrations
- sealing of cable passages, rear lights, surface mounted sliding roofs
- fixing of upright decorative frames
- waterproof mounting of antennas

Use

First test foundations based on PE, PP, silicones and bitumen for adhesion.