


Novatex Tape HM



TEXTILE TAPE WITH A VERY HIGH IMMEDIATE ADHESIVE POWER

- ✓ Very fast adhesion thanks to the hotmelt glue.
- ✓ Adheres to most materials and is repositionable.
- ✓ Temperature resistant up to 70 ° C.

Technical Info

- Thickness of the tape: +/- 0.21 mm.
- Thickness of the glue: +/- 80 micron.
- Tensile strength: 6,5 KN/m test method GB 7753-87.
- Temperature resistance: -15°C to +70°C.
- Elasticity: 25%.
- Rolling Ball Tack: 4 test method GB 7125-84.
- Adhesiveness: > 12 hrs test method GB 4851-84.
- Colour: yellow.
- First test foundations based on PE, PP, silicones and bitumen for adhesion.
- Shelf life: 36 months, keep dry, cool and frost-proof.

Packing

Novatex Tape HM yellow - roll 50mm / 50m 561038000

Product [NTX-HM]

Characteristics

- A fine woven textile tape provided with a strong hotmelt glue, with a very high immediate adhesive power.
- Easy to tear, even lengthwise.

Applications

- sealing of air ducts and other ducts.
- bundling cables.
- repairing tarpaulins, suction hoses,
- holding objects during bonding.
- temporary fixings - stand construction.
- temporary sealing of window and door openings.
- protecting sharp corners and edges.