

MBT-110 Muntin Bar Tape

Tapes



DOUBLE-SIDED MOUNTING TAPE FOR GLASS AND CROSSBARS

- ✓ Adheres to glass, aluminium and powder coatings.
- ✓ Absorbs dilatation differences in case of temperature fluctuations.
- ✓ Long-term UV-resistant.

Technical Info

- Adhesive: acrylic.
- Carrier: PE foam.
- Protective film: polyethylene.
- Colour: black.
- Thickness: 0.4 mm.
- Pressure sensitive: hardens by pressing.
- Processing temperature between +5°C and +35°C.
- Temperature resistance: -40°C to +100°C (peak up to +150°C).
- Shear strength (static, after 72 hrs): 72 N/cm².
- Tensile strength (after 72 hrs): 120 N/cm².
- Density: 100 kg/m².
- Shelf life: 36 months, dry, cool and frost-free.

Packing

MBT-110 Muntin Bar Tape - black - roll 12mm x 66m	554130390
MBT-110 Muntin Bar Tape - black - roll 19mm x 66m	554131390

Product [MBT-110]

Characteristics

Double-sided acrylic tape, suitable for indoor and outdoor use. The PE foam core compensates for differences in expansion. Resistant to extreme temperatures, high UV load, air pollution, salt spray, ...

Applications

- Bonding of crossbars on windows.
- Installation of reveals and small sash covers.
- Bonding of blind panels and profiles.

Use

- Apply to clean and dry surface, if necessary clean with Safety Clean and/or Multifoam.
- Remove protective foil, join the parts together and press firmly.

High immediate strength. Heating up the bonded parts (up to +65°C) accelerates the force build-up.

First test substrates based on PE, PP, silicones and bitumen for adhesion. Treating difficult plastics and powder coatings with Seal&Bond Special Primer can improve the adhesion, as can increasing the adhesion surface by sanding.