

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## TIP TAP AEROSOL

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : TIP TAP AEROSOL  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Cutting oil

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.

#### 2.2. Label elements



**Signal word** Danger

**H-statements**  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**P-statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard  
Caution! Substance is absorbed through the skin

# TIP TAP AEROSOL

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5 265-155-0	C≥25%	Asp. Tox. 1; H304	(1)(10)	Constituent	
distillates (petroleum), hydrotreated heavy paraffinic 01-2119484627-25	64742-54-7 265-157-1	C≤30%	Asp. Tox. 1; H304	(1)(2)(6)(10)	Constituent	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, consult a doctor/medical service.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Soap may be used.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

No effects known.

##### After skin contact:

No effects known.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

#### 5.3.2 Special protective equipment for fire-fighters:

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

2 / 13

# TIP TAP AEROSOL

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Store in a cool area. Keep container in a well-ventilated place. Protect against frost. Keep out of direct sunlight. Fireproof storeroom.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### Belgium

Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m <sup>3</sup>
	Short time value	10 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

#### The Netherlands

Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m <sup>3</sup>
---------------------------	---	---------------------

#### Germany

Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup> (1)

(1) UF: 4 (II)

# TIP TAP AEROSOL

## Austria

Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Mineral oil, excluding metal working fluids: Pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m <sup>3</sup> (1)
Propane	See Appendix F: Minimal Oxygen Content; Simple asphyxiant, Explosion hazard	

(1) (I): Inhalable fraction

### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

Product name	Test	Number
Oil Mist (Mineral)	NIOSH	5026
Petroleum Distillates Fractions	OSHA	48

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

##### DNEL/DMEL - Workers

distillates (petroleum), hydrotreated heavy naphthenic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.73 mg/m <sup>3</sup>	
	Long-term local effects inhalation	5.58 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.97 mg/kg bw/day	

distillates (petroleum), hydrotreated heavy paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.73 mg/m <sup>3</sup>	
	Long-term local effects inhalation	5.58 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.97 mg/kg bw/day	

##### DNEL/DMEL - General population

distillates (petroleum), hydrotreated heavy naphthenic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	0.74 mg/kg bw/day	

distillates (petroleum), hydrotreated heavy paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	0.74 mg/kg bw/day	

##### PNEC

distillates (petroleum), hydrotreated heavy paraffinic

Compartments	Value	Remark
Oral	9.33 mg/kg food	

#### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

# TIP TAP AEROSOL

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Colour	Brown
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	No data available in the literature
Boiling point	-42 °C ; Propellant
Flammability	Extremely flammable aerosol.
Explosion limits	2.1 - 9.5 vol % ; Propellant
Flash point	Not applicable (aerosol)
Auto-ignition temperature	No data available in the literature
Decomposition temperature	No data available in the literature
pH	Not applicable (non-soluble in water)
Kinematic viscosity	110 mm <sup>2</sup> /s ; 20 °C ; Liquid
Dynamic viscosity	100 mPa.s ; 20 °C ; Liquid
Solubility	Water ; insoluble
Log Kow	Not applicable (mixture)
Vapour pressure	8530 hPa ; 20 °C ; Propellant
Absolute density	900 kg/m <sup>3</sup> ; Liquid
Relative density	0.90 ; Liquid
Relative vapour density	> 1
Particle size	Not applicable (aerosol)

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### TIP TAP AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients  
distillates (petroleum), hydrotreated heavy naphthenic

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Skin	LD50	OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	OECD 403	> 5.53 mg/l	4 h	Rat (male / female)	Read-across	

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

5 / 13

# TIP TAP AEROSOL

distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	OECD 403	> 5.53 mg/l air	4 h	Rat (male / female)	Read-across	

## Conclusion

Not classified for acute toxicity

## Corrosion/irritation

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment with rinsing
Skin	Not irritating	Equivalent to OECD 404	24 h	24; 48; 72 hours	Rabbit	Read-across	

## Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male)	Read-across	
Skin	Not sensitizing	Human observation			Human (male / female)	Experimental value	

## Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

## Specific target organ toxicity

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	LOAEL	Equivalent to OECD 408	125 mg/kg bw/day	General (overall effects)	13 weeks (5 days / week)	Rat (male)	Read-across	
Dermal	NOAEL systemic effects	OECD 410	1000 mg/kg bw/day	No adverse systemic effects	4 weeks (6h / day, 3 days / week)	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	NOEL	Equivalent to OECD 412	220 mg/m <sup>3</sup> air	Lungs (no effect)	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	
Inhalation (aerosol)	NOAEC systemic effects	Equivalent to OECD 412	> 980 mg/m <sup>3</sup> air	No adverse systemic effects	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

6 / 13

# TIP TAP AEROSOL

distillates (petroleum), hydrotreated heavy paraffinic

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)		Read-across	
Positive with metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Read-across	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)		Read-across	

## Mutagenicity (in vivo)

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy paraffinic

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow (no effect)	Read-across	Single intraperitoneal injection

### Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal		Equivalent to OECD 451		No carcinogenic effect	78 week(s)	Mouse (female)	Read-across	

### Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### TIP TAP AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy paraffinic

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Developmental toxicity (Dermal)	LOAEL	Equivalent to OECD 414	125 mg/kg bw/day	20 days (gestation, daily)	Rat	Embryotoxicity and fetotoxicity	Read-across	
Maternal toxicity (Dermal)	LOAEL	Equivalent to OECD 414	8 mg/kg bw/day	20 days (gestation, daily)	Rat	Maternal toxicity	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 421	≥ 1000 mg/kg bw/day		Rat (male / female)	No effect	Read-across	

### Conclusion

Not classified for reprotoxic or developmental toxicity

## Aspiration hazard

### TIP TAP AEROSOL

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

## Toxicity other effects

### TIP TAP AEROSOL

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

### TIP TAP AEROSOL

No effects known.

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

7 / 13

# TIP TAP AEROSOL

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### TIP TAP AEROSOL

No (test) data on the mixture available

Judgement of the mixture is based on the relevant ingredients

distillates (petroleum), hydrotreated heavy naphthenic

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 100 mg/l WAF	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	Equivalent to OECD 202	> 10000 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l WAF	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		≥ 1000 mg/l	14 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEL	OECD 211	10 mg/l WAF	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Nominal concentration

distillates (petroleum), hydrotreated heavy paraffinic

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 100 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	Equivalent to OECD 202	> 10000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		≥ 1000 mg/l	14 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEL	OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

#### Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

### 12.2. Persistence and degradability

distillates (petroleum), hydrotreated heavy paraffinic

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	31 %; Oxygen consumption	28 day(s)	Experimental value

#### Conclusion

##### Water

Contains non readily biodegradable component(s)

### 12.3. Bioaccumulative potential

#### TIP TAP AEROSOL

##### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

distillates (petroleum), hydrotreated heavy naphthenic

#### BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	79 l/kg; Fresh weight			Estimated value

##### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			



# TIP TAP AEROSOL

distillates (petroleum), hydrotreated heavy paraffinic

## Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available in the literature			

## Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

## 12.4. Mobility in soil

distillates (petroleum), hydrotreated heavy naphthenic

### (log) Koc

Parameter	Method	Value	Value determination
log Koc		1.7 - 15	Calculated value

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	3.1 %		1.5 %	39 %	56 %	Calculated value

## Conclusion

No (test)data on mobility of the component(s) available

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### TIP TAP AEROSOL

#### Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)  
None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

distillates (petroleum), hydrotreated heavy naphthenic

#### Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Groundwater

Groundwater pollutant

distillates (petroleum), hydrotreated heavy paraffinic

#### Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.  
Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04\* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

9 / 13

# TIP TAP AEROSOL

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

## Rail (RID)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

## Inland waterways (ADN)

14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

## Sea (IMDG/IMSBC)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	
	2.1

# TIP TAP AEROSOL

## 14.4. Packing group

Packing group	
Labels	2.1

## 14.5. Environmental hazards

Marine pollutant	-
Environmentally hazardous substance mark	no

## 14.6. Special precautions for user

Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

## 14.7. Maritime transport in bulk according to IMO instruments

Annex II of MARPOL 73/78	Not applicable
--------------------------	----------------

## Air (ICAO-TI/IATA-DGR)

### 14.1. UN number or ID number

UN number/ID number	1950
---------------------	------

### 14.2. UN proper shipping name

Proper shipping name	aerosols, flammable
----------------------	---------------------

### 14.3. Transport hazard class(es)

Class	2.1
-------	-----

### 14.4. Packing group

Packing group	
Labels	2.1

### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

### 14.6. Special precautions for user

Special provisions	A145
Special provisions	A167
Special provisions	A802

### Passenger and cargo transport

Limited quantities: maximum net quantity per packaging	30 kg G
--	---------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
18 %	
153 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

REACH Candidate list

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· distillates (petroleum), hydrotreated heavy naphthenic · distillates (petroleum), hydrotreated heavy paraffinic	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

11 / 13

# TIP TAP AEROSOL

types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;  
 (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;  
 (c) hazard class 4.1;  
 (d) hazard class 5.1.

with ornamental aspects,  
 2. Articles not complying with paragraph 1 shall not be placed on the market.  
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  
 — can be used as fuel in decorative oil lamps for supply to the general public, and,  
 — present an aspiration hazard and are labelled with H304,  
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  
 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  
 a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";  
 b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  
 c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.

## National legislation Belgium

### TIP TAP AEROSOL

No data available

## National legislation The Netherlands

### TIP TAP AEROSOL

Waterbezwaarlijkheid	A (4); Algemene Beoordelingsmethodiek (ABM)
distillates (petroleum), hydrotreated heavy paraffinic	
SZW - Lijst van mutagene stoffen	aardoliegassen en residuen; Opgenomen in SZW-lijst van mutagene stoffen

## National legislation France

### TIP TAP AEROSOL

No data available

## National legislation Germany

### TIP TAP AEROSOL

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

## National legislation Austria

### TIP TAP AEROSOL

No data available

## National legislation United Kingdom

### TIP TAP AEROSOL

No data available

## Other relevant data

### TIP TAP AEROSOL

No data available

distillates (petroleum), hydrotreated heavy paraffinic	
TLV - Carcinogen	Mineral oil, excluding metal working fluids: Pure, highly and severely refined; A4

## 15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H229 Pressurised container: May burst if heated.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %

Reason for revision: 2; 3

Publication date: 2001-02-22

Date of revision: 2024-07-08

Revision number: 900

BIG number: 33710

12 / 13

# TIP TAP AEROSOL

EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.